

# SAFETY DATA SHEET

## 1. Identification

**Material name:** ELS 2 GL  
**Material:** 360620 802

### Recommended use and restriction on use

**Recommended use:** Coatings  
**Restrictions on use:** Not known.

### Manufacturer/Importer/Supplier/Distributor Information

Tremco Incorporated  
3735 Green Road  
BEACHWOOD OH 44122  
US

**Contact person:** EH&S Department  
**Telephone:** 216-292-5000  
**Emergency telephone number:** 1-800-424-9300 (US); 1-613-996-6666 (Canada)

## 2. Hazard(s) identification

### Hazard Classification

#### Health Hazards

Acute toxicity (Inhalation - vapor)	Category 4
Serious Eye Damage/Eye Irritation	Category 2A
Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 1A
Specific Target Organ Toxicity - Repeated Exposure	Category 1 <sup>1</sup>

#### Target Organs

1. Central nervous system

#### Unknown toxicity - Health

Acute toxicity, oral	29.8 %
Acute toxicity, dermal	32.61 %
Acute toxicity, inhalation, vapor	83.9 %
Acute toxicity, inhalation, dust or mist	98.31 %

### Environmental Hazards

Acute hazards to the aquatic environment	Category 3
Chronic hazards to the aquatic environment	Category 3

#### Unknown toxicity - Environment

Acute hazards to the aquatic environment	90.82 %
Chronic hazards to the aquatic environment	90.82 %

## Label Elements

### Hazard Symbol:



**Signal Word:** Danger

**Hazard Statement:** Harmful if inhaled.  
Causes serious eye irritation.  
May cause genetic defects.  
May cause cancer.  
Causes damage to organs through prolonged or repeated exposure.  
Harmful to aquatic life with long lasting effects.

### Precautionary Statements

**Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. Use personal protective equipment as required.

**Response:** IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention.

**Storage:** Store in a well-ventilated place. Keep container tightly closed. Store locked up.

**Disposal:** Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

**Hazard(s) not otherwise classified (HNOC):** None.

## 3. Composition/information on ingredients

### Mixtures

000000022763

Chemical Identity	CAS number	Content in percent (%)*
Asphalt	8052-42-4	20 - <50%
Calcium Carbonate (Limestone)	1317-65-3	10 - <20%
Stoddard solvent (Mineral Spirits)	8052-41-3	10 - <20%
Cellulose	9004-34-6	1 - <5%
Magnesite	546-93-0	1 - <5%
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	0.1 - <1%
Nonane	111-84-2	0.25 - <1%
1,2,4-Trimethylbenzene	95-63-6	0.1 - <1%
Hydrogen sulfide	7783-06-4	0.01 - <0.1%

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### 4. First-aid measures

##### Description of necessary first-aid measures

<b>Inhalation:</b>	Move to fresh air.
<b>Skin Contact:</b>	Wash skin thoroughly with soap and water. Get medical attention if symptoms occur.
<b>Eye contact:</b>	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.
<b>Ingestion:</b>	Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
<b>Personal Protection for First-aid Responders:</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

##### Most important symptoms/effects, acute and delayed

<b>Symptoms:</b>	May cause skin and eye irritation.
<b>Hazards:</b>	No data available.

##### Indication of immediate medical attention and special treatment needed

<b>Treatment:</b>	Symptoms may be delayed.
-------------------	--------------------------

#### 5. Fire-fighting measures

**General Fire Hazards:** No unusual fire or explosion hazards noted.

##### Suitable (and unsuitable) extinguishing media

<b>Suitable extinguishing media:</b>	Use fire-extinguishing media appropriate for surrounding materials.
<b>Unsuitable extinguishing media:</b>	Do not use water jet as an extinguisher, as this will spread the fire.

**Specific hazards arising from the chemical:** During fire, gases hazardous to health may be formed.

**Special protective equipment and precautions for fire-fighters**

**Special fire-fighting procedures:** No data available.

**Special protective equipment for fire-fighters:** Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

## 6. Accidental release measures

**Personal precautions, protective equipment and emergency procedures:** No data available.

**Accidental release measures:** In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

**Methods and material for containment and cleaning up:** Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

**Environmental Precautions:** Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

## 7. Handling and storage

### Handling

**Technical measures (e.g. Local and general ventilation):** Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

**Safe handling advice:** Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with eyes. Wash hands thoroughly after handling.

**Contact avoidance measures:** No data available.

**Hygiene measures:** Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Avoid contact with eyes.

### Storage

**Safe storage conditions:** Store locked up.

**Safe packaging materials:** No data available.

## 8. Exposure controls/personal protection

### Control Parameters

### Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Asphalt - Inhalable fume. - as benzene solubles	TWA	0.5 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2018)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Stoddard solvent (Mineral Spirits)	TWA	100 ppm	US. ACGIH Threshold Limit Values, as amended (2008)
	PEL	500 ppm 2,900 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Cellulose	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (2011)
Cellulose - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Cellulose - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Cellulose - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Cellulose - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Magnesite - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Magnesite - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Magnesite - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Magnesite - Respirable particles.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values, as amended (01 2021)
Magnesite - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Magnesite - Inhalable particles.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (01 2021)
Magnesite - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.05 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended (03 2016)
	OSHA_ACT	0.025 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended (03 2016)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	PEL	0.05 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (03 2016)
Crystalline Silica (Quartz)/	TWA	2.4 millions	US. OSHA Table Z-3 (29 CFR 1910.1000), as

Silica Sand - Respirable.		of particles per cubic foot of air	amended (2000)
	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	US. ACGIH Threshold Limit Values, as amended (02 2020)
1,2,4-Trimethylbenzene	REL	25 ppm 125 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	TWA	25 ppm 125 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	10 ppm	US. ACGIH Threshold Limit Values, as amended (01 2022)
Nonane	TWA	200 ppm	US. ACGIH Threshold Limit Values, as amended (02 2012)
Hydrogen sulfide	TWA	1 ppm	US. ACGIH Threshold Limit Values, as amended (2011)
	STEL	5 ppm	US. ACGIH Threshold Limit Values, as amended (2011)
	Ceiling	20 ppm	US. OSHA Table Z-2 (29 CFR 1910.1000), as amended (02 2006)
	MAX. CONC	50 ppm	US. OSHA Table Z-2 (29 CFR 1910.1000), as amended (02 2006)

Chemical name	Type	Exposure Limit Values	Source
Asphalt - Aerosol, inhalable. - as benzene solubles	TWA	0.5 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
Asphalt - Inhalable fraction. - as benzene solubles	TWA	0.5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Asphalt - Fume.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Stoddard solvent (Mineral Spirits)	STEL	580 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
	TWA	290 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)

Stoddard solvent (Mineral Spirits)	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Stoddard solvent (Mineral Spirits)	TWA	100 ppm	525 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Cellulose - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
Cellulose - Total dust.	TWA		10 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
Cellulose	TWA		10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Cellulose - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA		0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA		0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	TWA		0.05 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (04 2022)
1,2,4-Trimethylbenzene	TWA	25 ppm	123 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)

Chemical name	Type	Exposure Limit Values	Source
Asphalt - Aerosol, inhalable. - as benzene solubles	TWA	0.5 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
Asphalt - Inhalable fraction. - as benzene solubles	TWA	0.5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Asphalt - Fume.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Stoddard solvent (Mineral Spirits)	STEL	580 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
	TWA	290 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)



Stoddard solvent (Mineral Spirits)	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Stoddard solvent (Mineral Spirits)	TWA	100 ppm	525 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Cellulose - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
Cellulose - Total dust.	TWA		10 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
Cellulose	TWA		10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Cellulose - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Magnesite - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Magnesite - Respirable fraction.	TWA		3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Magnesite - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (06 2020)
Magnesite - Respirable particles.	TWA		3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Magnesite - Total dust.	TWA		10 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (06 2020)
Magnesite - Inhalable particles.	TWA		10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Magnesite - Inhalable fraction.	TWA		10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Propylene glycol - Aerosol.	TWA		10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Propylene glycol - Vapor and aerosol.	TWA	50 ppm	155 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA		0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA		0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	TWA		0.05 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (04 2022)

1,2,4-Trimethylbenzene	TWA	25 ppm	123 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)
Nonane	TWA	200 ppm	1,050 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (12 2008)
Nonane	TWA	200 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Nonane	TWA	200 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (06 2022)
Xylene	STEL	150 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
	TWA	100 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
Xylene	STEL	150 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Xylene	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	STEL	150 ppm	651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Hydrogen sulfide	CEILING	10 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
Hydrogen sulfide	STEL	15 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
	TWA	10 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Hydrogen sulfide	TWA	8 ppm		Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (04 2022)
Naphthalene	STEL	15 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
	TWA	10 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)

Naphthalene	TWA	10 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Naphthalene	TWA	10 ppm	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (09 2011)
Ethylbenzene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Ethylbenzene	TWA	20 ppm	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)

### Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Asphalt (1-Hydroxypyrene, with hydrolysis (1-HP): Sampling time: End of shift at end of work week.)	2.5 µg/l (Urine)	ACGIH BEI (01 2021)
Asphalt (3-Hydroxybenzo(a)pyrene, with hydrolysis: Sampling time: End of shift at end of work week.)	(Urine)	ACGIH BEI (01 2021)

### Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

### Individual protection measures, such as personal protective equipment

**Eye/face protection:** Wear safety glasses with side shields (or goggles).

### Skin Protection

**Hand Protection:** Additional Information: Use suitable protective gloves if risk of skin contact.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.

**Hygiene measures:** Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Avoid contact with eyes.

## 9. Physical and chemical properties

### Appearance

<b>Physical state:</b>	liquid
<b>Form:</b>	Viscous Liquid
<b>Color:</b>	Black
<b>Odor:</b>	Mild petroleum/solvent

<b>Odor threshold:</b>	No data available.
<b>pH:</b>	No data available.
<b>Melting point/freezing point:</b>	No data available.
<b>Initial boiling point and boiling range:</b>	No data available.
<b>Flash Point:</b>	No data available.
<b>Evaporation rate:</b>	Slower than Ether
<b>Flammability (solid, gas):</b>	No
<b>Upper/lower limit on flammability or explosive limits</b>	
<b>Flammability limit - upper (%):</b>	No data available.
<b>Flammability limit - lower (%):</b>	No data available.
<b>Explosive limit - upper:</b>	No data available.
<b>Explosive limit - lower:</b>	No data available.
<b>Vapor pressure:</b>	No data available.
<b>Vapor density:</b>	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
<b>Relative density:</b>	1.18
<b>Solubility(ies)</b>	
<b>Solubility in water:</b>	Practically Insoluble
<b>Solubility (other):</b>	No data available.
<b>Partition coefficient (n-octanol/water):</b>	No data available.
<b>Auto-ignition temperature:</b>	No data available.
<b>Decomposition temperature:</b>	No data available.
<b>Viscosity:</b>	No data available.

## 10. Stability and reactivity

<b>Reactivity:</b>	No data available.
<b>Chemical Stability:</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions:</b>	No data available.
<b>Conditions to avoid:</b>	Avoid heat or contamination.
<b>Incompatible Materials:</b>	Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates).
<b>Hazardous Decomposition Products:</b>	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation:</b>	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
<b>Skin Contact:</b>	May be harmful in contact with skin.

**Eye contact:** Causes serious eye irritation.

**Ingestion:** May be ingested by accident. Ingestion may cause irritation and malaise.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Inhalation:** No data available.

**Skin Contact:** No data available.

**Eye contact:** No data available.

**Ingestion:** No data available.

#### Information on toxicological effects

##### Acute toxicity (list all possible routes of exposure)

###### Oral

**Product:** ATEmix: 18,922.35 mg/kg

###### Dermal

**Product:** ATEmix: 2,381.97 mg/kg

###### Inhalation

**Product:** ATEmix: 5.85 mg/l

##### Repeated dose toxicity

**Product:** No data available.

##### Skin Corrosion/Irritation

**Product:** No data available.

###### Specified substance(s):

Asphalt in vivo (Rabbit): Not irritant , 24 - 72 h

Magnesite In vitro (Human, in vitro reconstituted epidermis model): not corrosive , 60 min

Nonane in vivo (Rabbit): Irritating , 72 h

1,2,4-Trimethylbenzene in vivo (Rabbit): Irritating , 24 - 72 h

##### Serious Eye Damage/Eye Irritation

**Product:** No data available.

###### Specified substance(s):

Asphalt Rabbit, 24 h: Not irritant

Magnesite	Reconstituted Corneal Epithelium model, 10 min: Not irritant
Nonane	Rabbit, 24 - 72 h: Not irritant
1,2,4-Trimethylbenzene	Rabbit, 30 min: Not irritant

**Respiratory or Skin Sensitization**

**Product:** No data available.

**Carcinogenicity**

**Product:** No data available.

**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Asphalt	Overall evaluation: Possibly carcinogenic to humans.
Crystalline Silica (Quartz)/ Silica Sand	Overall evaluation: Carcinogenic to humans.

**US. National Toxicology Program (NTP) Report on Carcinogens:**

Asphalt	Known To Be Human Carcinogen.
Crystalline Silica (Quartz)/ Silica Sand	Known To Be Human Carcinogen.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:**

Crystalline Silica (Quartz)/ Silica Sand	Cancer
--	--------

**Germ Cell Mutagenicity**

**In vitro Product:** No data available.

**In vivo Product:** No data available.

**Reproductive toxicity**

**Product:** No data available.

**Specific Target Organ Toxicity - Single Exposure**

**Product:** No data available.

**Specific Target Organ Toxicity - Repeated Exposure**

**Product:** No data available.

### Target Organs

Specific Target Organ Toxicity - Repeated Exposure: Central nervous system

### Aspiration Hazard

**Product:** No data available.

### Other effects:

Constituents of this product may include crystalline silica which, if in inhalable form, may cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. Constituents may also contain asbestiform or non-asbestiform tremolite or other silicates as impurities, and above de minimis exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems.

## 12. Ecological information

### Ecotoxicity:

#### Acute hazards to the aquatic environment:

#### Fish

**Product:** No data available.

#### Specified substance(s):

Asphalt	LL 50 (Oncorhynchus mykiss, 96 h): > 1,000 mg/l Read-across from supporting substance (structural analogue or surrogate), Key study
Magnesite	LC 50 (Pimephales promelas, 96 h): 2,120 mg/l Read-across from supporting substance (structural analogue or surrogate), Key study
Nonane	LL 50 (Oncorhynchus mykiss, 96 h): 1.125 mg/l QSAR QSAR, Key study
1,2,4-Trimethylbenzene	LC 50 (Pimephales promelas, 96 h): 7.72 mg/l Experimental result, Key study
Hydrogen sulfide	LC 50 (Pimephales promelas, 96 h): 0.0243 mg/l Experimental result, Weight of Evidence study

#### Aquatic Invertebrates

**Product:** No data available.

#### Specified substance(s):

Asphalt	LL 50 (Daphnia magna, 48 h): > 1,000 mg/l read-across from supporting substance (structural analogue or surrogate) Read-across from supporting substance (structural analogue or surrogate), Key study
Stoddard solvent (Mineral Spirits)	LC 50 (Daphnia magna, 48 h): 0.42 - 2.3 mg/l
Magnesite	LC 50 (Daphnia magna, 48 h): 140 mg/l read-across from supporting

	substance (structural analogue or surrogate) Read-across from supporting substance (structural analogue or surrogate), Key study
Nonane	EC 50 (Daphnia magna, 48 h): 0.2 mg/l experimental result Experimental result, Key study
1,2,4-Trimethylbenzene	LC 50 (Daphnia magna, 48 h): 3.6 mg/l experimental result Experimental result, Key study
Hydrogen sulfide	LC 50 (Sand shrimp (Metapenaeus monoceros), 96 h): 0.0352 mg/l Mortality LC 50 (Aquatic arthropod, 96 h): 0.022 mg/l No data, Weight of Evidence study LC 50 (Aquatic arthropod, 96 h): 0.84 mg/l No data, Weight of Evidence study EC 50 (Aquatic arthropod, 96 h): 0.059 mg/l No data, Weight of Evidence study LC 50 (Aquatic arthropod, 96 h): 0.059 mg/l No data, Weight of Evidence study

#### Chronic hazards to the aquatic environment:

##### Fish

**Product:** No data available.

**Specified substance(s):**

Asphalt  
NOAEL (Oncorhynchus mykiss):  $\geq 1,000$  mg/l read-across from supporting substance (structural analogue or surrogate) Read-across from supporting substance (structural analogue or surrogate), Key study

##### Aquatic Invertebrates

**Product:** No data available.

**Specified substance(s):**

Asphalt  
NOAEL (Daphnia magna):  $\geq 1,000$  mg/l read-across from supporting substance (structural analogue or surrogate) Read-across from supporting substance (structural analogue or surrogate), Key study

Nonane  
NOAEL (Daphnia magna): 0.17 mg/l read-across based on grouping of substances (category approach) Read-across based on grouping of substances (category approach), Key study

##### Toxicity to Aquatic Plants

**Product:** No data available.

#### Persistence and Degradability

##### Biodegradation

**Product:** No data available.

**Specified substance(s):**

Nonane  
100 % (15 d) Detected in water. Experimental result, Key study

##### BOD/COD Ratio

**Product:** No data available.



**Bioaccumulative potential****Bioconcentration Factor (BCF)****Product:** No data available.**Specified substance(s):**

Nonane Bioconcentration Factor (BCF): 105 Aquatic sediment Estimated by calculation, Key study

1,2,4-Trimethylbenzene Pimephales promelas, Bioconcentration Factor (BCF): 243 Aquatic sediment QSAR, Key study

**Partition Coefficient n-octanol / water (log Kow)****Product:** No data available.**Specified substance(s):**

Nonane Log Kow: 5.65

1,2,4-Trimethylbenzene Log Kow: 3.78

**Mobility in soil:** No data available.**Other adverse effects:** Toxic to aquatic organisms. Harmful to aquatic life with long lasting effects.**13. Disposal considerations****Disposal methods:** Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.**Contaminated Packaging:** No data available.**14. Transport information****TDG:**

Not Regulated

**CFR / DOT:**

Not Regulated

**IMDG:**

Not Regulated

**15. Regulatory information****US Federal Regulations**

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

None present or none present in regulated quantities.

**US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)**

None present or none present in regulated quantities.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended**

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Crystalline Silica (Quartz)/ Silica Sand	kidney effects lung effects immune system effects Cancer

**CERCLA Hazardous Substance List (40 CFR 302.4):**

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Asphalt	100 lbs.
Nonane	100 lbs.
Xylene	100 lbs.
Hydrogen sulfide	100 lbs.
Naphthalene	100 lbs.
Ethylbenzene	1000 lbs.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories**

- Immediate (Acute) Health Hazards
- Delayed (Chronic) Health Hazard
- Acute toxicity (any route or exposure)
- Serious eye damage or eye irritation
- Germ Cell Mutagenicity
- Carcinogenicity
- Specific target organ toxicity (single or repeated exposure)

**US. EPCRA (SARA Title III) Section 304 Extremely Hazardous Substances Reporting Quantities and the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substances**

Not regulated.

**US. EPCRA (SARA Title III Section 313 Toxic Chemical Release Inventory (TRI) Reporting**

Not regulated.

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Hydrogen sulfide	lbs

**Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)**

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	Reportable quantity: 100 lbs.

**US State Regulations**

**US. California Proposition 65**



**WARNING**

Cancer - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**International regulations**

**Montreal protocol**

Not applicable

**Stockholm convention**

Not applicable

**Rotterdam convention**

Not applicable

**Kyoto protocol**

Not applicable

**VOC:**

Regulatory VOC (less water and exempt solvent) : 192 g/l

VOC Method 310 : 16.31 %

**Inventory Status:**

Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	All components in this product are listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	All components in this product are listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	All components in this product are listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	All components in this product are listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Mexico INSQ:	One or more components in this product are not listed on or exempt from the Inventory.
Ontario Inventory:	One or more components in this

product are not listed on or exempt from the Inventory.

Taiwan Chemical Substance Inventory: One or more components in this product are not listed on or exempt from the Inventory.

Australia Industrial Chem. Act (AIC): One or more components in this product are not listed on or exempt from the Inventory.

Switzerland New Subs Notified/Registered: One or more components in this product are not listed on or exempt from the Inventory.

Thailand DIW Existing Chemical Inv. List: One or more components in this product are not listed on or exempt from the Inventory.

Vietnam National Chemical Inventory: One or more components in this product are not listed on or exempt from the Inventory.

<b>16. Other information, including date of preparation or last revision</b>
--

**Revision Date:** 04/05/2023

**Version #:** 1.3

**Further Information:** No data available.

**Disclaimer:** For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.