

Version 1.0 Print Date 03/04/2015

REVISION DATE: 05/14/2013

#### **SECTION 1 - PRODUCT IDENTIFICATION**

Trade name : TREMCO-USG SECUROCK .25" X 4' X 4'

Product code : 305725USG550

COMPANY : Tremco Incorporated

3735 Green Road Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST

After Hours: Chemtrec 1-800-424-9300

Product use : Insulation Board

#### **SECTION 2 - HAZARDS IDENTIFICATION**

#### **Emergency Overview**

Tan. Solid. May cause slight irritation to the respiratory system. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

#### **Acute Potential Health Effects/ Routes of Entry**

Inhalation : May cause slight irritation to the respiratory system.

Eyes : May cause mechanical irritation or abrasion. Direct contact may cause temporary redness

and discomfort.

Ingestion : Not applicable under normal conditions of use.

Skin : May cause mild irritation.

#### **Aggravated Medical Conditions**

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

### **Chronic Health Effects**

Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

Target Organs: Skin, Eye, Lung

### **SECTION 3 - PRODUCT COMPOSITION**

Chemical Name	CAS-No.	Weight %
Calcium salt	13397-24-5	> 60.0
Inert Filler	NJ TSRN# 51721300-5013P	5.0 - 10.0
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	3.0 - 7.0

### **SECTION 4 - FIRST AID MEASURES**

Get immediate medical attention for any significant overexposure.



Print Date 03/04/2015

**REVISION DATE: 05/14/2013** 

Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get

medical attention.

Eye contact : Flush with water for at least 15 minutes while holding eye lids apart. Get medical

attention immediately.

Skin contact Clean area of contact thoroughly using soap and water. If irritation, rash or other

disorders develop, get medical attention immediately.

Do not induce vomiting unless advised by a physician. Call nearest Poison Control Ingestion

Center or Physician immediately.

Notes to physician Not applicable.

### **SECTION 5 - FIRE FIGHTING MEASURES**

Not available. Flash point Not available. Method Lower explosion limit Not available. Upper explosion limit Not available. Autoignition temperature Not available.

Extinguishing media If water fog is ineffective, use carbon dioxide, dry chemical or foam. Hazardous combustion Hydrogen chloride. Carbon monoxide and carbon dioxide can form.

products

Protective equipment for

firefighters

Use accepted fire fighting techniques. Wear full firefighting protective

clothing, including self-contained breathing apparatus (SCBA).

### SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Scrape up and transfer to appropriate container for disposal.

### **SECTION 7 - HANDLING AND STORAGE**

Handle in compliance with common hygienic practices. Clean hands thoroughly after handling. Store under normal warehouse conditions below 120F/49C. Prevent inhalation of dust and contact with skin and eyes. Clean hands thoroughly after handling.

### SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

## Personal protection equipment

: Wear appropriate, properly fitted NIOSH/MSHA approved dust respirator Respiratory protection

> where airborne concentrations are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.

: Protect hands with impervious gloves. Hand protection

Eye protection Wear appropriate eye protection.

Skin and body protection Typical full cover clothing.

Protective measures Use professional judgment in the selection, care, and use.

Pm Company 2/6



Version 1.0 Print Date 03/04/2015

**REVISION DATE: 05/14/2013** 

Engineering measures : Use general ventilation and/ or local exhaust to reduce the airborne

contaminant concentration below the exposure limit listed in the MSDS

### **Exposure Limits**

Chemical Name	CAS Number	Regulation	<u>Limit</u>	<u>Form</u>
Calcium salt	13397-24-5	OSHA PEL: OSHA PEL: ACGIH TWA:	5 mg/m3 15 mg/m3 3 mg/m3	Respirable fraction. Total dust. Respirable particles.
		ACGIH TWA: OSHA TWA:	10 mg/m3 15 mg/m3	Inhalable particles. Total dust.
		OSHA TWA: ACGIH TWA:	5 mg/m3 10 mg/m3	Respirable fraction. Inhalable fraction.
Inert Filler	NJ TSRN# 51721300-5013P	ACGIH TWA: OSHA PEL: OSHA PEL: OSHA TWA: OSHA TWA:	10 mg/m3 5 mg/m3 15 mg/m3 15 mg/m3 5 mg/m3	Respirable fraction. Total dust. Total dust. Respirable fraction.
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	OSHA TWA: OSHA TWA: OSHA PEL: OSHA PEL: ACGIH TWA:	0.1 mg/m3 0.3 mg/m3 15 mg/m3 5 mg/m3 0.025 mg/m3	Respirable. Total dust. Total dust. Respirable fraction. Respirable fraction.

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form : Solid Color : Tan

Odor : Slight None

pH : 7

Vapour pressure : Not available. Vapor density : Not available. Melting point/range : Not available. Freezing point : Not available. Boiling point/range : Not available. Water solubility : Insoluble Specific Gravity : 0.96 % Volatile Weight : 0%

## **SECTION 10 - REACTIVITY / STABILITY**

Substances to avoid : Not Applicable.

Stability : Material is stable under normal storage, handling, and use.

Hazardous polymerization : Will not occur.

An RPM Company 3/6



Version 1.0 Print Date 03/04/2015

REVISION DATE: 05/14/2013

### SECTION 11 - TOXICOLOGICAL INFORMATION

No Data Available

### **SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

### **SECTION 13 - DISPOSAL CONSIDERATIONS**

Disposal Method : As purchased, this product, when discarded, is not a listed or characteristic hazardous

waste according to Federal regulations (40 CFR 261). Check local, regional, state or provincial regulations for applicable requirements for disposal. Any processing, using, alteration or chemical additions to the product, as purchased, may alter the disposal requirements. Under Federal regulations, it is the generator's responsibility to determine if a waste is a hazardous waste. Empty containers may retain product

residue. Do not reuse.

### **SECTION 14 - TRANSPORTATION / SHIPPING DATA**

## CFR / DOT:

Not Regulated

TDG:

Not Regulated

IMDG:

Not Regulated

## **SECTION 15 - REGULATORY INFORMATION**

#### North American Inventories:

One or more components are not listed on the TSCA inventory.

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

**U.S. Federal Regulations:** 

SARA 313 Components : None present or none present in regulated quantities.

SARA 311/312 Hazards : Acute Health Hazard

Chronic Health Hazard

OSHA Hazardous Components :



## Material Safety Data Sheet



## TREMCO-USG SECUROCK .25" X 4' X 4'

Version 1.0 Print Date 03/04/2015

**REVISION DATE: 05/14/2013** 

Calcium salt 13397-24-5

Inert Filler NJ TSRN# 51721300-5013P

Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

OSHA Status: Considered : Irritant hazardous based on the Carcinogen

following criteria:

OSHA Flammability : Not Regulated

Regulatory VOC (less water and

exempt solvent)

VOC Method 310 : 0 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen: Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

**U.S. State Regulations:** 

MASS RTK Components : Calcium salt 13397-24-5

: 0 g/l

Inert Filler NJ TSRN# 51721300-5013P

Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

Penn RTK Components : Calcium salt 13397-24-5

Inert Filler NJ TSRN# 51721300-5013P

Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

NJ RTK Components : Calcium salt 13397-24-5

Inert Filler NJ TSRN# 51721300-5013P

Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

Components under California Proposition 65:

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

### **SECTION 16 - OTHER INFORMATION**

#### **HMIS Rating:**

Health	1	0 = Minimum
Flammability	0	1 = Slight
Reactivity	0	2 = Moderate
PPE		3 = Serious
		4 = Severe

### Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

#### Prepared by: Rich Mikol

#### Legena

ACGIH - American Conference of Governmental Hygienists PEL - Permissible Exposure Limit

CERCLA - Comprehensive Environmental Response, Compensation, and RCRA - Resource Conservation and Recovery Act

An RPM Company 5/6



Version 1.0 Print Date 03/04/2015

Liability Act

DOT - Department of Transportation

DSL - Domestic Substance List

**REVISION DATE: 05/14/2013** 

EPA - Environmental Protection Agency

HMIS - Hazardous Materials Information System

IARC - International Agency for Research on Cancer

MSHA - Mine Safety Health Administration

NDSL - Non-Domestic Substance List

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

RTK - Right To Know

SARA - Superfund Amendments and Reauthorization Act

STEL - Short Term Exposure Limit

TLV - Threshold Limit Value

TSCA - Toxic Substances Control Act

TWA - Time Weighted Average

V - Volume

VOC - Volatile Organic Compound

WHMIS - Workplace Hazardous Materials Information

System