

SOLARGARD 6083 BASE COAT 5 GAL PL

Version 1.0 REVISION DATE: 11/12/2013 Print Date 07/23/2014

SECTION 1 - PRODUCT IDENTIFICATION

Trade name:SOLARGARD 6083 BASE COAT 5 GAL PLProduct code:1121700005PCOMPANY:Tremco Incorporated
3735 Green Road
Cleveland, OH 44122Telephone:(216) 292-5000 8:30 - 5:00 EST
After Hours: Chemtrec 1-800-424-9300Product use:Coating

SECTION 2 - HAZARDS IDENTIFICATION

Emergency Overview

Light Yellow. Liquid. No serious effects anticipated under normal conditions of use. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation	:	No serious effects anticipated under normal conditions of use.
Eyes	:	Direct contact may cause mild irritation.
Ingestion	:	May cause gastrointestinal irritation, nausea, and vomiting.
Skin	:	May cause mild irritation.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica. Long term overexposure to propylene glycol caused liver abnormalities, kidney damage in laboratory animals. Repeated excessive ingestion may cause central nervous system effects. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %
Calcium carbonate	471-34-1	30.0 - 60.0
Water	7732-18-5	30.0 - 60.0
Acrylic Polymer	NJ TSRN# 51721300-5208P	15.0 - 40.0
Titanium dioxide	13463-67-7	1.0 - 5.0
Propylene glycol	57-55-6	1.0 - 5.0
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	0.1 - 1.0
n-(3,4-dichlorophenyl)-n,n-dimethylurea	330-54-1	0.1 - 1.0
Aluminum oxide	1344-28-1	0.1 - 1.0
An RPM Company 1/6		



SOLARGARD 6083 BASE COAT 5 GAL PL

Version 1.0 REVISION DATE: 11/12/2013 Print Date 07/23/2014

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

Inhalation	:	Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
Eye contact	:	Flush with water for 15 minutes. If irritation persists, get medical attention.
Skin contact	:	Wash area of contact thoroughly with hand cleaner followed by soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
Ingestion	:	Get medical attention. Do not induce vomiting.

Notes to physician : Not applicable.

SECTION 5 - FIRE FIGHTING MEASURES

Flash point Method Lower explosion limit	: : :	Not available. Not applicable. Not available.
Upper explosion limit	:	Not available.
Autoignition temperature	:	Not available.
Extinguishing media	:	This product is not expected to burn under normal conditions of use.
Hazardous combustion products	:	Carbon monoxide and carbon dioxide can form.Smoke, fumes.
Protective equipment for firefighters	:	Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
Fire and explosion conditions	:	This product not expected to ignite under normal conditions of use.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Transfer to appropriate container for disposal. Stop flow. Contain spill. Keep out of water courses. Absorb spill in sand, earth or other suitable material. Transfer to appropriate container for disposal. Use appropriate protective equipment. Avoid contact with material.

SECTION 7 - HANDLING AND STORAGE

Handle in compliance with common hygienic practices. Clean hands thoroughly after handling. Keep from freezing. Do not use in confined or poorly ventilated areas. Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Store in sealed containers in a dry, ventilated warehouse location above freezing.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection equipment

An RPM Company 2/6



SOLARGARD 6083 BASE COAT 5 GAL PL

Version 1.0 REVISION DATE: 11/12/2013 Print Date 07/23/2014

Respiratory protection	:	Not required under normal conditions of use.Wear appropriate, NIOSH/MSHA approved respirator with combination particulate filter and vapor/gas removing cartridge when the ventilation is not adequate or if it is necessary to abrade or grind surfaces coated with this product.
Hand protection	:	Use suitable impervious rubber or vinyl gloves and protective apparel to reduce exposure.
Eye protection	:	Wear appropriate eye protection.Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
Skin and body protection	:	Prevent contact with shoes and clothing. Use rubber apron and overshoes.
Protective measures	:	Other equipment not normally required. Use professional judgment in the selection, care, and use.
Engineering measures	:	Not required under normal conditions of use.Use local exhaust when the general ventilation is inadequate.

Exposure Limits

Chemical Name	CAS Number	Regulation	<u>Limit</u>	<u>Form</u>
Titanium dioxide	13463-67-7	ACGIH TWA: OSHA PEL: OSHA TWA: OSHA TWA:	10 mg/m3 15 mg/m3 15 mg/m3 5 mg/m3	Total dust. Total dust. Respirable fraction.
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	OSHA TWA: OSHA TWA: OSHA PEL: OSHA PEL: ACGIH TWA:	0.1 mg/m3 0.3 mg/m3 15 mg/m3 5 mg/m3 0.025 mg/m3	Respirable. Total dust. Total dust. Respirable fraction. Respirable fraction.
n-(3,4-dichlorophenyl)- n,n-dimethylurea	330-54-1	ACGIH TWA:	10 mg/m3	
Aluminum oxide	1344-28-1	ACGIH TWA: OSHA PEL: OSHA PEL: OSHA TWA: OSHA TWA: ACGIH TWA:	10 mg/m3 5 mg/m3 15 mg/m3 15 mg/m3 5 mg/m3 1 mg/m3	Respirable fraction. Total dust. Total dust. Respirable fraction. Respirable fraction.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form	: Liquid
Color	: Light Yellow
Odor	: Light Amine
рН	: 8 - 10
Vapour pressure	: Not available.
Vapor density	: Heavier than air
An Rpm Company 3/6	

Material Safety Data Shee	et	TREMCO.
SOLARGARD 6083 BA	SE COA	T 5 GAL PL
Version <i>1.0</i> REVISION DATE: 11/12/2013		Print Date 07/23/2014
Melting point/range	: Not ava	ailable.
Freezing point	: 32 °F, 0	℃ (
Boiling point/range	: Not ava	uilable.
Water solubility	: Soluble	
Specific Gravity	: 1.46	
% Volatile Weight	: 33 %	
SECTION 10 - REACTIVITY	/ / STABIL	ΙΤΥ
Substances to avoid	: Strong	acids.Strong bases.
Stability	: Stable	
Hazardous polymerization	: Will not	occur.
SECTION 11 - TOXICOLOC	GICAL INFO	ORMATION
Calcium carbonate, CAS-No. Acute oral toxicity (LD-		6,450 mg/kg (Rat)
Propylene glycol, CAS-No.: 57-55-6 Acute oral toxicity (LD-50 oral)		30,000 mg/kg (Rat)18,000 mg/kg (Rabbit)19,000 mg/kg (Dog)23,900 - 31,800 mg/kg (Mouse)18,400 - 196,000 mg/kg (Guinea pig)
n-(3,4-dichlorophenyl)-n,n-dii Acute oral toxicity (LD-		CAS-No.: 330-54-1 3,400 mg/kg (Rat)1,017 mg/kg (Rat)

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method : Waste not regulated under RCRA. Dispose of in compliance with state and local regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA

CFR / DOT:

Not Regulated

TDG:

Not Regulated

An RPM Company 4/6



SOLARGARD 6083 BASE COAT 5 GAL PL

Version 1.0 **REVISION DATE: 11/12/2013** Print Date 07/23/2014

IMDG:

Not Regulated

SECTION 15 - REGULATORY INFORMATION

North American Inventories:

All components are listed or exempt from the TSCA inventory. This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

ARA 313 Components : None present or none present in re			lated quantities.
SARA 311/312 Hazards		: Acute Health Hazard Chronic Health Hazard	
OSHA Hazardous Compo	nen	ts :	
Titanium dioxide Crystalline Silica (Quartz) n-(3,4-dichlorophenyl)-n,r Aluminum oxide			
OSHA Status: Considered hazardous based on the following criteria:	ł	: Irritant Carcinogen	
OSHA Flammability		: Not Regulated	
Regulatory VOC (less wa exempt solvent)	ter a	nd : 36 g/l	
VOC Method 310		: 1.29 %	
Chemical is listed as an IA Crystalline Silica (Quartz) U.S. State Regulations:		NTP, OSHA, or ACGIH Carcinogen: ca Sand 14808-60-7	
MASS RTK Components	:	Calcium carbonate Titanium dioxide Crystalline Silica (Quartz)/ Silica Sand	471-34-1 13463-67-7 14808-60-7
Penn RTK Components : Calcium carbonate Water Acrylic Polymer Titanium dioxide Propylene glycol			471-34-1 7732-18-5 NJ TSRN# 51721300-5208P 13463-67-7 57-55-6



Print Date 07/23/2014

SOLARGARD 6083 BASE COAT 5 GAL PL

Version 1.0 REVISION DATE: 11/12/2013

> Propylene glycol Crystalline Silica (Quartz)/ Silica Sand

57-55-6 14808-60-7

Components under California Proposition 65:

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

SECTION 16 - OTHER INFORMATION

HMIS Rating :

Health	1
Flammability	0
Reactivity	0
PPE	

0 = Minimum 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

ACGIH - American Conference of Governmental Hygienists CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act DOT - Department of Transportation DSL - Domestic Substance List EPA - Environmental Protection Agency HMIS - Hazardous Materials Information System IARC - International Agency for Research on Cancer MSHA - Mine Safety Health Administration NDSL - Non-Domestic Substance List NIOSH - National Institute for Occupational Safety and Health NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act

RTK - Right To Know SARA - Superfund Amendments and Reauthorization Act STEL - Short Term Exposure Limit TLV - Threshold Limit Value TSCA - Toxic Substances Control Act TWA - Time Weighted Average V - Volume VOC - Volatile Organic Compound WHMIS - Workplace Hazardous Materials Information System

An **RPM** Company 6/6