

ECOmastic

A Heavily Fibrated Asphalt Mastic for General Roof Repairs

FEATURES

- Sag resistant
- Fibrated
- Asbestos free

DESCRIPTION

ECOmastic® is an asphalt-based, heavily fibrated mastic blended with penetrating oils and plasticizing agents. ECOMastic is asbestos free.

BASIC USES

ECOmastic is used for repairing and restoring flashings and asphalt built-up roofing defects including blisters, cracks, and punctures. Added strength can be obtained by using reinforcing membranes.

GRADE

Trowel

PACKAGING

ECOmastic is available in 18.9 and 208 litres (5 and 55 U.S. gallon) containers.

APPLICATION

Remove loose gravel, dirt, dust, deteriorated felt and foreign matter. Apply over clean, sound dry, base.

COVERAGE RATE

Coverage rates will vary depending on ambient temperature and actual surface conditions.

- Single coat: 3.3 L/m² (12.5 ft.²/U.S. gal.).
- 1 ply BURmesh: 6.5 L/m² (6.3 ft.²/U.S. gal.).
- 2 ply BURmesh: 9.7L/m² (4.2 ft.²/U.S. gal.).

LIMITATIONS

- Not intended for use as a wet patching material.
- Not for use on coal tar membranes.

MAINTENANCE

Your local Tremco Roofing representative can provide you with effective maintenance procedures, which may vary depending upon specific conditions. Periodic inspections, early repairs and preventive maintenance are all part of a sound roof program.

PRECAUTIONS

Users must read container labels and Safety Data Sheets for health and safety precautions prior to use.

TECHNICAL SUPPORT

Your local Tremco Representative, working with the Technical Service Staff, can help analyze conditions and needs to develop recommendations for special applications. The services of the Tremco Research Center, which has earned a unique reputation in weatherproofing technology, complement and extend the service of the Tremco Service Staff.



Roofing & Building Maintenance

www.tremcoroofing.com

3735 Green Road
Beachwood, Ohio 44122
1.800.852.6013

220 Wicksteed Avenue
Toronto, Ontario, M4H 1G7
1.800.668.9879

Tremco Roofing and Building
Maintenance is part of Tremco
Construction Products Group.

Tremco is a US Registered trademark of Tremco CPG Inc.

The information provided on this data page supersedes all previous data concerning this product and its application.

The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCE SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.