

TremFlash (TF) Tape

A flexible, non-drying, gasket forming, sealant tape

DESCRIPTION

TremFlash (TF)Tape is a flexible, butyl based sealant tape used to provide a compressible gasket when applied to surfaces to be joined by mechanical attachment.

BASIC USES

TremFlash Tape is applied to metal termination bars and Elastomeric Flashing Membrane before attachment to vertical surfaces in flashing applications. The TremFlash Tape compresses when the materials are mechanically attached and helps to form a gasket seal between the components, especially where the substrate may be slightly uneven.

PACKAGING

TremFlash Tape is available in 3 mm X 25 mm X 15.2 m (1/8" X 1" X 50') rolls and is packaged in cartons of 12 rolls. TremFlash Tape is conveniently applied to release paper backer to ease application and to prevent sticking to itself.

COLOR

TremFlash Tape is available in gray only.

STORAGE LIFE

Up to 1 year.

APPLICATION

Apply the TremFlash Tape to the clean mating surface of the material to which is to be attached. Apply the TremFlash Tape by adhering the tape to the surface and unrolling the TremFlash Tape with the release paper intact. Put slight pressure on the backer during application to assure adhesion to the surface.

Remove the release paper backer. Assure that the TremFlash Tape remains clean when exposed. Apply the material to be attached to the clean, dry substrate. Mechanically attach the material slightly compressing the TremFlash Tape to form a gasket seal without over compressing the gasket.

The joint created between the attached material and the substrate may be caulked with either TremSeal D, TremSeal HP or Reglet Joint Sealant per Tremco application specifications.

CLEAN UP

Immediately remove excess TremFlash Tape from any surface with Tremply Solvent or Xylene as work progresses.

LIMITATIONS

- Do not use on horizontal joints.
- Do not expose to standing water.
- Do not expose to constant contact with harsh chemicals such as acids, alkalies and organic solvents.

MAINTENANCE

Your local Tremco Roofing Sales Representative can provide you with effective maintenance procedures which may vary, depending upon specific conditions. Periodic inspections, early repairs and preventative maintenance are all part of a sound roof program.

PRECAUTIONS

Users must read container labels and Safety Data Sheets for health and safety precautions prior to use.

TECHNICAL SUPPORT

TremFlash (TF) Tape

Your local Tremco Roofing Sales Representative, working with the Technical Service Staff, can help analyze conditions and needs to develop recommendations for special applications.



www.tremcoroofing.com
3735 Green Road
Beachwood, Ohio 44122
1.800.852.6013

220 Wicksteed Avenue
Toronto, Ontario, M4H 1G7
1.800.668.9879

Tremco Roofing and Building
Maintenance is part of Tremco
Construction Products Group.

Tremco is a US Registered trademark of Tremco CPG Inc.

The information provided on this data page supersedes all previous data concerning this product and its application.

The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCE SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.