

# SAFETY DATA SHEET

## 1. Identification

**Material name:** POWERPLY STANDARD - WHITE GRANULE  
**Material:** 036STD601

**Recommended use and restriction on use**

**Recommended use:** Article  
**Restrictions on use:** Not known.

**Manufacturer/Importer/Supplier/Distributor Information**

Tremco Incorporated  
3735 Green Road  
BEACHWOOD OH 44122  
US

**Contact person:** EH&S Department  
**Telephone:** 216-292-5000  
**Emergency telephone number:** 1-800-424-9300 (US); 1-613-996-6666 (Canada)

## 2. Hazard(s) identification

### Hazard Classification

#### Health Hazards

Carcinogenicity Category 1A

#### Unknown toxicity - Health

Acute toxicity, oral	48.51 %
Acute toxicity, dermal	54.82 %
Acute toxicity, inhalation, vapor	99.35 %
Acute toxicity, inhalation, dust or mist	100 %

#### Unknown toxicity - Environment

Acute hazards to the aquatic environment	99.35 %
Chronic hazards to the aquatic environment	100 %

### Label Elements

**Hazard Symbol:**



**Signal Word:** Danger

**Hazard Statement:** May cause cancer.

**Precautionary Statement:**

- Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
- Response:** If exposed or concerned: Get medical advice/attention.
- Storage:** Store locked up.
- Disposal:** Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
- Other hazards which do not result in GHS classification:** None.

### 3. Composition/information on ingredients

#### Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium Carbonate (Limestone)	1317-65-3	30 - 60%
Asphalt	8052-42-4	15 - 40%
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	15 - 40%
Magnesite	546-93-0	3 - 7%
Fibrous Glass	65997-17-3	1 - 5%
Clay	1332-58-7	1 - 5%
Phthalocyanine green	1328-53-6	0.1 - 1%
Titanium dioxide	1317-80-2	0.1 - 1%
Carbon Black	1333-86-4	0.1 - 1%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Iron oxide	1309-37-1	0.1 - 1%

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

### 4. First-aid measures

- Ingestion:** Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
- Inhalation:** Move to fresh air.
- Skin Contact:** Wash skin thoroughly with soap and water. Get medical attention if symptoms occur.
- Eye contact:** Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

#### Most important symptoms/effects, acute and delayed

**Symptoms:** May cause skin and eye irritation.

#### Indication of immediate medical attention and special treatment needed

**Treatment:** Symptoms may be delayed.

## 5. Fire-fighting measures

**General Fire Hazards:** No unusual fire or explosion hazards noted.

### Suitable (and unsuitable) extinguishing media

**Suitable extinguishing media:** Use fire-extinguishing media appropriate for surrounding materials.

**Unsuitable extinguishing media:** Do not use water jet as an extinguisher, as this will spread the fire.

**Specific hazards arising from the chemical:** During fire, gases hazardous to health may be formed.

### Special protective equipment and precautions for firefighters

**Special fire fighting procedures:** No data available.

**Special protective equipment for fire-fighters:** Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

## 6. Accidental release measures

**Personal precautions, protective equipment and emergency procedures:** No data available.

**Methods and material for containment and cleaning up:** Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

**Notification Procedures:** In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

**Environmental Precautions:** Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

## 7. Handling and storage

**Precautions for safe handling:** Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust.

**Conditions for safe storage, including any incompatibilities:** Store locked up.

## 8. Exposure controls/personal protection

### Control Parameters

#### Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Asphalt - Inhalable fraction. - as benzene solubles	TWA	0.5 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values (2011)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values (2011)
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWA	2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA	0.1 mg/m <sup>3</sup>	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Crystalline Silica (Quartz)/ Silica Sand - Total dust.	TWA	0.3 mg/m <sup>3</sup>	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Magnesite - Total dust.	PEL	15 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Magnesite - Respirable fraction.	PEL	5 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Fibrous Glass - Inhalable fraction.	TWA	5 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values (03 2014)
Fibrous Glass - Fiber.	TWA	1 fibers/cm <sup>3</sup>	US. ACGIH Threshold Limit Values (03 2014)
	TWA	1 fibers/cm <sup>3</sup>	US. ACGIH Threshold Limit Values (03 2014)
	TWA	1 fibers/cm <sup>3</sup>	US. ACGIH Threshold Limit Values (03 2014)
	TWA	1 fibers/cm <sup>3</sup>	US. ACGIH Threshold Limit Values (03 2014)
	TWA	1 fibers/cm <sup>3</sup>	US. ACGIH Threshold Limit Values (03 2014)
	TWA	0.2 fibers/cm <sup>3</sup>	US. ACGIH Threshold Limit Values (03 2014)
Clay - Respirable fraction.	TWA	2 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Clay - Total dust.	PEL	15 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Phthalocyanine green - Dust and mist. - as Cu	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Phthalocyanine green - Fume. - as Cu	TWA	0.2 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Iron oxide - Respirable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (2011)
Iron oxide - Fume.	PEL	10 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (2011)
Carbon Black	PEL	3.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm      2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	type	Exposure Limit Values	Source
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m <sup>3</sup>	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m <sup>3</sup>	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Asphalt - Aerosol, inhalable. - as benzene solubles	TWA	0.5 mg/m <sup>3</sup>	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Asphalt - Inhalable fraction. - as benzene solubles	TWAEV	0.5 mg/m <sup>3</sup>	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Asphalt - Fume.	TWA	5 mg/m <sup>3</sup>	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m <sup>3</sup>	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWAEV	0.10 mg/m <sup>3</sup>	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m <sup>3</sup>	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Magnesite - Total dust.	TWAEV	10 mg/m <sup>3</sup>	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Magnesite - Total dust.	TWA	10 mg/m <sup>3</sup>	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Fibrous Glass - Fiber.	TWA	0.2 fibers/cm <sup>3</sup>	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	1 fibers/cm <sup>3</sup>	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Fibrous Glass - Inhalable fibers.	TWA	5 mg/m <sup>3</sup>	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Fibrous Glass - Inhalable	TWAEV	5 mg/m <sup>3</sup>	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Fibrous Glass - Respirable fibers.	TWAEV	1 fibers/mL	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Fibrous Glass - Fiber.	TWAEV	0.2 fibers/mL	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Fibrous Glass - Total dust.	TWA	10 mg/m <sup>3</sup>	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Fibrous Glass - Fiber.	TWA	1 fibres/cm <sup>3</sup> (non-asbestos fibres) -- size restrictions apply	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	TWA	2 fibres/cm <sup>3</sup> (non-asbestos fibres) -- size restrictions apply	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Clay - Respirable.	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Clay - Respirable fraction.	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Clay - Respirable dust.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Carbon Black - Inhalable	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black	TWAEV	3.5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Carbon Black	TWA	3.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Mist.	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical



			Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

**Appropriate Engineering Controls** Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

### Individual protection measures, such as personal protective equipment

**General information:** Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.

**Eye/face protection:** Wear safety glasses with side shields (or goggles).

#### Skin Protection

**Hand Protection:** Use suitable protective gloves if risk of skin contact.

**Other:** Wear suitable protective clothing.

**Respiratory Protection:** In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.

**Hygiene measures:** Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product.

## 9. Physical and chemical properties

### Appearance

**Physical state:** solid  
**Form:** solid  
**Color:** Various

**Odor:** Slight

**Odor threshold:** No data available.

**pH:** No data available.

**Melting point/freezing point:** No data available.

**Initial boiling point and boiling range:** No data available.

**Flash Point:** No data available.

**Evaporation rate:** No data available.

**Flammability (solid, gas):** No

#### Upper/lower limit on flammability or explosive limits

**Flammability limit - upper (%):** No data available.

**Flammability limit - lower (%):** No data available.

<b>Explosive limit - upper (%):</b>	No data available.
<b>Explosive limit - lower (%):</b>	No data available.
<b>Vapor pressure:</b>	No data available.
<b>Vapor density:</b>	No data available.
<b>Relative density:</b>	1.0
<b>Solubility(ies)</b>	
<b>Solubility in water:</b>	Insoluble in water
<b>Solubility (other):</b>	No data available.
<b>Partition coefficient (n-octanol/water):</b>	No data available.
<b>Auto-ignition temperature:</b>	No data available.
<b>Decomposition temperature:</b>	No data available.
<b>Viscosity:</b>	No data available.

## 10. Stability and reactivity

<b>Reactivity:</b>	No data available.
<b>Chemical Stability:</b>	Material is stable under normal conditions.
<b>Possibility of Hazardous Reactions:</b>	No data available.
<b>Conditions to Avoid:</b>	Avoid heat or contamination.
<b>Incompatible Materials:</b>	No data available.
<b>Hazardous Decomposition Products:</b>	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Ingestion:</b>	May be ingested by accident. Ingestion may cause irritation and malaise.
<b>Inhalation:</b>	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
<b>Skin Contact:</b>	May be harmful in contact with skin.
<b>Eye contact:</b>	Eye contact is possible and should be avoided.

### Information on toxicological effects

#### Acute toxicity (list all possible routes of exposure)

<b>Oral Product:</b>	ATEmix: 25,024.25 mg/kg
<b>Dermal Product:</b>	ATEmix: 4,647.13 mg/kg
<b>Inhalation</b>	

**Product:** No data available.

**Repeated dose toxicity  
Product:** No data available.

**Skin Corrosion/Irritation  
Product:** No data available.

**Serious Eye Damage/Eye Irritation  
Product:** No data available.

**Specified substance(s):**

Asphalt	in vivo (Rabbit, 24 hrs): Not irritating
Magnesite	In vitro (Reconstituted Corneal Epithelium model, 10 min): Not irritating
Phthalocyanine green	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Carbon Black	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit, 24 hrs): Not irritating
Iron oxide	in vivo (Rabbit, 1 - 72 hrs): Not irritating

**Respiratory or Skin Sensitization  
Product:** No data available.

**Carcinogenicity  
Product:** No data available.

**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Asphalt	Overall evaluation: Possibly carcinogenic to humans.
Crystalline Silica (Quartz)/ Silica Sand	Overall evaluation: Carcinogenic to humans.
Fibrous Glass	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Possibly carcinogenic to humans. Overall evaluation: Possibly carcinogenic to humans.
Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Carbon Black	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

**US. National Toxicology Program (NTP) Report on Carcinogens:**

Crystalline Silica (Quartz)/ Silica Sand	Known To Be Human Carcinogen.
Fibrous Glass	Reasonably Anticipated to be a Human Carcinogen. Reasonably Anticipated to be a Human Carcinogen.
Hydrotreated heavy naphthenic distillate	Known To Be Human Carcinogen.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):**

No carcinogenic components identified

**Germ Cell Mutagenicity**

**In vitro**  
**Product:** No data available.

**In vivo**  
**Product:** No data available.

**Reproductive toxicity**  
**Product:** No data available.

**Specific Target Organ Toxicity - Single Exposure**  
**Product:** No data available.

**Specific Target Organ Toxicity - Repeated Exposure**  
**Product:** No data available.

**Aspiration Hazard**  
**Product:** No data available.

**Other effects:** No data available.

## 12. Ecological information

### Ecotoxicity:

#### Acute hazards to the aquatic environment:

##### Fish

**Product:** No data available.

##### Aquatic Invertebrates

**Product:** No data available.

#### Chronic hazards to the aquatic environment:

##### Fish

**Product:** No data available.

##### Specified substance(s):

Asphalt NOAEL (Oncorhynchus mykiss, 28 d):  $\geq 1,000$  mg/l interpreted

Carbon Black NOAEL (Salmo sp., 30 d): 17 mg/l QSAR

Hydrotreated heavy naphthenic distillate NOAEL (Oncorhynchus mykiss, 14 d):  $\geq 1,000$  mg/l QSAR

Iron oxide LOAEL (Pimephales promelas, 33 d): 1.6 mg/l experimental result

##### Aquatic Invertebrates

**Product:** No data available.

##### Toxicity to Aquatic Plants

**Product:** No data available.

### Persistence and Degradability

##### Biodegradation

**Product:** No data available.

##### BOD/COD Ratio

**Product:** No data available.

### Bioaccumulative Potential

##### Bioconcentration Factor (BCF)

**Product:** No data available.

##### Partition Coefficient n-octanol / water (log Kow)

**Product:** No data available.

**Mobility in Soil:** No data available.

**Other Adverse Effects:** No data available.

### 13. Disposal considerations

**Disposal instructions:** Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

**Contaminated Packaging:** No data available.

### 14. Transport information

**TDG:**

Not Regulated

**CFR / DOT:**

Not Regulated

**IMDG:**

Not Regulated

### 15. Regulatory information

**US Federal Regulations**

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**  
None present or none present in regulated quantities.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

**Chemical Identity**

Formaldehyde

**OSHA hazard(s)**

Acute toxicity  
Skin irritation  
Skin sensitization  
Flammability  
respiratory tract irritation  
Respiratory sensitization  
Cancer  
Eye irritation

**CERCLA Hazardous Substance List (40 CFR 302.4):**

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Asphalt	100 lbs.
Formaldehyde	100 lbs.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)****Hazard categories**

Delayed (Chronic) Health Hazard

**SARA 302 Extremely Hazardous Substance**

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Formaldehyde	100 lbs.	500 lbs.

**SARA 304 Emergency Release Notification**

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Asphalt	100 lbs.
Phthalocyanine green	
Formaldehyde	100 lbs.

**SARA 311/312 Hazardous Chemical**

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Formaldehyde	500lbs
Calcium Carbonate (Limestone)	500 lbs
Asphalt	500 lbs
Crystalline Silica (Quartz)/ Silica Sand	500 lbs
Magnesite	500 lbs
Fibrous Glass	500 lbs
Clay	500 lbs
Phthalocyanine green	500 lbs
Titanium dioxide	500 lbs
Carbon Black	500 lbs
Hydrotreated heavy naphthenic distillate	500 lbs
Iron oxide	500 lbs

**SARA 313 (TRI Reporting)**

None present or none present in regulated quantities.

**Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)**

None present or none present in regulated quantities.

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):**

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Formaldehyde	15000 lbs

**US State Regulations****US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

## **US. New Jersey Worker and Community Right-to-Know Act**

### **Chemical Identity**

Calcium Carbonate (Limestone)  
Asphalt  
Crystalline Silica (Quartz)/ Silica Sand  
Magnesite  
Fibrous Glass  
Clay

## **US. Massachusetts RTK - Substance List**

### **Chemical Identity**

Calcium Carbonate (Limestone)  
Asphalt  
Crystalline Silica (Quartz)/ Silica Sand  
Magnesite  
Fibrous Glass  
Clay  
Formaldehyde

## **US. Pennsylvania RTK - Hazardous Substances**

### **Chemical Identity**

Calcium Carbonate (Limestone)  
Asphalt  
Crystalline Silica (Quartz)/ Silica Sand  
Fibrous Glass  
Clay

## **US. Rhode Island RTK**

No ingredient regulated by RI Right-to-Know Law present.

## **Other Regulations:**

### **Inventory Status:**

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.



Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

<b>16. Other information, including date of preparation or last revision</b>
--

<b>Revision Date:</b>	07/28/2015
<b>Version #:</b>	1.0
<b>Further Information:</b>	No data available.
<b>Disclaimer:</b>	For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

