

Revision Date: 08/03/2015

SAFETY DATA SHEET

1. Identification

Material name: OB BURMASTIC COMPOSITE PLY HT

Material: 108700 601

Recommended use and restriction on use

Recommended use: Article Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S. Roofing 3735 Green Road Cleveland OH 44122

US

Contact person:EH&S DepartmentTelephone:216-292-5000

Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Carcinogenicity Category 1A

Unknown toxicity - Health

Acute toxicity, oral 48.19 %
Acute toxicity, dermal 56.07 %
Acute toxicity, inhalation, vapor 100 %
Acute toxicity, inhalation, dust or mist 100 %

Environmental Hazards

Acute hazards to the aquatic Category 3

environment

Unknown toxicity - Environment

Acute hazards to the aquatic 99.96 %

environment

Chronic hazards to the aquatic 100 %

environment

Label Elements

Hazard Symbol:



Signal Word: Danger



Revision Date: 08/03/2015

Hazard Statement: May cause cancer.

Harmful to aquatic life.

Precautionary Statement:

Prevention: Obtain special instructions before use. Do not handle until all safety

precautions have been read and understood. Use personal protective

equipment as required.

Response: If exposed or concerned: Get medical advice/attention.

Storage: Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Other hazards which do not result in GHS classification:

None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Asphalt	8052-42-4	40 - 70%
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	15 - 40%
Calcium Carbonate (Limestone)	1317-65-3	15 - 40%
Fibrous Glass	65997-17-3	5 - 10%
Magnesite	546-93-0	1 - 5%

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.

Inhalation: Move to fresh air.

Skin Contact: Wash skin thoroughly with soap and water. Get medical attention if

symptoms occur.

Eye contact: Any material that contacts the eye should be washed out immediately with

water. If easy to do, remove contact lenses. If eye irritation persists: Get

medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.



Revision Date: 08/03/2015

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be

worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: No data available.

Methods and material for containment and cleaning

up:

Collect spillage in containers, seal securely and deliver for disposal

according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in

accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or

spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Precautions for safe handling: Do not handle until all safety precautions have been read and understood.

Obtain special instructions before use. Use personal protective equipment as required. Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in

case of handling which causes formation of dust.

Conditions for safe storage,

including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection

Control Parameters



Revision Date: 08/03/2015

Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Asphalt - Inhalable fraction as benzene solubles	TWA	0.5 mg/m3	US. ACGIH Threshold Limit Values (2011)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	US. ACGIH Threshold Limit Values (2011)
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWA	2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Crystalline Silica (Quartz)/ Silica Sand - Total dust.	TWA	0.3 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Fibrous Glass - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Fibrous Glass - Fiber.	TWA	1 fibers/cm3	US. ACGIH Threshold Limit Values (03 2014)
	TWA	1 fibers/cm3	US. ACGIH Threshold Limit Values (03 2014)
	TWA	1 fibers/cm3	US. ACGIH Threshold Limit Values (03 2014)
	TWA	1 fibers/cm3	US. ACGIH Threshold Limit Values (03 2014)
	TWA	1 fibers/cm3	US. ACGIH Threshold Limit Values (03 2014)
	TWA	0.2 fibers/cm3	US. ACGIH Threshold Limit Values (03 2014)
Magnesite - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Magnesite - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)





Revision Date: 08/03/2015

Chemical name	type	Exposure Limit Values	Source
Asphalt - Aerosol, inhalable as benzene solubles	TWA	0.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Asphalt - Inhalable fraction as benzene solubles	TWAEV	0.5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Asphalt - Fume.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWAEV	0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Fibrous Glass - Fiber.	TWA	0.2 fibers/cm3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	fibers/cm3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)



Revision Date: 08/03/2015

Fibrous Glass - Inhalable fibers.	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Fibrous Glass - Inhalable	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Fibrous Glass - Respirable fibers.	TWAEV	1 fibers/mL	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Fibrous Glass - Fiber.	TWAEV	0.2 fibers/mL	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Fibrous Glass - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Fibrous Glass - Fiber.	TWA	fibres/cm3 (non- asbestos fibres) size restriction s apply	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	TWA	fibres/cm3 (non- asbestos fibres) size restriction s apply	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Magnesite - Total dust.	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Magnesite - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required.

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information: Good general ventilation (typically 10 air changes per hour) should be used.

Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists,

mechanical generation of dusts, drying of solids, etc.

Eye/face protection: Wear safety glasses with side shields (or goggles).



Revision Date: 08/03/2015

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other: Wear suitable protective clothing.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product.

9. Physical and chemical properties

Appearance

Physical state: solid
Form: solid
Color: Black
Odor: Slight

Odor threshold:

pH:

No data available.

No data available.

Melting point/freezing point:

No data available.

No data available.

No data available.

Flash Point:

No data available.

No data available.

Evaporation rate:

No data available.

Flammability (solid, gas): No Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper (%):

Explosive limit - lower (%):

No data available.

No data available.

No data available.

Vapor pressure:

No data available.

No data available.

No data available.

Relative density: 1.5

Solubility(ies)

Solubility in water:
Solubility (other):
No data available.
Partition coefficient (n-octanol/water):
No data available.
Auto-ignition temperature:
No data available.
Decomposition temperature:
No data available.
Viscosity:
No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.



Revision Date: 08/03/2015

Possibility of Hazardous

Reactions:

No data available.

Conditions to Avoid: Avoid heat or contamination.

Incompatible Materials: No data available.

Hazardous Decomposition

Products:

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise.

In high concentrations, vapors, fumes or mists may irritate nose, throat and

mucus membranes.

Skin Contact: May be harmful in contact with skin.

Eye contact: Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: 47,335.37 mg/kg

Dermal

Product: ATEmix: 2,152.35 mg/kg

Inhalation

Product: No data available.

Specified substance(s):

Asphalt LC 50 (Rat): > 94.4 mg/m3

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Asphalt in vivo (Rabbit, 24 hrs): Not irritating

Magnesite In vitro (Reconstituted Corneal Epithelium model, 10 min): Not irritating



Revision Date: 08/03/2015

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Asphalt Overall evaluation: Possibly carcinogenic to humans.

Crystalline Silica

(Quartz)/ Silica

Sand

Overall evaluation: Carcinogenic to humans.

Fibrous Glass Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall

evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Possibly carcinogenic to humans. Overall evaluation: Possibly

carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Crystalline Silica Known To Be Human Carcinogen.

(Quartz)/ Silica

Sand

Fibrous Glass Reasonably Anticipated to be a Human Carcinogen. Reasonably Anticipated

to be a Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.



Revision Date: 08/03/2015

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Aquatic Invertebrates

Product: No data available.

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Asphalt NOAEL (Oncorhynchus mykiss, 28 d): >= 1,000 mg/l interpreted

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Mobility in Soil: No data available.

Other Adverse Effects: Harmful to aquatic organisms.

13. Disposal considerations



Revision Date: 08/03/2015

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity Reportable quantity

Asphalt 100 lbs. Hydrogen sulfide 100 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

<u>Reportable</u>

Chemical Identity quantity Threshold Planning Quantity

Hydrogen sulfide 100 lbs. 500 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u> <u>Reportable quantity</u>

Asphalt 100 lbs. Hydrogen sulfide 100 lbs.



Revision Date: 08/03/2015

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u> <u>Threshold Planning Quantity</u>

Hydrogen sulfide 500lbs Asphalt 500 lbs Crystalline Silica (Quartz)/ 500 lbs

Silica Sand

Calcium Carbonate 500 lbs

(Limestone)

Fibrous Glass 500 lbs Magnesite 500 lbs

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Chemical Identity Reportable quantity

Hydrogen sulfide 10000 lbs

US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Asphalt

Crystalline Silica (Quartz)/ Silica Sand

Calcium Carbonate (Limestone)

Fibrous Glass

Magnesite

US. Massachusetts RTK - Substance List

Chemical Identity

Asphalt

Crystalline Silica (Quartz)/ Silica Sand

Calcium Carbonate (Limestone)

Fibrous Glass

Magnesite

Hydrogen sulfide

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Asphalt

Crystalline Silica (Quartz)/ Silica Sand

Calcium Carbonate (Limestone)

Fibrous Glass

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

Other Regulations:



Revision Date: 08/03/2015

Inventory Status:

Australia AICS:

One or more components in this product are

not listed on or exempt from the inventory.

Canada DSL Inventory List: All components in this product are listed on or

exempt from the Inventory.

EINECS, ELINCS or NLP: One or more components in this product are

not listed on or exempt from the Inventory.

Japan (ENCS) List:

One or more components in this product are

not listed on or exempt from the Inventory.

China Inv. Existing Chemical Substances: One or more components in this product are

not listed on or exempt from the Inventory.

Korea Existing Chemicals Inv. (KECI): One or more components in this product are

not listed on or exempt from the Inventory.

Canada NDSL Inventory: One or more components in this product are

not listed on or exempt from the Inventory.

Philippines PICCS: One or more components in this product are

not listed on or exempt from the Inventory.

US TSCA Inventory: All components in this product are listed on or

exempt from the Inventory.

New Zealand Inventory of Chemicals:

One or more components in this product are

not listed on or exempt from the Inventory.

Japan ISHL Listing: One or more components in this product are

not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are

not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date: 08/03/2015

Version #: 1.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard

information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including

the safe use of the product under every foreseeable condition.



Revision Date: 08/03/2015