

TPA FLEECE BACKED WB SINGLE PLY BA 5 GAL

Version 1.2

Print Date 05/11/2010

REVISION DATE: 04/11/2008

SECTION 1 - PRODUCT IDENTIFICATION

Trade name : TPA FLEECE BACKED WB SINGLE PLY BA 5 GAL
 Product code : 505420 805

COMPANY : Tremco Incorporated
 3735 Green Road
 Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST
 Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST
 After Hours: Chemtrec 1-800-424-9300

SECTION 2 - HAZARDS IDENTIFICATION
Emergency Overview

White. Liquid. Vapor may irritate respiratory tract. May cause nausea, headaches, and dizziness. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation : Vapor may irritate respiratory tract. May cause nausea, headaches, and dizziness.
 Eyes : Direct contact may cause mild irritation. May cause temporary injury.
 Ingestion : May cause gastrointestinal irritation, nausea, and vomiting.
 Skin : May cause sensitization resulting in irritation, itching and redness.

Aggravated Medical Conditions

Pre-existing eye, skin, liver, kidney, and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Methanol (methyl alcohol) may cause adverse liver, kidney, lung, spleen and nervous system damage. Ingestion may cause visual disturbances including optic nerve damage and blindness. Prolonged or repeated exposure may cause defatting, drying, and irritation of the skin, dermatitis, central nervous system (CNS) effects, heart muscle sensitization and arrhythmia, hearing loss, and brain, liver, kidney, and testes damage. Toluene overexposure may cause burns of the skin, respiratory tract damage. May be harmful to the human fetus based on animal tests and limited epidemiology data. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

Target Organs: Skin, Eye, Ingestion, Lung

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %
Water	7732-18-5	30.0 - 60.0
Synthetic Rubber	NJ TSRN# 51721300-5675P	30.0 - 60.0
Hydrocarbon Resin	NJ TSRN# 51721300-5677P	10.0 - 30.0
Toluene	108-88-3	7.0 - 13.0
Non-Hazardous Filler	NJ TSRN# 51721300-6167P	3.0 - 7.0
Titanium dioxide	13463-67-7	1.0 - 5.0
Methanol	67-56-1	1.0 - 5.0

TPA FLEECE BACKED WB SINGLE PLY BA 5 GAL

Version 1.2

Print Date 05/11/2010

REVISION DATE: 04/11/2008

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

- | | | |
|--------------|---|--|
| Inhalation | : | Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention. |
| Eye contact | : | Flush with water for 15 minutes. If irritation persists, get medical attention. |
| Skin contact | : | Wash area of contact thoroughly with hand cleaner followed by soap and water. If irritation, rash or other disorders develop, get medical attention immediately. |
| Ingestion | : | Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately. |

SECTION 5 - FIRE FIGHTING MEASURES

- | | | |
|---------------------------------------|---|---|
| Flash point | : | 142 °F, 61 °C |
| Method | : | Not available. |
| Lower explosion limit | : | Not available. |
| Upper explosion limit | : | Not available. |
| Autoignition temperature | : | Not available. |
| Extinguishing media | : | If water fog is ineffective, use carbon dioxide, dry chemical or foam. |
| Hazardous combustion products | : | Smoke, fumes. Carbon monoxide and carbon dioxide can form. |
| Protective equipment for firefighters | : | Water may be used to cool containers to minimize pressure build-up. Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA). |
| Fire and explosion conditions | : | Closed container, may burst when exposed to extreme heat. Empty containers may contain ignitable vapors. Vapor concentrations in enclosed areas may ignite explosively. Vapors may travel to sources of ignition and flashback. |

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Remove sources of ignition immediately. Stop flow of material if safe to do so. Contain spill and keep out of water courses. Ventilate area.

SECTION 7 - HANDLING AND STORAGE

Store under dry warehouse conditions away from heat and all ignition sources. Store in a cool, well ventilated area. Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Do not smoke, weld, generate sparks, or use flame near container. Change soiled work clothes frequently. Clean hands thoroughly after handling.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION
Personal protection equipment



TPA FLEECE BACKED WB SINGLE PLY BA 5 GAL

Version 1.2

Print Date 05/11/2010

REVISION DATE: 04/11/2008

- Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved organic vapor or supplied air respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
- Hand protection : Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure.
- Eye protection : Chemical splash goggles.
- Protective measures : Use professional judgment in the selection, care, and use.
- Engineering measures : Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use general ventilation and/ or local exhaust to reduce the airborne contaminant concentration below the exposure limit listed in the MSDS

Exposure Limits

Chemical Name	CAS Number	Regulation	Limit	Form
Toluene	108-88-3	ACGIH TWA: OSHA TWA:	20 ppm 200 ppm	
Titanium dioxide	13463-67-7	ACGIH TWA: OSHA PEL: OSHA TWA: OSHA TWA:	10 mg/m3 15 mg/m3 15 mg/m3 5 mg/m3	Total dust. Total dust. Respirable fraction.
Methanol	67-56-1	ACGIH TWA: ACGIH STEL: OSHA PEL:	200 ppm 250 ppm 260 mg/m3	

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

- Form : Liquid
- Color : White
- Odor : Neutral
- pH : Not available.
- Vapour pressure : Not available.
- Vapor density : Heavier than air
- Melting point/range : Not available.
- Freezing point : Not available.
- Boiling point/range : Not available.
- Water solubility : Negligible
- Specific Gravity : 1.078
- % Volatile Weight : 46 %

SECTION 10 - REACTIVITY / STABILITY

- Substances to avoid : Epoxy curing agents. Amines and oxidizing agents.

TPA FLEECE BACKED WB SINGLE PLY BA 5 GAL

Version 1.2

Print Date 05/11/2010

REVISION DATE: 04/11/2008

Stability : Material is stable under normal storage, handling, and use.

Hazardous polymerization : Will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

Toluene, CAS-No.: 108-88-3

Acute oral toxicity (LD-50 oral)	2,600 - 7,500 mg/kg (Rat) 5,000 mg/kg (Rat)
Acute inhalation toxicity (LC-50)	26,700 mg/l for 1 h (Rat) 400 mg/l for 24 h (Mouse) 5,320 mg/l for 8 h (Mouse)
Acute dermal toxicity (LD-50 dermal)	12,124 mg/kg (Rabbit)

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method : Recycle or dispose of in compliance with local, provincial and federal regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA

TDG / DOT Shipping Description:

NOT REGULATED

SECTION 15 - REGULATORY INFORMATION
North American Inventories:

All components are listed or exempt from the TSCA inventory.

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

SARA 313 Components	:	Toluene	108-88-3
		Methanol	67-56-1

SARA 311/312 Hazards	:	Acute Health Hazard
		Fire Hazard

OSHA Hazardous Components :

Toluene	108-88-3
Titanium dioxide	13463-67-7
Methanol	67-56-1

OSHA Status: Considered : Irritant
hazardous based on the following criteria:

OSHA Flammability : IIIA



TPA FLEECE BACKED WB SINGLE PLY BA 5 GAL

Version 1.2

Print Date 05/11/2010

REVISION DATE: 04/11/2008

Regulatory VOC (less water and exempt solvent) : 178 g/l

VOC Method 310 : 9 %

U.S. State Regulations:

MASS RTK Components : Toluene 108-88-3
Titanium dioxide 13463-67-7
Methanol 67-56-1

Penn RTK Components : Water 7732-18-5
Synthetic Rubber NJ TSRN# 51721300-5675P
Hydrocarbon Resin NJ TSRN# 51721300-5677P
Toluene 108-88-3
Non-Hazardous Filler NJ TSRN# 51721300-6167P
Titanium dioxide 13463-67-7
Methanol 67-56-1

NJ RTK Components : Water 7732-18-5
Synthetic Rubber NJ TSRN# 51721300-5675P
Hydrocarbon Resin NJ TSRN# 51721300-5677P
Toluene 108-88-3
Non-Hazardous Filler NJ TSRN# 51721300-6167P
Titanium dioxide 13463-67-7
Methanol 67-56-1

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm:

108-88-3 Toluene

SECTION 16 - OTHER INFORMATION

HMSIS Rating :

Health	2
Flammability	2
Reactivity	0
PPE	B

0 = Minimum
1 = Slight
2 = Moderate
3 = Serious
4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

ACGIH - American Conference of Governmental Hygienists
CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act
DOT - Department of Transportation
DSL - Domestic Substance List
EPA - Environmental Protection Agency

PEL - Permissible Exposure Limit
RCRA - Resource Conservation and Recovery Act
RTK - Right To Know
SARA - Superfund Amendments and Reauthorization Act
STEL - Short Term Exposure Limit



TPA FLEECE BACKED WB SINGLE PLY BA 5 GAL

Version 1.2

Print Date 05/11/2010

REVISION DATE: 04/11/2008

HMIS - Hazardous Materials Information System
IARC - International Agency for Research on Cancer
MSHA - Mine Safety Health Administration
NDSL - Non-Domestic Substance List
NIOSH - National Institute for Occupational Safety and Health
NTP - National Toxicology Program
OSHA - Occupational Safety and Health Administration

TLV - Threshold Limit Value
TSCA - Toxic Substances Control Act
TWA - Time Weighted Average
V - Volume
VOC - Volatile Organic Compound
WHMIS - Workplace Hazardous Materials Information System