

## LEED DATA SHEET

DATE:		
PROJECT NAME:		
PROJECT LOCATION:		
NAME OF PRODUCT:	ELS	
DESCRIPTION:	A Heavily Fibrated Asphalt Mastic for General Roof Repair	
PRODUCT/MATERIAL COST: \$		

### SOLAR REFLECTIVITY INDEX (SRI)

PAVING & SLOPED ROOF >2:12 MUST BE AT LEAST 29:	N/A
LOW SLOPED ROOF MATERIALS MUST BE AT LEAST 78:	N/A

### RECYCLED CONTENT

PRE-CONSUMER:	4.66	%
POST CONSUMER:	0	%

### REGIONAL QUALIFICATIONS FOR PRODUCT/MATERIALS:

		DISTANCE FROM PROJECT:	MILES
LOCATION OF PROCESS:		DISTANCE FROM PROJECT:	MILES
LOCATION OF MANUFACTURE:	Cleveland, OH	DISTANCE FROM PROJECT:	MILES

### LOW EMITTING MATERIALS:

COATING VOC <small>(GRAMS/L)</small>	SEALANT VOC <small>(GRAMS/L)</small>	ADHESIVE VOC <small>(GRAMS/L)</small>	USE OF MATERIAL
		<190 g/L	

### RAPIDLY RENEWABLE MATERIAL:

PERCENT RENEWABLE:	0	%
COST:	\$	

PREPARED BY:	
--------------	--

*\*Extraction/Process/Manufacture is defined as the assembly of a final product not including on-site assembly or installation.  
 \*\*Due to several sources of raw materials for this product, specifying the origin of the component materials may not be possible.*