

Cured Cover Strip

Self-Adhering Cover Strip

Composition: Tremco Cured Cover strip is a cured 0.030" EPDM membrane laminated to a 0.035" black butyl-based pressure-sensitive fully cured adhesive/sealant tape for single ply roofing membranes.

Basic Uses: Tremco Cured Cover strip can be used as a cover for metal and polymeric fastening plates and bars, gravel stop flashing, patching and repairing seams. Tremco Cured Cover strip was specifically developed for use with EPDM single ply membranes. However, it adheres well to most types of single ply roofing membranes.

Limitations:

- Do not apply over wet surfaces
- Do not apply over asphalt mastics or previously applied adhesives

Packaging: Available rolls 6"x100' 2-rolls/box, 9",12" x 100' 1-roll/box

Storage Life: 12 months stored indoors, out of direct sunlight between 60° F (15° C) and 80° F (26.6° C).

Surface Preparation: Surface must be clean, dry, free of dirt, oil, debris, dust, and other contaminants.

Product Advantages	
Features	Benefits
Easy, Fast Application	• Reduces Labor Cost
100% Solids	• No Volatile Organic Compounds
Excellent heat, water, and chemical resistance	• Long performance life

Application: Prime area to be sealed with Tremco Primer/Splice Wash. Allow primer/splice wash to dry. Then align and center Tremco Cured Cover strip over the seam or repair area. Unroll a 12-18" section of cover strip so that the butyl adhesive portion of the cover strip is temporarily exposed. The applicator should place the knee on the exposed release paper while unrolling and aligning additional sections of the cover strip. Apply firm hand pressure. Cut cover strip to desired length. Adjacent sections of cover strip should be butted and sealed with uncured flashing. Apply firm pressure with a hand roller along the length and width of the cover strip to ensure a watertight seal.

Coverage:

6" x 100' approximately 50 sq.ft./roll
9" x 100' approximately 75 sq.ft./roll
12" x 100' approximately 100 sq.ft./roll

Precautions: Users must read container labels and Material Safety Data Sheets for health and safety precautions prior to use.

Availability and Cost: Contact your local Tremco Roofing Representative for pricing and availability. For the name and number of your Representative, call the Roofing Division at 216/292-5000.

Maintenance: Your local Tremco Roofing Representative can provide you with effective maintenance procedures which may vary, depending upon specific conditions. Periodic inspections, early repairs and preventive maintenance are all part of a sound roof program.

Guarantee/Warranty: Tremco Inc. warrants Cured Cover Strip to be free of defects and to meet published physical properties when tested according to ASTM and Tremco standards. Under this warranty, any Cured Cover Strip product that is proved to be defective when applied in accordance to our written instruc-

TREMCO

Roofing & Weatherproofing Peace of Mind™

tions, and in applications recommended by Tremco as suitable for this product will be replaced with like product at no charge. THIS IS BUYERS SOLE AND EXCLUSIVE REMEDY.

All claims concerning product defects must be made in writing within twelve (12) months of shipment. The absence of such claims in writing during this period will constitute a waiver of all claims with respect to such product. This warranty shall be IN LIEU OF any other warranty, express or implied, including but not limited to, any implied warranty of MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Technical Services: Your local Tremco Representative, working with the Technical Service Staff, can help analyze conditions and needs to develop recommendations for special applications. The services of the Tremco Research Center, which has earned a unique reputation in weatherproofing technology, complement and extend the services of the Tremco Technical Service staff.

Statement of Policy and Responsibility: Tremco takes responsibility for furnishing quality materials and for providing specifications and recommendations for their proper installation.

As neither Tremco itself nor its Representatives practice architecture or engineering, Tremco offers no opinion on, and expressly disclaims any responsibility for the soundness of any structure on which its products may be applied. If questions arise as to the soundness of a structure or its ability to support a planned installation properly, the Owner should obtain the opinion of competent structural engineers before proceeding. Tremco accepts no liability for any structural failure or for resultant damages, and no Tremco Representative is authorized to vary this disclaimer.

Physical Performance Characteristics

Cured Cover Strip Adhesive/Sealant		
Property	Typical Value	Test Method
Tensile	100 psi	ASTM 412
Elongation	1,200%	ASTM 412
Heat Aging at 300°F	No appearance change after 180 hrs	ASTM 412
Brittleness Temperature °F	Less than -50	ASTM 412

TREMCO

An **RPM** Company

3735 Green Road
Beachwood, OH 44122
216-292-5000

220 Wicksteed Ave
Toronto, ONT M4H 1G7
416-421-3300

R00-409
Printed in USA

Rev. 3/98