

## ***A single-component, quick-drying primer for Geogard and AlphaGuard products***

<b>DESCRIPTION:</b>	Geogard Primer is a single component primer designed to enhance adhesion when using Tremco urethane primer products including AlphaGuard, Geogard, and urethane sealants.		
<b>BASIC USES:</b>	Geogard Primer is utilized to promote adhesion of cured urethane coatings and sealants to newly applied coats. It can also be used as primer over approved substrates. To determine if a substrate is approved, reference current Tremco literature or contact Tremco Product & Technical Group.		
<b>ADVANTAGES:</b>	Geogard Primer is a quick drying primer with excellent adhesion properties.		
<b>PREPARATION:</b>	All surfaces are to be free of dirt, grease, oil, chalk, loose paint, rust, mortar, and other foreign matter, which could prevent proper adhesion. This is best accomplished by power washing or utilizing a stiff broom. All surfaces must be completely dry prior to the application of GEOGARD Primer.		
<b>APPLICATION:</b>	Geogard Primer can be brush, roller, or spray applied. Apply primer evenly on surface at the recommended coverage rate. Do not allow the product to puddle. Once the primer becomes dry and tacky (typically 15-30 mins) it can be top coated. Primer must be top coated prior to curing hard, glossy, and tack-free (typically within 1-2 hours). If this occurs, clean the primed area and re-prime following the application instructions listed above.		
<b>COVERAGE:</b>	400 sq. ft. / gal (4 wet mils)		
<b>LIMITATIONS:</b>	Apply only when ambient temperatures are 40F and rising. Do not apply over wet or damp surfaces or when precipitation is imminent. Only apply over approved substrates and products. Exposed primer will yellow as it weathers.		
<b>MAINTENANCE:</b>	GEOGARD Primer is designed to be top coated with an approved Tremco urethane product. It is recommended that the coating installation be checked on a regular schedule with additional inspections after the system has been exposed to severe weather conditions. Small area touch-up can be made at any time by following the recommended application procedures.		
<b>TECHNICAL SERVICES:</b>	Technical advice or service on suitability of material for specific application and end-use requirements is available from the manufacturer. Refer to label and Safety Data Sheet (SDS) for precautionary information.		
<b>PHYSICAL PROPERTIES:</b>	<b>Property</b>	<b>Test Method</b>	<b>Typical Value</b>
	Weight per Gallon	ASTM D 1475	10.32 lbs.
	Viscosity	ASTM D 562	20-50 CPS
	VOC		5 g/L
	Dry Time		15-30 mins at 70°F (21°C)
	Flashpoint	ASTM D 3278	109°F (43°C)
	Clean Up		Xylene

# Geogard® Primer



TDS 7019  
08/30/16

**[www.tremcoroofing.com](http://www.tremcoroofing.com)**  
3735 Green Road  
Beachwood, Ohio 44122  
1.800.852.6013



50 Beth Neelson Drive  
Toronto, Ontario M4H 1M6  
1.800.668.9879

GEOGARD is a U.S. registered trademark of Republic Powdered Metals, Inc.

The information provided on this data sheet is effective as of August 2016 and supersedes all previous data concerning this product and its application.

The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCES SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.