

# TremPly® TPO 6" Cover Tape



## *An Accessory designed for TremPly TPO Single Ply Roof System*

### FEATURES

Cost effective

Factory-built accessories

Uniform look

### BENEFITS

Reduces installed costs

Improved reliability, reduces risk of leaks and callbacks

Improved aesthetics

### DESCRIPTION:

TremPly® TPO 6" Cover Tape provides roofing contractors with an easy-to-install, factory-built detail. It is constructed from Tremco's proven, durable, high-performance TremPly TPO.

### BASIC USES:

TremPly TPO 6" Cover Tape is a 6" (152 mm) wide, non-reinforced TPO membrane backed with a butyl tape adhesive. For use in stripping-in primed galvanized edge metal and to install end laps.

### COLORS:

White, Tan, Gray

### PACKAGING:

Roll length 100' (30.5 m), Roll width 6" (152 mm).  
2 Rolls per case, Case weight 37.4 lb. (16.96 kg), 27 Cases per pallet.

### APPLICATION:

For use in stripping-in primed, galvanized edge metal. Using soap and water, clean the entire surface and roof membrane to be covered. Dry the entire area. Wipe area to be primed with a white cloth moistened with TremPly TPO Cleaner. Brush or roller-apply TremPly Primer 3" (76 mm) onto each surface, carrying this past the ends 3" (76 mm). Install the TremPly TPO 6" Cover Tape over the primer after flash-off and roll-in with a silicone roller.

### MAINTENANCE:

Your local Tremco Roofing representative can provide you with effective maintenance procedures, which may vary depending upon specific conditions. Periodic inspections, early repairs and preventive maintenance are all part of a sound roof program.

### TECHNICAL SERVICES:

Your local Tremco Roofing representative, working with the Technical Service Staff, can help analyze conditions and needs to develop recommendations for special applications.



7154  
3/20/18

[www.tremcoroofing.com](http://www.tremcoroofing.com)  
3735 Green Road  
Beachwood, Ohio 44122  
1.800.852.6013



50 Beth Neelson Drive  
Toronto, Ontario M4H 1M6  
1.800.668.9879

TremPly is a U.S. registered trademark of Tremco Incorporated

The information provided on this data sheet is effective as of December 2017 and supersedes all previous data concerning this product and its application.

The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCES SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.