

TremPly® TPO LV Bonding Adhesive



An Accessory Designed for TremPly TPO Single Ply Roof System

FEATURES

Low VOC— <250 g/L
 High coverage
 Fast-drying solvent system
 Roller or brush application
 High initial tack

BENEFITS

Environmentally friendly
 Up to 120 sq. ft. per gallon (2.95 m²/liter) of bonded membrane
 Quicker application time
 Easy application
 Quicker application time

DESCRIPTION:

TremPly® TPO LV Bonding Adhesive contains less than 250 grams per liter of Volatile Organic Compounds (VOCs) and has been formulated using a blend of VOC exempt and non-exempt solvents to be in compliance with air quality regulations for single ply roofing adhesives.

BASIC USES:

TremPly TPO LV Bonding Adhesive is a contact-type bonding adhesive specially designed for bonding TPO single-ply roofing membranes and flashings to various roofing substrates.

COLOR:

Yellow

PACKAGING:

5-gallon (18.93 liter) pails; Weight, 40 lb. (18.14 kg); 45 pails per pallet

APPLICATION:

Roller, brush, or spray. Recommended storage temperature range 40°F – 90°F (4.4°C – 32.2°C). Shelf life approximately one year. Storage for continued periods outside this temperature range may shorten shelf life.

Installation: Minimum application temperature of bonding adhesive is 40°F (4.4°C) and rising.

Base: Synthetic polymer

Flash Point: -9.4°F (-23°C)

Viscosity: 1,200 – 1,700 cps

Coverage: 100 – 120 sq. ft./ gallon (2.45 – 2.95 m²/liter)

Total Solids: 38% +/- 1% VOC: 247 grams/liter

Open Time: Up to 60 minutes **Dry Time:** 5 – 15 minutes Application

VOC: <245 g/l

Solvent: VOC-compliant blend

Weight/Gallon: 8 lb. (3.63 kg/liter)

Shelf Life: 1 year, unopened

MAINTENANCE:

Your local Tremco Roofing representative can provide you with effective maintenance procedures, which may vary depending upon specific conditions. Periodic inspections, early repairs and preventive maintenance are all part of a sound roof program.

TECHNICAL SERVICES:

Your local Tremco Roofing representative, working with the Technical Service Staff, can help analyze conditions and needs to develop recommendations for special applications.



7136
6/13/18

www.tremcoroofing.com
 3735 Green Road
 Beachwood, Ohio 44122
 1.800.852.6013

50 Beth Neelson Drive
 Toronto, Ontario M4H 1M6
 1.800.668.9879



TremPly is a U.S. registered trademark of Tremco Incorporated.

The information provided on this data sheet is effective as of December 2017 and supersedes all previous data concerning this product and its application.

The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCES SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.