

Revision Date: 10/12/2018

# **SAFETY DATA SHEET**

# 1. Identification

Material name: TREMPRIME Q.D. LOW ODOR 55 GL

Material: 022045A855

Recommended use and restriction on use

Recommended use: Coatings Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S. Roofing 3735 Green Road Beachwood OH 44122

US

Contact person:EH&S DepartmentTelephone:216-292-5000

**Emergency telephone number:** 1-800-424-9300 (US); 1-613-996-6666 (Canada)

# 2. Hazard(s) identification

## **Hazard Classification**

#### **Physical Hazards**

Flammable liquids Category 3

## **Health Hazards**

Acute toxicity (Inhalation - vapor) Category 4
Serious Eye Damage/Eye Irritation Category 2A
Germ Cell Mutagenicity Category 1B
Carcinogenicity Category 1B

# **Unknown toxicity - Health**

Acute toxicity, oral 40.8 %
Acute toxicity, dermal 43 %
Acute toxicity, inhalation, vapor 97 %
Acute toxicity, inhalation, dust 100 %

or mist

## **Label Elements**

### **Hazard Symbol:**



Revision Date: 10/12/2018



Signal Word: Danger

Hazard Statement: Flammable liquid and vapor.

Harmful if inhaled.

Causes serious eye irritation. May cause genetic defects.

May cause cancer.

Precautionary Statements

**Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Keep container tightly closed. Ground and bond

container and receiving equipment. Use explosion-proof

[electrical/ventilating/lighting/...] equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective

clothing/eye protection/face protection. Avoid breathing

dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and

understood. Use personal protective equipment as required.

**Response:** IF INHALED: Remove person to fresh air and keep comfortable for

breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. Call a POISON CENTER/doctor if you feel unwell. In case of fire: Use... to

extinguish.

Storage: Store in a well-ventilated place. Keep cool. Store locked up.

**Disposal:** Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC):

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and

vapor. May cause flash fire or explosion.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical Identity	CAS number	Content in percent (%)*



Revision Date: 10/12/2018

Oxidized asphalt	64742-93-4	40 - 70%
Stoddard solvent (Mineral Spirits)	8052-41-3	40 - 70%
Nonane	111-84-2	3 - 7%
Trimethyl benzene (mixed isomers)	25551-13-7	1 - 5%

<sup>\*</sup> All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### 4. First-aid measures

Ingestion: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

**Inhalation:** Move to fresh air.

Skin Contact: Wash skin thoroughly with soap and water. Take off immediately all

contaminated clothing. If skin irritation occurs: Get medical advice/attention.

**Eye contact:** Immediately flush with plenty of water for at least 15 minutes. If easy to do,

remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

**Symptoms:** Respiratory tract irritation.

Indication of immediate medical attention and special treatment needed

**Treatment:** Symptoms may be delayed.

# 5. Fire-fighting measures

**General Fire Hazards:** Use water spray to keep fire-exposed containers cool. Water may be

ineffective in fighting the fire. Fight fire from a protected location. Move

containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from

the chemical:

Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of

vapors or gases to explosive concentrations.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.



Revision Date: 10/12/2018

Special protective equipment for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

# 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind.

Methods and material for containment and cleaning up:

Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

**Notification Procedures:** 

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

**Environmental Precautions:** 

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

# 7. Handling and storage

Precautions for safe handling:

Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities:

Store locked up. Store in a well-ventilated place. Store in a cool place.

# 8. Exposure controls/personal protection

## **Control Parameters**

# **Occupational Exposure Limits**

Chemical Identity	Туре	Exposure Limit Values	Source
Stoddard solvent (Mineral Spirits)	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	500 ppm 2,900 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Nonane	TWA	200 ppm	US. ACGIH Threshold Limit Values (02 2012)
Trimethyl benzene (mixed isomers)	TWA	25 ppm	US. ACGIH Threshold Limit Values (2011)



Revision Date: 10/12/2018

Chemical name	Туре	Exposure Limit Values	Source
Stoddard solvent (Mineral Spirits)	STEL	580 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	290 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Stoddard solvent (Mineral Spirits)	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Stoddard solvent (Mineral Spirits)	TWA	100 ppm 525 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Nonane	TWA	200 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Nonane	TWA	200 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Nonane	TWA	200 ppm 1,050 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Trimethyl benzene (mixed isomers)	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Trimethyl benzene (mixed isomers)	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Trimethyl benzene (mixed isomers)	TWA	25 ppm 123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

# Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

# Individual protection measures, such as personal protective equipment

**General information:** Provide easy access to water supply and eye wash facilities. Good general

ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable

level. Use explosion-proof ventilation equipment.

**Eye/face protection:** Wear safety glasses with side shields (or goggles).

**Skin Protection** 

**Hand Protection:** Use suitable protective gloves if risk of skin contact.

Other: Wear suitable protective clothing.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.



Revision Date: 10/12/2018

**Hygiene measures:** Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product. Avoid contact with eyes. When

using do not smoke.

# 9. Physical and chemical properties

**Appearance** 

Physical state: liquid

Form: Viscous Liquid

Color: Black

Odor: Mild petroleum/solvent
Odor threshold: No data available.

pH: No data available.

Melting point/freezing point: No data available.

Initial boiling point and boiling range: 149 °C 300 °F

Flash Point: 38 °C 100 °F(Tag closed cup)

**Evaporation rate:** Slower than Ether

Flammability (solid, gas):

No
Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%): 6.7 %(V)Flammability limit - lower (%): 0.9 %(V)

Explosive limit - upper (%):

Explosive limit - lower (%):

No data available.

Vapor pressure:

No data available.

Vapor density: Vapors are heavier than air and may travel along the floor and

in the bottom of containers.

Relative density: 0.892

Solubility(ies)

Solubility in water: Practically Insoluble
Solubility (other): No data available.

Partition coefficient (n-octanol/water): No data available.

Auto-ignition temperature:No data available.Decomposition temperature:No data available.Viscosity:No data available.

# 10. Stability and reactivity

Reactivity: No data available.

**Chemical Stability:** Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.

Conditions to avoid: Heat, sparks, flames.



Revision Date: 10/12/2018

Incompatible Materials: Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and

chromates).

**Hazardous Decomposition** 

Products:

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.

# 11. Toxicological information

Information on likely routes of exposure

**Inhalation:** In high concentrations, vapors, fumes or mists may irritate nose, throat and

mucus membranes.

**Skin Contact:** May be harmful in contact with skin. Causes mild skin irritation.

**Eye contact:** Causes serious eye irritation.

**Ingestion:** May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

**Inhalation:** No data available.

**Skin Contact:** No data available.

**Eye contact:** No data available.

**Ingestion:** No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

**Product:** Not classified for acute toxicity based on available data.

Specified substance(s):

Oxidized asphalt LD 50 (Rat): > 5,000 mg/kg

Nonane LD 50 (Rat): > 5,000 mg/kg

Trimethyl benzene

(mixed isomers)

LD 50 (Rat): 8,970 mg/kg

Dermal

**Product:** ATEmix: 2,000 mg/kg

Inhalation

**Product:** ATEmix: 17 mg/l

Repeated dose toxicity

**Product:** No data available.



Revision Date: 10/12/2018

Skin Corrosion/Irritation

**Product:** No data available.

Specified substance(s):

Oxidized asphalt in vivo (Rabbit): Not irritant Read-across from supporting substance

(structural analogue or surrogate), Key study

Nonane in vivo (Rabbit): Irritating Read-across based on grouping of substances

(category approach), Key study

Serious Eye Damage/Eye Irritation

**Product:** No data available.

Specified substance(s):

Oxidized asphalt Rabbit, 24 hrs: Not irritating

Nonane Rabbit, 24 - 72 hrs: Not irritating

**Respiratory or Skin Sensitization** 

**Product:** No data available.

Carcinogenicity

**Product:** May cause cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

**US. National Toxicology Program (NTP) Report on Carcinogens:** 

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

**Germ Cell Mutagenicity** 

In vitro

**Product:** No data available.

In vivo

**Product:** No data available.

Reproductive toxicity

**Product:** No data available.



Revision Date: 10/12/2018

**Specific Target Organ Toxicity - Single Exposure** 

**Product:** No data available.

**Specific Target Organ Toxicity - Repeated Exposure** 

**Product:** No data available.

**Aspiration Hazard** 

**Product:** No data available.

Other effects: No data available.

# 12. Ecological information

# **Ecotoxicity:**

# Acute hazards to the aquatic environment:

Fish

**Product:** No data available.

**Aquatic Invertebrates** 

**Product:** No data available.

Specified substance(s):

Trimethyl benzene LC 50 (Daggerblade grass shrimp (Palaemonetes pugio), 24 h): 7 mg/l

(mixed isomers) Mortality

# Chronic hazards to the aquatic environment:

**Fish** 

**Product:** No data available.

Specified substance(s):

Oxidized asphalt LL 50 (Oncorhynchus mykiss, 28 d): > 1,000 mg/l QSAR QSAR, Key study

NOAEL (Oncorhynchus mykiss, 28 d): >= 1,000 mg/l QSAR QSAR, Key

study

**Aquatic Invertebrates** 

**Product:** No data available.

**Toxicity to Aquatic Plants** 

**Product:** No data available.

# **Persistence and Degradability**



Revision Date: 10/12/2018

Biodegradation

**Product:** No data available.

**BOD/COD Ratio** 

**Product:** No data available.

Bioaccumulative potential

**Bioconcentration Factor (BCF)** 

**Product:** No data available.

Partition Coefficient n-octanol / water (log Kow)

**Product:** No data available.

Specified substance(s):

Stoddard solvent (Mineral Log Kow: 3.16 - 7.15

Spirits)

Nonane Log Kow: 5.46

Mobility in soil: No data available.

Other adverse effects: No data available.

13. Disposal considerations

**Disposal instructions:** Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Contaminated Packaging: No data available.

# 14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

UN1139, COATING SOLUTION, 3, PG III

# **Further Information:**

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.



Revision Date: 10/12/2018

# 15. Regulatory information

## **US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Chemical Identity Reportable quantity

Nonane De minimis concentration: TSCA 4% One-Time Export Notification only.

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

#### CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u> <u>Reportable quantity</u>

Nonane 100 lbs.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

# **Hazard categories**

Fire Hazard

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard

#### **SARA 302 Extremely Hazardous Substance**

None present or none present in regulated quantities.

# **SARA 304 Emergency Release Notification**

Chemical Identity Reportable quantity

Nonane 100 lbs.

# SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u> <u>Threshold Planning Quantity</u>

Oxidized asphalt 10000 lbs Stoddard solvent (Mineral 10000 lbs

Spirits)

Nonane 10000 lbs Trimethyl benzene (mixed 10000 lbs

isomers)

#### SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

# Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

#### **US State Regulations**

## **US. California Proposition 65**



WARNING

Cancer - www.P65Warnings.ca.gov



Revision Date: 10/12/2018

#### US. New Jersey Worker and Community Right-to-Know Act

# **Chemical Identity**

Oxidized asphalt

Stoddard solvent (Mineral Spirits)

Nonane

Trimethyl benzene (mixed isomers)

#### **US. Massachusetts RTK - Substance List**

#### **Chemical Identity**

Stoddard solvent (Mineral Spirits)

Nonane

Trimethyl benzene (mixed isomers)

# US. Pennsylvania RTK - Hazardous Substances

#### **Chemical Identity**

Oxidized asphalt

Stoddard solvent (Mineral Spirits)

Nonane

Trimethyl benzene (mixed isomers)

# **US. Rhode Island RTK**

# **Chemical Identity**

Stoddard solvent (Mineral Spirits)

Nonane

Trimethyl benzene (mixed isomers)

# International regulations

# **Montreal protocol**

Not applicable

# Stockholm convention

Not applicable

#### **Rotterdam convention**

Not applicable

# **Kyoto protocol**

Not applicable

# VOC:

Regulatory VOC (less water and : 410 g/l

exempt solvent)

VOC Method 310 : 46.00 %



Revision Date: 10/12/2018

**Inventory Status:** 

Australia AICS: All components in this product are listed on or

exempt from the Inventory.

Canada DSL Inventory List: All components in this product are listed on or

exempt from the Inventory.

EINECS, ELINCS or NLP: All components in this product are listed on or

exempt from the Inventory.

Japan (ENCS) List: All components in this product are listed on or

exempt from the Inventory.

China Inv. Existing Chemical Substances: All components in this product are listed on or

exempt from the Inventory.

Korea Existing Chemicals Inv. (KECI): All components in this product are listed on or

exempt from the Inventory.

Canada NDSL Inventory: One or more components in this product are

not listed on or exempt from the Inventory.

Philippines PICCS: All components in this product are listed on or

exempt from the Inventory.

US TSCA Inventory:

All components in this product are listed on or

exempt from the Inventory.

New Zealand Inventory of Chemicals: All components in this product are listed on or

exempt from the Inventory.

Japan ISHL Listing: All components in this product are listed on or

exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are

not listed on or exempt from the Inventory.

# 16.Other information, including date of preparation or last revision

**Revision Date:** 10/12/2018

Version #: 1.1

Further Information: No data available.



Revision Date: 10/12/2018

Disclaimer:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.