

Version: 1.0 Revision Date: 08/13/2015

# SAFETY DATA SHEET

## 1. Identification

Material name: TREMPRIME LV 5 GL PL Material: 022048 805

#### Recommended use and restriction on use

Recommended use: Coatings Restrictions on use: Not known.

#### Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S. Roofing 3735 Green Road Beachwood OH 44122 US

Contact person: Telephone: Emergency telephone number: EH&S Department 216-292-5000 1-800-424-9300 (US); 1-613-996-6666 (Canada)

## 2. Hazard(s) identification

Hazard	C	ass	ific	catio	on
	<b>.</b>		-1		

Physical Hazards	
Flammable liquids	Category 3
Health Hazards	
Serious Eye Damage/Eye Irritation	Category 2A
Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 1B
Unknown toxicity - Health	
Acute toxicity, oral	35.05 %
Acute toxicity, dermal	35.05 %
Acute toxicity, inhalation, vapor	100 %
Acute toxicity, inhalation, dust or mist	100 %
Environmental Hazards	
Acute hazards to the aquatic	Category 3
environment	
Unknown toxicity - Environment	
Acute hazards to the aquatic	99.95 %
environment	400.0/
Chronic hazards to the aquatic	100 %
environment	

#### Label Elements

Hazard Symbol:





Signal Word:	Danger
Hazard Statement:	Flammable liquid and vapor. Causes serious eye irritation. May cause genetic defects. May cause cancer. Harmful to aquatic life.
Precautionary Statement:	
Prevention:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If exposed or concerned: Get medical advice/attention. In case of fire: Use to extinguish.
Storage:	Store in well-ventilated place. Keep cool. Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
nazards which do not n GHS classification:	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

# 3. Composition/information on ingredients

## Mixtures

Other result

Chemical Identity	CAS number	Content in percent (%)*
Asphalt	8052-42-4	60 - 100%
Stoddard solvent (Mineral Spirits)	8052-41-3	30 - 60%

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

# 4. First-aid measures



Ingestion:	Call a POISON CENTER/doctor//if you feel unwell. Rinse mouth.	
Inhalation:	Move to fresh air.	
Skin Contact:	Wash skin thoroughly with soap and water. Get medical attention if symptoms occur. Take off immediately all contaminated clothing.	
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.	
Most important symptoms/effect	s, acute and delayed	
Symptoms:	Respiratory tract irritation.	
Indication of immediate medical a	ttention and special treatment needed	
Treatment:	Symptoms may be delayed.	
5. Fire-fighting measures		
General Fire Hazards:	Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.	
Suitable (and unsuitable) ex	xtinguishing media	
Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.	
Unsuitable extinguishing media:	Avoid water in straight hose stream; will scatter and spread fire.	
Specific hazards arising from the chemical:	Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.	
Special protective equipment an	d precautions for firefighters	
Special fire fighting procedures:	No data available.	
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.	
6. Accidental release measures		
Personal precautions, protective equipment and emergency procedures:	Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind.	
Methods and material for containment and cleaning up:	Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.	



Version: 1.0 Revision Date: 08/13/2015

Notification Procedures:	In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.
Environmental Precautions:	Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.
7. Handling and storage	
Precautions for safe handling:	Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Take precautionary measures against static discharges. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities:	Store locked up. Store in a well-ventilated place. Store in a cool place.

# 8. Exposure controls/personal protection

## **Control Parameters**

## **Occupational Exposure Limits**

Chemical Identity	type	Exposure Limit Values	Source
Asphalt - Inhalable fraction as benzene solubles	TWA	0.5 mg/m3	US. ACGIH Threshold Limit Values (2011)
Stoddard solvent (Mineral Spirits)	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	500 ppm 2,900 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)



Chemical name	type	Exposure Limit Values	Source
Asphalt - Aerosol, inhalable as benzene solubles	TWA	0.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Asphalt - Inhalable fraction as benzene solubles	TWAEV	0.5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Asphalt - Fume.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Stoddard solvent (Mineral Spirits)	STEL	580 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	290 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Stoddard solvent (Mineral Spirits)	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Stoddard solvent (Mineral Spirits)	TWA	100 ppm 525 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

#### Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

## Individual protection measures, such as personal protective equipment

General information:	Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof ventilation equipment.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing.
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.



Hygiene measures:

Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Avoid contact with eyes. When using do not smoke.

## 9. Physical and chemical properties

Appearance	
Physical state:	liquid
Form:	Viscous Liquid
Color:	Black
Odor:	Mild petroleum/solvent
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	149 - 199 °C 300 - 390 °F
Flash Point:	41 °C 105 °F(Setaflash Closed Cup)
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosi	ve limits
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	0.892
Solubility(ies)	
Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

# 10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of Hazardous Reactions:	No data available.
Conditions to Avoid:	Heat, sparks, flames.
Incompatible Materials:	Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates).



Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.	
11. Toxicological information		
Information on likely routes of ex Ingestion:	<b>posure</b> May be ingested by accident. Ingestion may cause irritation and malaise.	
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.	
Skin Contact:	May be harmful in contact with skin.	
Eye contact:	Causes serious eye irritation.	
Information on toxicological effe	ects	
Acute toxicity (list all possible	e routes of exposure)	
Oral Product:	No data available.	
Dermal Product:	ATEmix: 2,000 mg/kg	
Inhalation Product:	No data available.	
Specified substance(s): Asphalt	LC 50 (Rat): > 94.4 mg/m3	
Repeated dose toxicity Product:	No data available.	
Skin Corrosion/Irritation Product:	No data available.	
Serious Eye Damage/Eye Irritati Product:	i <b>on</b> No data available.	
Specified substance(s): Asphalt	in vivo (Rabbit, 24 hrs): Not irritating	
Stoddard solvent (Mineral Spirits)	Irritating	
Respiratory or Skin Sensitizatio Product:	n No data available.	
Carcinogenicity Product:	May cause cancer.	



IARC Monographs on the I	Evaluation of Carcinogenic Risks to Humans:
Asphalt	Overall evaluation: Possibly carcinogenic to humans
	rogram (NTP) Report on Carcinogens: ic components identified
	gulated Substances (29 CFR 1910.1001-1050): ic components identified
Germ Cell Mutagenicity	
In vitro Product:	No data available.
In vivo Product:	No data available.
Reproductive toxicity Product:	No data available.
Specific Target Organ Tox Product:	<b>icity - Single Exposure</b> No data available.
Specific Target Organ Tox Product:	icity - Repeated Exposure No data available.
Aspiration Hazard Product:	No data available.
Other effects:	No data available.
12. Ecological information	n

## Ecotoxicity:

## Acute hazards to the aquatic environment:

Fish Product:

No data available.

#### Aquatic Invertebrates Product:

No data available.

## Chronic hazards to the aquatic environment:

#### Fish



Product:	No data available.
<b>Specified substance(s):</b> Asphalt	NOAEL (Oncorhynchus mykiss, 28 d): >= 1,000 mg/l interpreted
Aquatic Invertebrates Product:	No data available.
Toxicity to Aquatic Plants Product:	No data available.
Persistence and Degradability	
Biodegradation Product:	No data available.
BOD/COD Ratio Product:	No data available.
Bioaccumulative Potential Bioconcentration Factor (BCF) Product: No data available.	
Partition Coefficient n-octan Product:	ol / water (log Kow) No data available.
<b>Specified substance(s):</b> Stoddard solvent (Mineral Spirits)	Log Kow: 3.16 - 7.15
Mobility in Soil:	No data available.
Other Adverse Effects:	Harmful to aquatic organisms.
13. Disposal considerations	
Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.
14. Transport information	
TDG	

## TDG:

Not Regulated

## CFR / DOT:



Version: 1.0 Revision Date: 08/13/2015

#### Not Regulated

#### IMDG:

UN1139, COATING SOLUTION, 3, PG III

#### **Further Information:**

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

## 15. Regulatory information

#### **US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) None present or none present in regulated quantities.

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) None present or none present in regulated quantities.

#### CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	<b>Reportable quantity</b>
Asphalt	100 lbs.
Hydrogen sulfide	100 lbs.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

## Hazard categories

Fire Hazard Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard

#### SARA 302 Extremely Hazardous Substance

	<u>Reportable</u>	
Chemical Identity	quantity	Threshold Planning Quantity
Hydrogen sulfide	100 lbs.	500 lbs.

#### SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Asphalt	100 lbs.
Hydrogen sulfide	100 lbs.

## SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Hydrogen sulfide	500lbs
Asphalt	500 lbs
Stoddard solvent (Mineral	500 lbs
Spirits)	

## SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.



All components in this product are listed on or

All components in this product are listed on or

All components in this product are listed on or

All components in this product are listed on or

All components in this product are listed on or

All components in this product are listed on or

exempt from the Inventory.

## Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Chemical Identity Hydrogen sulfide Reportable quantity 10000 lbs

## **US State Regulations**

## **US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

#### US. New Jersey Worker and Community Right-to-Know Act

<u>Chemical Identity</u> Asphalt Stoddard solvent (Mineral Spirits)

## **US. Massachusetts RTK - Substance List**

<u>Chemical Identity</u> Asphalt Stoddard solvent (Mineral Spirits) Hydrogen sulfide

#### US. Pennsylvania RTK - Hazardous Substances

<u>Chemical Identity</u> Asphalt Stoddard solvent (Mineral Spirits)

#### US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

#### Other Regulations:

Regulatory VOC (less water	313 g/l
and exempt solvent):	
VOC Method 310:	35.05 %

## Inventory Status:

Australia AICS:

Canada DSL Inventory List:

EINECS, ELINCS or NLP:

Japan (ENCS) List:

China Inv. Existing Chemical Substances:

Korea Existing Chemicals Inv. (KECI):



Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	All components in this product are listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	All components in this product are listed on or exempt from the Inventory.
Japan ISHL Listing:	All components in this product are listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

# 16.Other information, including date of preparation or last revision

Revision Date:	08/13/2015
Version #:	1.0
Further Information:	No data available.
Disclaimer:	For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.