

# SAFETY DATA SHEET

Category 1A Category 1<sup>1.</sup>

## 1. Identification

Material name: POWERPLY 2PM Material: 0362PM601

#### Recommended use and restriction on use

Recommended use: Article Restrictions on use: Not known.

#### Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S. Roofing 3735 Green Road Beachwood OH 44122 US

Contact person: Telephone: Emergency telephone number: EH&S Department 216-292-5000 1-800-424-9300 (US); 1-613-996-6666 (Canada)

#### 2. Hazard(s) identification

## Hazard Classification

#### Health Hazards

Carcinogenicity Specific Target Organ Toxicity -Repeated Exposure

Target Organs

1. Lung

#### **Unknown toxicity - Health**

Acute toxicity, oral	62.18 %
Acute toxicity, dermal	67.9 %
Acute toxicity, inhalation, vapor	100 %
Acute toxicity, inhalation, dust or mist	99.99 %

#### Label Elements

#### Hazard Symbol:





Signal Word:	Danger
Hazard Statement:	May cause cancer. Causes damage to organs through prolonged or repeated exposure.
Precautionary Statements	
Prevention:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product.
Response:	IF exposed or concerned: Get medical advice/attention.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC):	None.

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical Identity	CAS number	Content in percent (%)*
Calcium Carbonate (Limestone)	1317-65-3	20 - <50%
Asphalt	8052-42-4	20 - <50%
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	10 - <20%
Magnesite	546-93-0	5 - <10%
Fibrous Glass	65997-17-3	0.1 - <1%

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### 4. First-aid measures Description of necessary first-aid measures

Inheletien: Meus te fasch ein	

Move to fresh air.
Wash skin thoroughly with soap and water. Get medical attention if symptoms occur.
Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.
Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.



Personal Protection for First- aid Responders:	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.		
Most important symptoms/effects, acute and delayed			
Symptoms:	May cause skin and eye irritation.		
Hazards:	No data available.		
Indication of immediate medical	attention and special treatment needed		
Treatment:	Symptoms may be delayed.		
5. Fire-fighting measures			
General Fire Hazards:	No unusual fire or explosion hazards noted.		
Suitable (and unsuitable) exting	uishing media		
Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.		
Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.		
Specific hazards arising from the chemical:	During fire, gases hazardous to health may be formed.		
Special protective equipment a	nd precautions for firefighters		
Special fire fighting procedures:	No data available.		
Special protective equipment for fire-fighters:	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.		
6. Accidental release measure	es		
Personal precautions, protective equipment and emergency procedures:	No data available.		
Accidental release measures:	In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.		
Methods and material for containment and cleaning up:	Collect spillage in containers, seal securely and deliver for disposal according to local regulations.		
Environmental Precautions:	Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.		



7. Handling and storage	
Handling	
Technical measures (e.g. Local and general ventilation):	Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.
Safe handling advice:	Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required.Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust.
Contact avoidance measures:	No data available.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product.
Storage	
Safe storage conditions:	Store locked up.
Safe packaging materials:	No data available.

## 8. Exposure controls/personal protection

## **Control Parameters**

## Occupational Exposure Limits

Chemical Identity	Туре	Exposure Limit Values	Source
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Asphalt - Inhalable fume as benzene solubles	TWA	0.5 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2018)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	US. ACGIH Threshold Limit Values, as amended (2011)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.05 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended (03 2016)
	OSHA_AC T	0.025 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended (03 2016)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	PEL	0.05 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (03 2016)
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWA	2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Magnesite - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Magnesite - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as



			amended (02 2006)
Fibrous Glass - Inhalable	TWA	5 mg/m3	US. ACGIH Threshold Limit Values, as
fraction.			amended (03 2014)
Fibrous Glass - Fiber.	TWA	1 fibers/cm3	US. ACGIH Threshold Limit Values, as
			amended (03 2018)
	TWA	1 fibers/cm3	US. ACGIH Threshold Limit Values, as
			amended (03 2018)
	TWA	1 fibers/cm3	US. ACGIH Threshold Limit Values, as
			amended (03 2018)
	TWA	1 fibers/cm3	US. ACGIH Threshold Limit Values, as
			amended (03 2018)
	TWA	1 fibers/cm3	US. ACGIH Threshold Limit Values, as
			amended (03 2018)
	TWA	0.2	US. ACGIH Threshold Limit Values, as
		fibers/cm3	amended (03 2018)

Chemical name	Туре	Exposure Limit Values	Source
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Asphalt - Aerosol, inhalable as benzene solubles	TWA	0.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Asphalt - Inhalable fraction as benzene solubles	TWA	0.5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Asphalt - Fume.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Magnesite - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Fibrous Glass - Fiber.	TWA	0.2 fibers/cm3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	1 fibers/cm3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)



Fibrous Glass - Inhalable fibers.	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Fibrous Glass - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Fibrous Glass - Fiber.	TWA	2 fibres/cm3 (non- asbestos fibres) size restrictions apply	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
	TWA	1 fibres/cm3 (non- asbestos fibres) size restrictions apply	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Fibrous Glass - fibers, total dust	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
Fibrous Glass - Respirable fibers.	TWA	1 Fibers/cc	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (08 2017)
	TWA	0.5 Fibers/cc	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (08 2017)
Calcium stearate	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium stearate	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Hydrotreated Oil - Mist.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated Oil - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Hydrotreated Oil - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment), as amended (09 2017)

Appropriate Engineering Controls Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

#### Individual protection measures, such as personal protective equipment

**General information:** Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.



Eye/face protection:	Wear safety glasses with side shields (or goggles).	
Skin Protection Hand Protection:	Use suitable protective gloves if risk of skin contact.	
Other:	Wear suitable protective clothing.	
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.	
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product.	

## 9. Physical and chemical properties

Appearance	
Physical state:	solid
Form:	solid
Color:	Black
Odor:	Slight
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	No data available.
Flammability (solid, gas):	No
Upper/lower limit on flammability or explo	osive limits
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	No data available.
Relative density:	1.50
Solubility(ies)	
Solubility in water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

#### 10. Stability and reactivity

Reactivity:

No data available.



Chemical Stability:	Material is stable under normal conditions.	
Possibility of hazardous reactions:	No data available.	
Conditions to avoid:	Avoid heat or contamination.	
Incompatible Materials:	No data available.	
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.	
11. Toxicological information		
Information on likely routes of ex Inhalation:	<b>xposure</b> In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.	
Skin Contact:	May be harmful in contact with skin.	
Eye contact:	Eye contact is possible and should be avoided.	
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.	
Symptoms related to the physical, chemical and toxicological characteristics		
Inhalation:	No data available.	
Skin Contact:	No data available.	
Eye contact:	No data available.	
Ingestion:	No data available.	
Information on toxicological effe	ects	
Acute toxicity (list all possible routes of exposure)		
Oral Product:	Not classified for acute toxicity based on available data.	
Specified substance(s): Asphalt	LD 50 (Rat): > 5,000 mg/kg	
Magnesite	LD 50 (Rat): > 2,000 mg/kg	
Fibrous Glass	LD 50 (Rat): > 2,000 mg/kg	
Dermal Product:	Not classified for acute toxicity based on available data.	



Specified substance(s): Asphalt	LD 50 (Rabbit): > 2,000 mg/kg
Inhalation Product:	Not classified for acute toxicity based on available data.
Specified substance(s): Asphalt	LC 50 (Rat): > 94.4 mg/m3
Crystalline Silica (Quartz)/ Silica Sand	LC 50: > 5.0 mg/l
Repeated dose toxicity Product:	No data available.
Skin Corrosion/Irritation Product:	No data available.
Specified substance(s): Asphalt	in vivo (Rabbit): Not irritant
Magnesite	In vitro (Human, in vitro reconstituted epidermis model): Not irritant
Fibrous Glass	in vivo (Rabbit): Not irritant
Serious Eye Damage/Eye Irritation Product: No data available. Specified substance(s):	
Asphalt	Rabbit, 24 hrs: Not irritating
Magnesite	Reconstituted Corneal Epithelium model, 10 min: Not irritating
Respiratory or Skin Sensitizatio Product:	n No data available.
Carcinogenicity Product:	No data available.



## IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

	Asphalt	Overall evaluation: Possibly carcinogenic to humans.	
	Crystalline Silica (Quartz)/ Silica Sand	Overall evaluation: Carcinogenic to humans.	
	Fibrous Glass	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Possibly carcinogenic to humans. Overall evaluation: Possibly carcinogenic to humans.	
US. Nationa		<b>m (NTP) Report on Carcinogens:</b> Known To Be Human Carcinogen.	
	Fibrous Glass	Reasonably Anticipated to be a Human Carcinogen. Reasonably Anticipated to be a Human Carcinogen.	I
US. OSHA S	Specifically Regulate Crystalline Silica	ed Substances (29 CFR 1910.1001-1050):	
	(Quartz)/ Silica Sand	Cancer	
Germ Cell M	Mutagenicity		
In vitro Produ	ict:	No data available.	
In vivo Produ	ıct:	No data available.	
Reproducti Product		No data available.	
Specific Ta Product	rget Organ Toxicity · t:	- Single Exposure No data available.	
Specific Ta Produ	• • •	• Repeated Exposure No data available.	
	<b>t Organs</b> fic Target Organ Toxic	tity - Repeated Exposure: Lung	
Aspiration Product		No data available.	
Other effe	cts:	No data available.	



## 12. Ecological information

Acute hazards to the aquatic environment:

## Ecotoxicity:

Acute hazards to the aquatic environment.		
Fish Product:	No data available.	
Aquatic Invertebrates Product:	No data available.	
Chronic hazards to the aquatic	environment:	
Fish Product:	No data available.	
Specified substance(s): Asphalt	NOAEL (Oncorhynchus mykiss, 28 d): >= 1,000 mg/l Read-across from supporting substance (structural analogue or surrogate), Key study LL 50 (Oncorhynchus mykiss, 28 d): > 1,000 mg/l Read-across from supporting substance (structural analogue or surrogate), Key study	
Aquatic Invertebrates Product:	No data available.	
Toxicity to Aquatic Plants Product:	No data available.	
Persistence and Degradability		
Biodegradation Product:	No data available.	
BOD/COD Ratio Product:	No data available.	
Bioaccumulative potential Bioconcentration Factor (BC Product:	F) No data available.	
Partition Coefficient n-octanol / water (log Kow) Product: No data available.		



Mobility in soil:	No data available.
Other adverse effects:	No data available.
13. Disposal considerations	
Disposal methods:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.

## 14. Transport information

## TDG:

Not Regulated

## CFR / DOT:

Not Regulated

#### IMDG:

Not Regulated

## 15. Regulatory information

#### **US Federal Regulations**

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

## US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

None present or none present in regulated quantities.

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Chemical Identity	OSHA hazard(s)
Crystalline Silica	kidney effects
(Quartz)/ Silica Sand	lung effects
. ,	immune system effects
	Cancer

#### CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	<b>Reportable quantity</b>
Asphalt	100 lbs.



#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### **Hazard categories**

Delayed (Chronic) Health Hazard Carcinogenicity Specific target organ toxicity (single or repeated exposure)

#### SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

#### SARA 304 Emergency Release Notification

Chemical Identity	<b>Reportable quantity</b>
Asphalt	100 lbs.

## SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Calcium Carbonate	10000 lbs
(Limestone)	
Asphalt	10000 lbs
Crystalline Silica (Quartz)/	10000 lbs
Silica Sand	
Magnesite	10000 lbs
Fibrous Glass	10000 lbs

#### SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3) None present or none present in regulated quantities.

#### **US State Regulations**

#### **US. California Proposition 65**



WARNING Cancer - www.P65Warnings.ca.gov

#### US. New Jersey Worker and Community Right-to-Know Act

## Chemical Identity

Calcium Carbonate (Limestone) Asphalt Crystalline Silica (Quartz)/ Silica Sand Magnesite Fibrous Glass

#### US. Massachusetts RTK - Substance List

#### Chemical Identity

Calcium Carbonate (Limestone) Asphalt Crystalline Silica (Quartz)/ Silica Sand Magnesite



#### US. Pennsylvania RTK - Hazardous Substances

#### **Chemical Identity**

Calcium Carbonate (Limestone) Asphalt Crystalline Silica (Quartz)/ Silica Sand

## US. Rhode Island RTK

#### **Chemical Identity**

Calcium Carbonate (Limestone) Asphalt Crystalline Silica (Quartz)/ Silica Sand Magnesite

#### International regulations

#### Montreal protocol

Not applicable

#### Stockholm convention

Not applicable

#### **Rotterdam convention**

Not applicable

#### Kyoto protocol

Not applicable

#### VOC:

Regulatory VOC (less water and exempt solvent)	:	0 g/l
VOC Method 310	:	0.00 %



## Inventory Status:

Australia AICS:

Canada DSL Inventory List:

Canada NDSL Inventory:

Ontario Inventory:

China Inv. Existing Chemical Substances:

Japan (ENCS) List:

Japan ISHL Listing:

Japan Pharmacopoeia Listing:

Korea Existing Chemicals Inv. (KECI):

Mexico INSQ:

New Zealand Inventory of Chemicals:

Philippines PICCS:

Taiwan Chemical Substance Inventory:

US TSCA Inventory:

EINECS, ELINCS or NLP:

One or more components in this product are not listed on or exempt from the Inventory.

All components in this product are listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

All components in this product are listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.



## 16.Other information, including date of preparation or last revision

Revision Date:	12/12/2019
Version #:	1.0
Further Information:	No data available.
Disclaimer:	For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.