

Version 1.0 Print Date 04/15/2013

REVISION DATE: 04/12/2013

SECTION 1 - PRODUCT IDENTIFICATION

Trade name : POWERPLY 300 FR - WHITE GRANULE

Product code : 36300FR601

COMPANY : Tremco Incorporated

3735 Green Road Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST

After Hours: Chemtrec 1-800-424-9300

Product use : Roof Sheeting

SECTION 2 - HAZARDS IDENTIFICATION

Emergency Overview

Solid ply rolls. Not applicable under normal conditions of use. Generally not required under normal conditions of use.

Acute Potential Health Effects/ Routes of Entry

Inhalation : Not applicable under normal conditions of use. Eyes : Not applicable under normal conditions of use. Ingestion : Not applicable under normal conditions of use.

Skin : May cause mild irritation.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

This product contains granular materials which may cause mechanical skin, eye or respiratory irritation. Carbon black is classified by IARC to be a known animal carcinogen and a possible human carcinogen (Group 2B). The International Agency for Research on Cancer (IARC) has classified ceramic fiber, fibrous glasswool, and mineral wool (rockwool and slagwool) as possible human carcinogens (Group 2B) based on sufficient evidence of carcinogenicity in animals but insufficient data in humans. In the National Toxicology Program's (NTP) 7th Annual Report on Carcinogens (1994), respirable glasswool was classified as reasonably anticipated to be carcinogenic. Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica. OSHA considers fibrous glass dust a nuisance dust. Fibrous glass can cause dermatitis, local irritation.

Target Organs: Skin, Eye, Lung

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %	
Asphalt	8052-42-4	30.0 - 60.0	
Rhyolitic argillite/roofing granules	NJ TSRN# 51721300-5488P	15.0 - 40.0	
Fire retardant	NJ TSRN# 51721300-5035P	15.0 - 40.0	
		10.0	



Version 1.0 Print Date 04/15/2013

REVISION DATE: 04/12/2013

Crystalline Silica (Quartz)/ Silica Sand 14808-60-7 10.0 - 30.0 Styrene-butadiene copolymers NJ TSRN# 51721300-5132P 3.0 - 7.0Fibrous Glass 3.0 - 7.065997-17-3 Clay 1332-58-7 1.0 - 5.0Hydrotreated heavy naphthenic distillate 64742-52-5 0.1 - 1.0Carbon Black 1333-86-4 0.1 - 1.0

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

Inhalation : Generally not required under normal conditions of use.

Eye contact : Generally not required under normal conditions of use.

Skin contact : Clean area of contact thoroughly using soap and water. If irritation, rash or other

disorders develop, get medical attention immediately.

Ingestion : Not applicable under normal conditions of use.

Notes to physician : Not applicable.

SECTION 5 - FIRE FIGHTING MEASURES

Flash point : Not available.

Method : Not available.

Lower explosion limit : Not available.

Upper explosion limit : Not available.

Autoignition temperature : Not available.

Hazardous combustion

products

Hydrogen sulfide and hydrocarbon fractions.

Protective equipment for : Use accepted fire fighting techniques. Wear full firefighting protective

firefighters clothing, including self-contained breathing apparatus (SCBA).

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Scrape up and transfer to appropriate container for disposal.

SECTION 7 - HANDLING AND STORAGE

Store under normal warehouse conditions.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection equipment

Respiratory protection : Not required under normal conditions of use.

Hand protection : Use suitable impervious leather gloves and protective apparel to reduce

exposure.

Eye protection : Wear appropriate eye protection.

An RPM Company 2/6



Version 1.0 Print Date 04/15/2013

REVISION DATE: 04/12/2013

Skin and body protection : Not required.

Protective measures : Other equipment not normally required.

Engineering measures : General ventilation is sufficient.

Exposure Limits

Chemical Name	CAS Number	Regulation	<u>Limit</u>	<u>Form</u>
Asphalt	8052-42-4	ACGIH TWA: benzene solubles	0.5 mg/m3	Inhalable fraction.as
Fire retardant	NJ TSRN# 51721300-5035P	ACGIH TWA:	1 mg/m3	Respirable fraction.
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	OSHA TWA: OSHA TWA: OSHA PEL: OSHA PEL: ACGIH TWA:	0.1 mg/m3 0.3 mg/m3 15 mg/m3 5 mg/m3 0.025 mg/m3	Respirable. Total dust. Total dust. Respirable fraction. Respirable fraction.
Fibrous Glass	65997-17-3	ACGIH TWA:	5 mg/m3	Inhalable fraction.
Clay	1332-58-7	ACGIH TWA: OSHA PEL: OSHA PEL: OSHA TWA: OSHA TWA: OSHA PEL: OSHA PEL:	2 mg/m3 15 mg/m3 5 mg/m3 15 mg/m3 5 mg/m3 5 mg/m3 15 mg/m3	Respirable fraction. Total dust. Respirable fraction. Total dust. Respirable fraction. Respirable fraction. Total dust.
Hydrotreated heavy naphthenic distillate	64742-52-5	OSHA PEL: OSHA PEL: ACGIH TWA:	2,000 mg/m3 5 mg/m3 5 mg/m3	Mist. Inhalable fraction.
Carbon Black	1333-86-4	ACGIH TWA: OSHA PEL: OSHA TWA: OSHA TWA:	3.5 mg/m3 3.5 mg/m3 15 mg/m3 5 mg/m3	Total dust. Respirable fraction.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form : Solid ply rolls

Odor : None

pH : Not available.

Vapour pressure : Not available.

Vapor density : Not available.

Melting point/range : Not available.

Freezing point : Not available.

Boiling point/range : Not available.

Water solubility : Not available.

An RPM Company 3/6



Version 1.0 Print Date 04/15/2013

REVISION DATE: 04/12/2013

Specific Gravity : 1.3 % Volatile Weight : 0 %

SECTION 10 - REACTIVITY / STABILITY

Stability : Material is stable under normal storage, handling, and use.

Hazardous polymerization : Will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

Aluminum hydroxide, CAS-No.: 21645-51-2

Acute oral toxicity (LD-50 oral) 5,000 mg/kg (Rat)

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method : As purchased, this product, when discarded, is not a listed or characteristic hazardous

waste according to Federal regulations (40 CFR 261). Check local, regional, state or provincial regulations for applicable requirements for disposal. Any processing, using, alteration or chemical additions to the product, as purchased, may alter the disposal requirements. Under Federal regulations, it is the generator's responsibility to determine if a waste is a hazardous waste. Empty containers may retain product

residue. Do not reuse.

SECTION 14 - TRANSPORTATION / SHIPPING DATA

CFR / DOT:

Not Regulated

TDG:

Not Regulated

IMDG:

Not Regulated

SECTION 15 - REGULATORY INFORMATION

North American Inventories:

An RPM Company 4/6



Version 1.0 Print Date 04/15/2013

REVISION DATE: 04/12/2013

One or more components are not listed on the TSCA inventory.

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

SARA 313 Components None present or none present in regulated quantities.

SARA 311/312 Hazards Acute Health Hazard

Chronic Health Hazard

OSHA Hazardous Components:

Asphalt 8052-42-4

Fire retardant NJ TSRN# 51721300-5035P

Crystalline Silica (Quartz)/ Silica Sand 14808-60-7 Fibrous Glass 65997-17-3 Clav 1332-58-7 Hydrotreated heavy naphthenic distillate 64742-52-5 Carbon Black 1333-86-4

OSHA Status: Considered : Irritant hazardous based on the Carcinogen

following criteria:

OSHA Flammability : Not Regulated

Regulatory VOC (less water and : 0 g/l

exempt solvent)

VOC Method 310 : 0%

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen: Crystalline Silica (Quartz)/ Silica Sand 14808-60-7 Hydrotreated heavy naphthenic distillate 64742-52-5 Carbon Black 1333-86-4

U.S. State Regulations:

MASS RTK Components Asphalt 8052-42-4

> Crystalline Silica (Quartz)/ Silica Sand 14808-60-7 Fibrous Glass 65997-17-3 Clay 1332-58-7 Formaldehyde 50-00-0

Penn RTK Components Asphalt 8052-42-4

> Rhyolitic argillite/roofing granules NJ TSRN# 51721300-5488P Fire retardant NJ TSRN# 51721300-5035P

Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

Styrene-butadiene copolymers NJ TSRN# 51721300-5132P

Fibrous Glass 65997-17-3 Clay 1332-58-7

NJ RTK Components Asphalt 8052-42-4

> Rhyolitic argillite/roofing granules NJ TSRN# 51721300-5488P Fire retardant

NJ TSRN# 51721300-5035P

Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

Styrene-butadiene copolymers NJ TSRN# 51721300-5132P

Fibrous Glass 65997-17-3



Version 1.0 Print Date 04/15/2013

REVISION DATE: 04/12/2013

Clay 1332-58-7 Hydrotreated heavy naphthenic distillate 64742-52-5 Carbon Black 1333-86-4

Components under California Proposition 65:

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

SECTION 16 - OTHER INFORMATION

HMIS Rating:

Health	1	0 = Minimum
Flammability	0	1 = Slight
Reactivity	0	2 = Moderate
PPE		3 = Serious
		4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

ACGIH - American Conference of Governmental Hygienists

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

DOT - Department of Transportation

DSL - Domestic Substance List

EPA - Environmental Protection Agency

HMIS - Hazardous Materials Information System

IARC - International Agency for Research on Cancer

MSHA - Mine Safety Health Administration

NDSL - Non-Domestic Substance List

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act

RTK - Right To Know

SARA - Superfund Amendments and Reauthorization Act

STEL - Short Term Exposure Limit

TLV - Threshold Limit Value

TSCA - Toxic Substances Control Act

TWA - Time Weighted Average

V - Volume

VOC - Volatile Organic Compound

WHMIS - Workplace Hazardous Materials Information

System