

SAFETY DATA SHEET

1. Identification

Material name: POWERPLY ENDURE 320 SMOOTH Material: 036E320SM601

Recommended use and restriction on use

Recommended use: Article Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S. Roofing 3735 Green Road Beachwood OH 44122 US

Contact person: Telephone: Emergency telephone number: EH&S Department 216-292-5000 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Acute toxicity (Inhalation - dust and mist)	Category 4
Carcinogenicity	Category 1A
Specific Target Organ Toxicity - Repeated Exposure	Category 1 ^{1.}

Target Organs

1. Lung

Unknown toxicity - Health

Acute toxicity, oral	20.65 %
Acute toxicity, dermal	53.24 %
Acute toxicity, inhalation, vapor	100 %
Acute toxicity, inhalation, dust or mist	77.53 %

Label Elements

Hazard Symbol:





Signal Word:	Danger
Hazard Statement:	Harmful if inhaled. May cause cancer. Causes damage to organs through prolonged or repeated exposure.
Precautionary Statements	
Prevention:	Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product.
Response:	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC):	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Asphalt	8052-42-4	20 - <50%
Aluminum hydroxide	21645-51-2	20 - <50%
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	10 - <20%
Fibrous Glass	65997-17-3	10 - <20%
Calcium carbonate	471-34-1	0.1 - <1%

All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
Inhalation:	Move to fresh air.
Skin Contact:	Wash skin thoroughly with soap and water. Get medical attention if symptoms occur.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.
	2/17



Most important symptoms/effects, acute and delayed		
Symptoms:	May cause skin and eye irritation.	
Indication of immediate medical a	ttention and special treatment needed	
Treatment:	Symptoms may be delayed.	
5. Fire-fighting measures		
General Fire Hazards:	No unusual fire or explosion hazards noted.	
Suitable (and unsuitable) exting	lishing media	
Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.	
Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.	
Specific hazards arising from the chemical:	During fire, gases hazardous to health may be formed.	
Special protective equipment an	d precautions for firefighters	
Special fire fighting procedures:	No data available.	
Special protective equipment for fire-fighters:	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.	
6. Accidental release measure	S	
Personal precautions, protective equipment and emergency procedures:	No data available.	
Methods and material for containment and cleaning up:	Collect spillage in containers, seal securely and deliver for disposal according to local regulations.	
Notification Procedures:	In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.	
Environmental Precautions:	Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.	



7. Handling and storage

Precautions for safe handling:	Wash hands thoroughly after handling. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust.
Conditions for safe storage, including any incompatibilities:	Store locked up.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity Type Exposure Limit Values		Source	
Asphalt - Inhalable fume as benzene solubles	TWA	0.5 mg/m3	US. ACGIH Threshold Limit Values (03 2018)
Aluminum hydroxide - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
·	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Aluminum hydroxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Aluminum hydroxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	US. ACGIH Threshold Limit Values (2011)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.05 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (03 2016)
	OSHA_AC T	0.025 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (03 2016)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	PEL	0.05 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (03 2016)
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWA	2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Fibrous Glass - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Fibrous Glass - Fiber.	TWA	1 fibers/cm3	US. ACGIH Threshold Limit Values (03 2018)
	TWA	1 fibers/cm3	US. ACGIH Threshold Limit Values (03 2018)
	TWA	1 fibers/cm3	US. ACGIH Threshold Limit Values (03 2018)
	TWA	1 fibers/cm3	US. ACGIH Threshold Limit Values (03 2018)
	TWA	1 fibers/cm3	US. ACGIH Threshold Limit Values (03 2018)
	TWA	0.2 fibers/cm3	US. ACGIH Threshold Limit Values (03 2018)
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)



Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Chemical name	Туре	Exposure Limit Values	Source
Asphalt - Aerosol, inhalable as benzene solubles	TWA	0.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Asphalt - Inhalable fraction as benzene solubles	TWA	0.5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Asphalt - Fume.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Aluminum hydroxide - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Aluminum hydroxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Aluminum hydroxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Aluminum hydroxide - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Aluminum hydroxide - Inhalable fraction.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Aluminum hydroxide - Respirable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Aluminum hydroxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Fibrous Glass - Fiber.	TWA	0.2 fibers/cm3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	1 fibers/cm3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)



Fibrous Glass - Inhalable fibers.	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupation Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Fibrous Glass - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure Biological or Chemical Agents) (06 2015)
Fibrous Glass - Fiber.	TWA	2 fibres/cm3 (non- asbestos fibres) size restrictions apply	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	1 fibres/cm3 (non- asbestos fibres) size restrictions apply	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Fibrous Glass - fibers, total dust	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Fibrous Glass - Respirable fibers.	TWA	1 Fibers/cc	Canada. Ontario OELs. (Control of Exposure Biological or Chemical Agents) (08 2017)
	TWA	0.5 Fibers/cc	Canada. Ontario OELs. (Control of Exposure Biological or Chemical Agents) (08 2017)
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupationa Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupationa Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupationa Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium stearate	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupationa Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium stearate	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure t Biological or Chemical Agents) (11 2010)
Hydrotreated Oil - Mist.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupationa Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated Oil - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure t Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure t Biological or Chemical Agents) (06 2015)
Hydrotreated Oil - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)



Talc - Respirable.	TWA		2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Talc - Respirable dust.	TWA		3 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Talc	TWA		2 Fibers/cc	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (08 2017)
Talc - Respirable fraction.	TWA		2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (08 2017)
Butylated hydroxytoluene - Vapor and aerosol, inhalable.	TWA		2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Butylated hydroxytoluene - Inhalable fraction and vapor.	TWA		2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Butylated hydroxytoluene	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Vinyl acetate	TWA	10 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	15 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Vinyl acetate	TWA	10 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	15 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Vinyl acetate	STEL	15 ppm	53 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	10 ppm	35 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection Hand Protection: Other:	Use suitable protective gloves if risk of skin contact. Wear suitable protective clothing.
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from
	local supervisor.



Hygiene measures:

Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product.

9. Physical and chemical properties

Appearance

Physical state:	solid		
Form:	solid		
Color:	Black		
Odor:	Slight		
Odor threshold:	No data available.		
pH:	No data available.		
Melting point/freezing point:	No data available.		
Initial boiling point and boiling range:	No data available.		
Flash Point:	No data available.		
Evaporation rate:	No data available.		
Flammability (solid, gas):	No		
Upper/lower limit on flammability or explosive limits			
Flammability limit - upper (%):	No data available.		
Flammability limit - lower (%):	No data available.		
Explosive limit - upper (%):	No data available.		
Explosive limit - lower (%):	No data available.		
Vapor pressure:	No data available.		
Vapor density:	No data available.		
Relative density:	1.5		
Solubility(ies)			
Solubility in water:	Insoluble in water		
Solubility (other):	No data available.		
Partition coefficient (n-octanol/water):	No data available.		
Auto-ignition temperature:	No data available.		
Decomposition temperature:	No data available.		
Viscosity:	No data available.		

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	No data available.



Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.		
11. Toxicological information			
Information on likely routes of ex Inhalation:	xposure In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.		
Skin Contact:	May be harmful in contact with skin.		
Eye contact:	Eye contact is possible and should be avoided.		
Ingestion:	May be harmful if swallowed.		
Symptoms related to the physical, chemical and toxicological characteristics			
Inhalation:	No data available.		
Skin Contact:	No data available.		
Eye contact:	No data available.		
Ingestion:	No data available.		
Information on toxicological effe	cts		
Acute toxicity (list all possible	routes of exposure)		
Oral Product:	Not classified for acute toxicity based on available data.		
Specified substance(s): Asphalt	LD 50 (Rat): > 5,000 mg/kg		
Aluminum hydroxide	LD 50 (Rat): > 2,000 mg/kg		
Fibrous Glass	LD 50 (Rat): > 2,000 mg/kg		
Calcium carbonate	LD 50 (Rat): > 2,000 mg/kg		
Dermal Product:	Not classified for acute toxicity based on available data.		
Specified substance(s): Asphalt	LD 50 (Rabbit): > 2,000 mg/kg		
Calcium carbonate	LD 50 (Rat): > 2,000 mg/kg		



Inhalation Product:	ATEmix: 1.9 mg/l	
Repeated dose toxicity Product:	No data available.	
Skin Corrosion/Irritation Product:	No data available.	
Specified substance(s): Asphalt	in vivo (Rabbit): Not irritant Experimental result, Key study	
Aluminum hydroxide	in vivo (Rabbit): Not classified as an Irritant Experimental result, Key study	
Fibrous Glass	in vivo (Rabbit): Not irritant Experimental result, Key study	
Calcium carbonate	in vivo (Rabbit): Not irritant Experimental result, Key study	
Serious Eye Damage/Eye Irritation Product: No data available.		

Specified substance(s):	no data avaliable.
Asphalt	Rabbit, 24 hrs: Not irritating
Aluminum hydroxide	Rabbit, 24 hrs: Not irritating
Calcium carbonate	Rabbit, 24 - 72 hrs: Not irritating

Respiratory or Skin Sensitization Product: No

Product: No data available.

Carcinogenicity Product:

No data available.



IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

	Asphalt		Overall evaluation: Possibly carcinogenic to humans.	
	Crystalline Sil (Quartz)/ Silic Sand		Overall evaluation: Carcinogenic to humans.	
	Fibrous Glass	;	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Possibly carcinogenic to humans. Overall evaluation: Possic carcinogenic to humans.	
US. Nationa	I Toxicology I Crystalline (Quartz)/ Sand		n (NTP) Report on Carcinogens: Known To Be Human Carcinogen.	
	Fibrous Glass	5	Reasonably Anticipated to be a Human Carcinogen. Reasonably Anticito be a Human Carcinogen.	pated
US. OSHA S			l Substances (29 CFR 1910.1001-1050):	
	Crystalline Sil (Quartz)/ Silic Sand		Cancer	
Germ Cell M	lutagenicity			
In vitro Produ	ct:		No data available.	
In vivo Produ	ct:		No data available.	
Reproductiv Product			No data available.	
Specific Tar Product		xicity - S	Single Exposure No data available.	
Specific Tar Produ		xicity - ∣	Repeated Exposure No data available.	
	t Organs ic Target Organ	n Toxicit	y - Repeated Exposure: Lung	
Aspiration H Product			No data available.	
Other effec	ets:		No data available.	11/17



12. Ecological information

Ecotoxicity:		
Acute hazards to the aquatic e	environment:	
Fish Product:	No data available.	
Aquatic Invertebrates Product:	No data available.	
Chronic hazards to the aquati	c environment:	
Fish Product:	No data available.	
Specified substance(s): Asphalt	NOAEL (Oncorhynchus mykiss, 28 d): >= 1,000 mg/l Read-across from supporting substance (structural analogue or surrogate), Key study LL 50 (Oncorhynchus mykiss, 28 d): > 1,000 mg/l Read-across from supporting substance (structural analogue or surrogate), Key study	
Aquatic Invertebrates Product:	No data available.	
Toxicity to Aquatic Plants Product:	No data available.	
Persistence and Degradability		
Biodegradation Product:	No data available.	
BOD/COD Ratio Product:	No data available.	
Bioaccumulative potential Bioconcentration Factor (BCF) Product: No data available.		
Partition Coefficient n-octanol / water (log Kow) Product: No data available.		



Mobility in soil:	No data available.	
Other adverse effects:	No data available.	
13. Disposal considerations		
Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.	
Contaminated Packaging:	No data available.	
14. Transport information		
TRC		

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Chemical Identity	<u>OSHA hazard(s)</u>
Crystalline Silica	kidney effects
(Quartz)/ Silica Sand	lung effects
	immune system effects
	Cancer

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Asphalt	100 lbs.
Vinyl acetate	5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate (Acute) Health Hazards



Delayed (Chronic) Health Hazard Acute toxicity (any route or exposure) Carcinogenicity Specific target organ toxicity (single or repeated exposure)

SARA 302 Extremely Hazardous Substance

	<u>Reportable</u>	
Chemical Identity	quantity	Threshold Planning Quantity
Vinyl acetate	5000 lbs.	1000 lbs.

SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Asphalt	100 lbs.
Vinyl acetate	5000 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Vinyl acetate	500lbs
Asphalt	10000 lbs
Aluminum hydroxide	10000 lbs
Crystalline Silica (Quartz)/	10000 lbs
Silica Sand	
Fibrous Glass	10000 lbs
Calcium carbonate	10000 lbs

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Chemical Identity	Reportable quantity
Vinyl acetate	lbs

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3) None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65



WARNING Cancer - www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act

<u>Chemical Identity</u> Asphalt Crystalline Silica (Quartz)/ Silica Sand Fibrous Glass



US. Massachusetts RTK - Substance List

<u>Chemical Identity</u> Asphalt Crystalline Silica (Quartz)/ Silica Sand Fibrous Glass Vinyl acetate

US. Pennsylvania RTK - Hazardous Substances

<u>Chemical Identity</u> Asphalt Crystalline Silica (Quartz)/ Silica Sand Fibrous Glass

US. Rhode Island RTK

Chemical Identity

Asphalt Aluminum hydroxide Crystalline Silica (Quartz)/ Silica Sand Fibrous Glass

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

VOC:

Regulatory VOC (less water and exempt solvent)	:	0 g/l
VOC Method 310	:	0.00 %



Inventory Status: Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	One or more components in this product are not listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Mexico INSQ:	One or more components in this product are not listed on or exempt from the Inventory.
Ontario Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Taiwan Chemical Substance Inventory:	One or more components in this product are not listed on or exempt from the Inventory.



16.Other information, including date of preparation or last revision

Revision Date:	02/04/2019
Version #:	1.0
Further Information:	No data available.
Disclaimer:	For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.