

Revision Date: 09/28/2015

# SAFETY DATA SHEET

#### 1. Identification

Material name: OB PRIMER/SPLICE WASH LV 1 GL

Material: 068330 801

Recommended use and restriction on use

Recommended use: Coatings Restrictions on use: Not known.

#### Manufacturer/Importer/Supplier/Distributor Information

Tremco Incorporated 3735 Green Road BEACHWOOD OH 44122 US

Contact person:EH&S DepartmentTelephone:216-292-5000

**Emergency telephone number:** 1-800-424-9300 (US); 1-613-996-6666 (Canada)

## 2. Hazard(s) identification

## **Hazard Classification**

## **Physical Hazards**

Flammable liquids Category 2

### **Health Hazards**

Acute toxicity (Oral)

Skin Corrosion/Irritation

Category 2

Germ Cell Mutagenicity

Category 1B

Carcinogenicity

Category 1B

Toxic to reproduction

Category 2

Aspiration Hazard

Category 1

# Unknown toxicity - Health

Acute toxicity, oral 0 %
Acute toxicity, dermal 74.74 %
Acute toxicity, inhalation, vapor 88.83 %
Acute toxicity, inhalation, dust or mist 100 %

# **Environmental Hazards**

Acute hazards to the aquatic Category 3 environment

# Unknown toxicity - Environment

Acute hazards to the aquatic 82.18 % environment

Chronic hazards to the aquatic 100 %

environment

## **Label Elements**

#### **Hazard Symbol:**



Revision Date: 09/28/2015



Signal Word: Danger

**Hazard Statement:** Highly flammable liquid and vapor.

> Harmful if swallowed. Causes skin irritation. May cause genetic defects.

May cause cancer.

Suspected of damaging fertility or the unborn child. May be fatal if swallowed and enters airways.

Harmful to aquatic life.

**Precautionary** Statement: Prevention:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond

container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take

precautionary measures against static discharge. Wear protective

gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as

required.

Response: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower. If skin irritation occurs: Get medical advice/attention.

Rinse mouth. IF SWALLOWED: Immediately call a POISON

CENTER/doctor. Do NOT induce vomiting. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Take off

contaminated clothing. In case of fire: Use ... to extinguish.

Storage: Store in well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Other hazards which do not result in GHS classification: Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and

vapor. May cause flash fire or explosion.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical Identity	CAS number	Content in percent (%)*
P-chlorobenzotrifluoride	98-56-6	60 - 100%



Revision Date: 09/28/2015

Toluene	108-88-3	10 - 30%
Xylene	1330-20-7	3 - 7%
Aliphatic Naphtha (Light aliphatic naphtha)	64742-89-8	3 - 7%
Hexane	110-54-3	1 - 5%
Ethylbenzene	100-41-4	1 - 5%

<sup>\*</sup> All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

# 4. First-aid measures

**Ingestion:** Rinse mouth. Call a physician or poison control center immediately. Never

give liquid to an unconscious person. If vomiting occurs, keep head low so

that stomach content doesn't get into the lungs.

**Inhalation:** Move to fresh air.

Skin Contact: Take off immediately all contaminated clothing. Immediately flush with

plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Get medical

attention.

**Eye contact:** Immediately flush with plenty of water for at least 15 minutes. If easy to do,

remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

**Symptoms:** Respiratory tract irritation. Prolonged or repeated contact with skin may

cause redness, itching, irritation and eczema/chapping.

Indication of immediate medical attention and special treatment needed

**Treatment:** Symptoms may be delayed.

# 5. Fire-fighting measures

**General Fire Hazards:** Use water spray to keep fire-exposed containers cool. Water may be

ineffective in fighting the fire. Fight fire from a protected location. Move

containers from fire area if you can do so without risk.

#### Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from

the chemical:

Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of

vapors or gases to explosive concentrations.

Special protective equipment and precautions for firefighters



Revision Date: 09/28/2015

Special fire fighting procedures:

No data available.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning up:

Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

**Notification Procedures:** 

In the event of a spill or accidental release, notify relevant authorities in

accordance with all applicable regulations.

**Environmental Precautions:** 

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

#### 7. Handling and storage

Precautions for safe handling:

Do not taste or swallow. Wash hands thoroughly after handling. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Avoid contact with skin. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage,

including any incompatibilities:

Store locked up. Store in a well-ventilated place. Store in a cool place.

## 8. Exposure controls/personal protection

#### **Control Parameters**

**Occupational Exposure Limits** 

Chemical Identity	type	Exposure Limit Values	Source
Toluene	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	TWA	200 ppm	US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	Ceiling	300 ppm	US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	MAX. CONC	500 ppm	US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)



Revision Date: 09/28/2015

Xylene	TWA	100 ppm		US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hexane	TWA	50 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	500 ppm	1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethylbenzene	TWA	20 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	type	Exposure Limit Values		Source
Toluene	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Toluene	TWAEV	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
mg/m3 Labor - Regu Quality of the				Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm	651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)



Revision Date: 09/28/2015

Hexane	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)	
Hexane	TWAEV	50 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)	
Hexane	TWA	50 ppm	176 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)	
Ethylbenzene	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)	
Ethylbenzene	STEL	125 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)	
	TWAEV	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)	
Ethylbenzene	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)	
	STEL	125 ppm	543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)	



Revision Date: 09/28/2015

**Biological Limit Values** 

Chemical Identity	Exposure Limit Values	Source
Toluene (o-Cresol, with hydrolysis: Sampling time: End of shift.)	0.3 mg/g (Creatinine in urine)	ACGIH BEL (03 2013)
Toluene (toluene: Sampling time: Prior to last shift of work week.)	0.02 mg/l (Blood)	ACGIH BEL (03 2013)
Toluene (toluene: Sampling time: End of shift.)	0.03 mg/l (Urine)	ACGIH BEL (03 2013)
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Hexane (2,5- Hexanedion, without hydrolysis: Sampling time: End of shift at end of work week.)	0.4 mg/l (Urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

# Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

# Individual protection measures, such as personal protective equipment

**General information:** Use explosion-proof ventilation equipment. Good general ventilation

(typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide easy

access to water supply and eye wash facilities.

**Eye/face protection:** Wear safety glasses with side shields (or goggles).

**Skin Protection** 

**Hand Protection:** Use suitable protective gloves if risk of skin contact.

Other: Wear chemical-resistant gloves, footwear, and protective clothing

appropriate for the risk of exposure. Contact health and safety professional

or manufacturer for specific information.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.



Revision Date: 09/28/2015

**Hygiene measures:** Do not eat, drink or smoke when using the product. Wash hands after

handling. Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. When using do not smoke. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wash contaminated

clothing before reuse. Avoid contact with skin.

## 9. Physical and chemical properties

**Appearance** 

Physical state:liquidForm:liquidColor:Amber

Odor: Mild petroleum/solvent
Odor threshold: No data available.

pH: No data available.

Melting point/freezing point: No data available.

Initial boiling point and boiling range: 65 - 71 °C 149 - 159 °F

Flash Point: -18 °C 0 °F(Setaflash Closed Cup)

**Evaporation rate:** Slower than Ether

Flammability (solid, gas):

No
Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%): 10.50 %(V)
Flammability limit - lower (%): 1.00 %(V)

Explosive limit - upper (%):

No data available.

Explosive limit - lower (%):

No data available.

Vapor pressure: 227 mmHg

Vapor density: Vapors are heavier than air and may travel along the floor and

in the bottom of containers.

Relative density: 1.169 (25 °C 77 °F)

Solubility(ies)

Solubility in water:
Solubility (other):
No data available.
Partition coefficient (n-octanol/water):
No data available.
Auto-ignition temperature:
No data available.
Decomposition temperature:
No data available.

**Viscosity:** < 20.5 mm2/s (40 °C 104 °F)

#### 10. Stability and reactivity

Reactivity: No data available.

**Chemical Stability:** Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.

Conditions to avoid: Heat, sparks, flames.



Revision Date: 09/28/2015

Incompatible Materials: Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides

and chromates). Strong bases.

**Hazardous Decomposition** 

**Products:** 

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.

# 11. Toxicological information

Information on likely routes of exposure

**Ingestion:** Harmful if swallowed.

**Inhalation:** In high concentrations, vapors, fumes or mists may irritate nose, throat and

mucus membranes.

**Skin Contact:** Causes skin irritation.

**Eye contact:** Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

**Product:** ATEmix: 1,202.52 mg/kg

**Dermal** 

**Product:** ATEmix: 13,866.42 mg/kg

Inhalation

**Product:** No data available.

Repeated dose toxicity

**Product:** No data available.

Skin Corrosion/Irritation

**Product:** No data available.

Serious Eye Damage/Eye Irritation

**Product:** No data available.

Specified substance(s):

Toluene in vivo (Rabbit, 24 - 72 hrs): Not irritating

Xylene in vivo (Rabbit, 24 hrs): Moderately irritating

Aliphatic Naphtha (Light

aliphatic naphtha)

in vivo (Rabbit, 24 - 72 hrs): Not irritating

Hexane in vivo (Rabbit, 24 - 72 hrs): Not irritating

Ethylbenzene Irritating



Revision Date: 09/28/2015

Respiratory or Skin Sensitization

**Product:** No data available.

Carcinogenicity

**Product:** May cause cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Ethylbenzene Overall evaluation: Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

**Germ Cell Mutagenicity** 

In vitro

**Product:** No data available.

In vivo

**Product:** No data available.

Reproductive toxicity

**Product:** Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure
Product:
No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

**Aspiration Hazard** 

**Product:** May be fatal if swallowed and enters airways.

Other effects: No data available.

# 12. Ecological information

## **Ecotoxicity:**

#### Acute hazards to the aquatic environment:

**Fish** 

**Product:** No data available.

Specified substance(s):

Toluene LC 50 (Fathead minnow (Pimephales promelas), 96 h): 71.7 - 82.8 mg/l

Mortality



Revision Date: 09/28/2015

Xylene LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality

Hexane LC 50 (Fathead minnow (Pimephales promelas), 96 h): 2.101 - 2.981 mg/l

Mortality

Ethylbenzene LC 50 (Bluegill (Lepomis macrochirus), 24 h): 70 - 149 mg/l Mortality

LC 50 (Bluegill (Lepomis macrochirus), 24 h): 112 - 170 mg/l Mortality LC 50 (Bluegill (Lepomis macrochirus), 24 h): 113 - 162 mg/l Mortality LC 50 (Bluegill (Lepomis macrochirus), 24 h): 66 - 276 mg/l Mortality

LC 50 (Rainbow trout, donaldson trout (Oncorhynchus mykiss), 24 h): 11 - 18

mg/I Mortality

**Aquatic Invertebrates** 

**Product:** No data available.

Specified substance(s):

Toluene LC 50 (Water flea (Daphnia magna), 24 h): 240 - 420 mg/l Mortality

EC 50 (Water flea (Daphnia magna), 48 h): < 9.83 mg/l Intoxication

Xylene LC 50 (Water flea (Daphnia magna), 24 h): > 100 - 1,000 mg/l Mortality

Hexane LC 50 (Water flea (Daphnia magna), 24 h): > 50 mg/l Mortality

Ethylbenzene EC 50 (Water flea (Daphnia magna), 24 h): 1.47 - 2.18 mg/l Intoxication

EC 50 (Water flea (Daphnia magna), 24 h): 1.51 - 2.14 mg/l Intoxication EC 50 (Water flea (Daphnia magna), 24 h): 1.63 - 2.28 mg/l Intoxication

EC 50 (Water flea (Daphnia magna), 24 h): 2.2 mg/l Intoxication

EC 50 (Water flea (Daphnia magna), 24 h): 1.53 - 3.17 mg/l Intoxication

#### Chronic hazards to the aquatic environment:

Fish

**Product:** No data available.

Specified substance(s):

Toluene NOAEL (Pimephales promelas, 32 d): 4 mg/l experimental result

Xylene NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l experimental result

Aliphatic Naphtha (Light

aliphatic naphtha)

NOAEL (Daphnia magna, 21 d): 2.6 mg/l read across

Hexane NOAEL (Oncorhynchus mykiss, 28 d): 2.8 mg/l QSAR

**Aquatic Invertebrates** 

**Product:** No data available.

**Toxicity to Aquatic Plants** 

**Product:** No data available.

# Persistence and Degradability

Biodegradation

**Product:** No data available.



Revision Date: 09/28/2015

**BOD/COD Ratio** 

**Product:** No data available.

**Bioaccumulative Potential** 

**Bioconcentration Factor (BCF)** 

**Product:** No data available.

Specified substance(s):

Toluene Green algae (Selenastrum capricornutum), Bioconcentration Factor (BCF):

3,016 (Static)

Partition Coefficient n-octanol / water (log Kow)

**Product:** No data available.

Specified substance(s):

Toluene Log Kow: 2.73

Xylene Log Kow: 3.12 - 3.20

Hexane Log Kow: 3.90

Ethylbenzene Log Kow: 3.15

Mobility in Soil: No data available.

Other Adverse Effects: Harmful to aquatic organisms.

13. Disposal considerations

**Disposal instructions:** Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

UN1133, ADHESIVES, 3, PG II

CFR / DOT:

UN1133, Adhesives, 3, PG II

IMDG:

UN1133, ADHESIVES, 3, PG II

**Further Information:** 

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.



Revision Date: 09/28/2015

## 15. Regulatory information

#### **US Federal Regulations**

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Chemical Identity Reportable quantity

P-chlorobenzotrifluoride De minimis concentration: 1.0% One-Time Export Notification only.

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

#### CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity		
Toluene	1000 lbs.		
Xylene	100 lbs.		
Hexane	5000 lbs.		
Ethylbenzene	1000 lbs.		

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

### **Hazard categories**

Fire Hazard

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard

## **SARA 302 Extremely Hazardous Substance**

None present or none present in regulated quantities.

#### SARA 304 Emergency Release Notification

DAILA GOT EINCIGCIOS INCICAGO NOTIFICATION				
Chemical Identity	Reportable quantity			
Toluene	1000 lbs.			
Xylene	100 lbs.			
Hexane	5000 lbs.			
Ethylbenzene	1000 lbs.			

## SARA 311/312 Hazardous Chemical

<b>Chemical Identity</b>	<b>Threshold Planning Quantity</b>
P-chlorobenzotrifluoride	500 lbs
Toluene	500 lbs
Xylene	500 lbs
Aliphatic Naphtha (Light aliphatic naphtha)	500 lbs
Harraga	500 lb -

Hexane 500 lbs Ethylbenzene 500 lbs

# SARA 313 (TRI Reporting)

## **Chemical Identity**

Toluene Xylene Hexane Ethylbenzene

## Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.



Revision Date: 09/28/2015

### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

#### **US State Regulations**

# **US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

## US. New Jersey Worker and Community Right-to-Know Act

#### **Chemical Identity**

P-chlorobenzotrifluoride

Toluene

Xylene

Hexane

Ethylbenzene

#### **US. Massachusetts RTK - Substance List**

## **Chemical Identity**

Toluene

Xylene

Hexane

Ethylbenzene

## US. Pennsylvania RTK - Hazardous Substances

## **Chemical Identity**

Toluene

Xylene

Hexane

Ethylbenzene

### **US. Rhode Island RTK**

## **Chemical Identity**

Toluene

Xylene

Hexane

Ethylbenzene

#### Other Regulations:

Regulatory VOC (less water

250 g/l

and exempt solvent):

VOC Method 310:

4.60 %

# **Inventory Status:**

Australia AICS: One or more components in this product are

not listed on or exempt from the inventory.

Canada DSL Inventory List: All components in this product are listed on or

exempt from the Inventory.

EINECS, ELINCS or NLP: One or more components in this product are

not listed on or exempt from the Inventory.



Revision Date: 09/28/2015

Japan (ENCS) List:

One or more components in this product are

not listed on or exempt from the Inventory.

China Inv. Existing Chemical Substances: One or more components in this product are

not listed on or exempt from the Inventory.

Korea Existing Chemicals Inv. (KECI): One or more components in this product are

not listed on or exempt from the Inventory.

Canada NDSL Inventory: One or more components in this product are

not listed on or exempt from the Inventory.

Philippines PICCS: One or more components in this product are

not listed on or exempt from the Inventory.

US TSCA Inventory: All components in this product are listed on or

exempt from the Inventory.

New Zealand Inventory of Chemicals:

One or more components in this product are

not listed on or exempt from the Inventory.

Japan ISHL Listing: One or more components in this product are

not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing: One or more components in this product are

not listed on or exempt from the Inventory.

## 16.Other information, including date of preparation or last revision

**Revision Date:** 09/28/2015

Version #: 1.0

Further Information: No data available.

**Disclaimer:** For Industrial Use Only. Keep out of Reach of Children. The hazard

information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including

the safe use of the product under every foreseeable condition.