

SAFETY DATA SHEET

1. Identification

Material name: Solargard® 6083 Base Coat Material: 1121700053D

Recommended use and restriction on use

Recommended use: Coatings Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S. Roofing 3735 Green Road Beachwood OH 44122 US

Contact person: Telephone: Emergency telephone number: EH&S Department 216-292-5000 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Acute toxicity (Inhalation - dust and mist)	Category 4
Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 1A
Toxic to reproduction	Category 1B

Unknown toxicity - Health

Acute toxicity, oral	33.21 %
Acute toxicity, dermal	36.73 %
Acute toxicity, inhalation, vapor	100 %
Acute toxicity, inhalation, dust or mist	63.9 %

Environmental Hazards

Acute hazards to the aquatic Category 3 environment

Unknown toxicity - Environment

Acute hazards to the aquatic environment	60.18 %
Chronic hazards to the aquatic environment	100 %



Label Elements

Hazard Symbol:

Signal Word:	Danger
Hazard Statement:	Harmful if inhaled. May cause genetic defects. May cause cancer. May damage fertility or the unborn child. Harmful to aquatic life.
Precautionary Statements	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
Storage:	Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC):	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity

CAS number

Content in percent (%)*



Calcium carbonate	471-34-1	30 - 60%
Titanium dioxide	13463-67-7	1 - 5%
Propylene glycol	57-55-6	1 - 5%
Magnesite	546-93-0	0.5 - 1.5%
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	0.1 - 1%
n-(3,4-dichlorophenyl)-n,n- dimethylurea	330-54-1	0.1 - 1%
Kaolin Clay	1332-58-7	0.1 - 1%
Methyl benzimidazole-2-yl carbamate	10605-21-7	0.1 - 1%
Aluminum oxide	1344-28-1	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures		
I inst-aid incusures		
Ingestion:	Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.	
Inhalation:	Move to fresh air.	
Skin Contact:	Wash skin thoroughly with soap and water. Get medical attention if symptoms occur.	
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.	
Most important symptoms/effec	ts, acute and delayed	
Symptoms:	May cause skin and eye irritation.	
Indication of immediate medical attention and special treatment needed		
Treatment:	Symptoms may be delayed.	
5. Fire-fighting measures		
General Fire Hazards:	No unusual fire or explosion hazards noted.	
Suitable (and unsuitable) exting	uishing media	
Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.	
Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.	
Specific hazards arising from the chemical:	During fire, gases hazardous to health may be formed.	
Special protective equipment a	nd precautions for firefighters	



Special fire fighting procedures:	No data available.
Special protective equipment for fire-fighters:	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
6. Accidental release measures	\$
Personal precautions, protective equipment and emergency procedures:	No data available.
Methods and material for containment and cleaning up:	Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.
Notification Procedures:	In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.
Environmental Precautions:	Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.
7. Handling and storage	
Precautions for safe handling:	Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities:	Store locked up.

8. Exposure controls/personal protection


Control Parameters

Occupational Exposure Limits

Chemical Identity	Туре	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA	50 millions of particles per cubic foot of	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)



Magnesite - Total dust. PEL 15 mg/m3 US. OSHA Table Z-1 fumits for Air Contaminants (20 CFR 1910.1000) (02 2006) Contaminants (20 CFR 1910.1000) (02 2006) Crystalline Silica (Quartzy) TWA 0.025 mg/m3 US. OSHA Table Z-1 fumits for Air Contaminants (20 CFR 1910.1000) (02 2006) Crystalline Silica (Quartzy) TWA 0.025 mg/m3 US. OSHA Specifically Regulated Substances (29 CFR 1910.1001/03) (03 2016) Crystalline Silica (Quartzy) TWA 0.025 mg/m3 US. OSHA Specifically Regulated Substances (29 CFR 1910.1001/03) (03 2016) Crystalline Silica (Quartzy) TWA 0.025 mg/m3 US. OSHA Table Z-1 lumits for Air Contaminants (29 CFR 1910.1000) (03 2016) Crystalline Silica (Quartzy) TWA 0.102 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) Silica Sand - Respirable dica (Quartzy) TWA 0.1 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) r TWA 0.1 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) (2000) n=(14, 24, 24, 26, 26, 26, 26, 26, 26, 26, 26, 26, 26			air	
Contaminants (20 CFR 1910.1000) (02 2006) Verystalline Silica (Quartz) TWA 0.025 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (28 CFR 1910.1000) (02 2006) Crystalline Silica (Quartz) TWA 0.025 mg/m3 US. OSHA Specifically Regulated Substances (29 CFR 1010.1001.1053) (03 2016) Crystalline Silica (Quartz) TWA 0.05 mg/m3 US. OSHA Specifically Regulated Substances (29 CFR 1010.1001.1053) (03 2016) Crystalline Silica (Quartz) PEL 0.05 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (08 2016) Crystalline Silica (Quartz) PEL 0.05 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) Silica Sand - Respirable TWA 2.4 millions of patricles US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) Crystalline Silica (Quartz) TWA 0.1 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) Silica Sand - Respirable TWA 0.1 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) Crystalline Silica (Quartz) TWA 0.1 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Crystalline Silica (Quartz) TWA 2 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) K	Magnesite - Total dust.	PEL		US. OSHA Table Z-1 Limits for Air
Traction Contaminants (22 CFR 1910.1000) (02 2006). Crystalline Silica (Ountzy) TWA 0.025 mg/m3 US. ACGIH Threshold Limit Values (2011) Silica Sand - Respirable fraction. CoNTAMINE VALUES (2011) VIX. O.05 mg/m3 US. ACGIH Threshold Limit Values (2011) Crystalline Silica (Ountzy) TWA 0.025 mg/m3 US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (03 2016) Crystalline Silica (Ountzy) PEL 0.05 mg/m3 US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) (03 2016) Crystalline Silica (Ountzy) PEL 0.05 mg/m3 US. OSHA Table 2.7 Limits for Air Contaminants (29 CFR 1910.1000) (2000) Crystalline Silica (Ountzy) TWA 0.1 mg/m3 US. OSHA Table 2.3 (29 CFR 1910.1000) (2000) Silica Sand - Respirable (ust. TWA 0.1 mg/m3 US. ACGIH Threshold Limit Values (2011) Idmethylurea TWA 10 mg/m3 US. ACGIH Threshold Limit Values (2011) Kaolin Clay - Total dust. PEL 5 mg/m3 US. OSHA Table 2.7 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Kaolin Clay - Total dust. PEL 5 mg/m3 US. OSHA Table 2.3 (29 CFR 1910.1000) (02 2006) Kaolin Clay - Total dust. TWA				
Crystalline Silica (Ountzy) TWA 0.025 mg/m3 US. ACGIH Threshold Limit Values (2011) Silica Sand - Respirable dust. OSHA_AC 0.025 mg/m3 US. OSHA Specifically Regulated Substances Crystalline Silica (Ountzy) TWA 0.05 mg/m3 US. OSHA Specifically Regulated Substances Crystalline Silica (Ountzy) PEL 0.05 mg/m3 US. OSHA Specifically Regulated Substances Crystalline Silica (Ountzy) PEL 0.05 mg/m3 US. OSHA Table Z-1 Limits for Air Silica Sand - Respirable dust. TWA 2.4 millions Contaminats (29 CFR 1910.1000) (03 2016) Crystalline Silica (Ountzy) TWA 2.4 millions US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Silica Sand - Respirable TWA 0.1 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Crystalline Silica (Ountzy) TWA 0.1 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) (2001) Silica Sand - Respirable TWA 10 mg/m3 US. ACGIH Threshold Limit Values (2011) diadin Clay - Total dust. PEL 5 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)		PEL	5 mg/m3	
Silica Sand - Respirable fraction. TWA 0.05 mg/m3 US: OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (03 2016) Crystalline Silica (Quartzy) TWA 0.05 mg/m3 US: OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (03 2016) Crystalline Silica (Quartzy) PEL 0.05 mg/m3 US: OSHA Table 2-1 Limits for Air Contaminants (29 CFR 1910.1000) (03 2016) Crystalline Silica (Quartzy) TWA 0.1 mg/m3 US: OSHA Table 2-3 (29 CFR 1910.1000) (2000) risco Sand - Respirable dust. TWA 0.1 mg/m3 US: OSHA Table 2-3 (29 CFR 1910.1000) (2000) rotatine Silica (Quartzy) TWA 0.1 mg/m3 US: OSHA Table 2-3 (29 CFR 1910.1000) (2000) rotatine Silica (Quartzy) TWA 0.1 mg/m3 US: OSHA Table 2-3 (29 CFR 1910.1000) (2000) rotatine Silica (Quartzy) TWA 10 mg/m3 US: ACGIH Threshold Limit Values (2011) diamethylurea TWA 2 mg/m3 US: ACGIH Threshold Limit Values (2011) fraction. PEL 5 mg/m3 US: OSHA Table 2-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Kaolin Clay - Total dust. PEL 15 mg/m3 US: OSHA Table 2-3 (29 CFR 1910.1000) (03 2016) Kaolin Clay - Total d			0.005 / 0	
fraction. VMA 0.05 mg/m3 US. OSHA Specifically Regulated Substances (29 CFR 1910.1001.1053) (03 2016) Silica Sand - Respirable dust. OSHA_AC 0.025 mg/m3 US. OSHA Specifically Regulated Substances (29 CFR 1910.1001.1053) (03 2016) Crystalline Silica (Ouartzy) FEL 0.05 mg/m3 US. OSHA Table 2-1 Limits for Air Contaminants (29 CFR 1910.1000) (03 2016) Crystalline Silica (Ouartzy) TWA 2.4 millions of particles per cubic foot of air US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) - rotation of the spirable TWA 0.1 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) - rotation of the spirable TWA 0.1 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) - rotation clay - Respirable TWA 0.1 mg/m3 US. ACGIH Threshold Limit Values (2011) faction. PEL 5 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Kaolin Clay - Total dust. PEL 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Kaolin Clay - Total dust. PEL 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Kaolin Clay - Total dust. TWA 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) <td></td> <td>IWA</td> <td>0.025 mg/m3</td> <td>US. ACGIH Threshold Limit Values (2011)</td>		IWA	0.025 mg/m3	US. ACGIH Threshold Limit Values (2011)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust. TWA 0.05 mg/m3 US. OSHA Specifically. Regulated Substances (29 CFR 1910.1001-1053) (08 2016) Crystalline Silica (Quartz)/ Silica Sand - Respirable dust. OSHA_AC 0.025 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (20 CFR 1910.1000) (03 2016) Crystalline Silica (Quartz)/ Silica Sand - Respirable. TWA 2.4 millions of particles per cubic foot of air US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) 23 (20 CFR 1910.1000) - respirable. TWA 0.1 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) 20 (20 0) - respirable. TWA 0.1 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) 20 (20 0) - respirable TWA 0.1 mg/m3 US. ACGIH Threshold Limit Values (2011) - respirable TWA 2 mg/m3 US. ACGIH Threshold Limit Values (2011) fraction. PEL 5 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Kaolin Clay - Total dust. PEL 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2006) Kaolin Clay - Total dust. PEL 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2006) Kaolin Clay - Total dust. TWA <td< td=""><td></td><td></td><td></td><td></td></td<>				
OSHA_AC T 0.025 mg/m3 US. OSHA Specifically. Regulated Substances (29 CFR 1910 1001-1053) (08 2016) Crystalline Silica (Quartz)/ Silica Sand - Respirable dust. PEL 0.05 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (03 2016) Crystalline Silica (Quartz)/ Silica Sand - Respirable. TWA 2.4 millions of particles per cubic foot of air US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) n-(3,4-dichlorophenyl)-n,n- dimethylurea TWA 10 mg/m3 US. ACGIH Threshold Limit Values (2011) Kaolin Clay - Respirable TWA 2 mg/m3 US. ACGIH Threshold Limit Values (2011) Kaolin Clay - Total dust. PEL 5 mg/m3 US. ACGIH Threshold Limit Values (2011) Kaolin Clay - Total dust. PEL 15 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Kaolin Clay - Total dust. PEL 15 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (03 2016) Kaolin Clay - Total dust. PEL 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2006) Kaolin Clay - Respirable fraction. TWA 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Kaolin Clay - Total dust. TWA 15 mg/m3 US. OSHA Table		TWA	0.05 mg/m3	US. OSHA Specifically Regulated Substances
T Capstalline Silica (Quartz)' PEL 0.05 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (03 2016) Crystalline Silica (Quartz)/ Silica Sand - Respirable. TWA 2.4 millions of particles per cubic foot US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) n-(3.4-dichlorophenyl)-n,n- dimethylurea TWA 0.1 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) Kaolin Clay - Respirable TWA 2 mg/m3 US. ACGIH Threshold Limit Values (2011) Kaolin Clay - Total dust. PEL 5 mg/m3 US. ACGIH Threshold Limit Values (2011) Kaolin Clay - Total dust. PEL 5 mg/m3 US. OSHA Table Z-1 timits for Air Contaminants (29 CFR 1910.1000) (02 2006) Kaolin Clay - Total dust. PEL 15 mg/m3 US. OSHA Table Z-1 timits for Air Contaminants (29 CFR 1910.1000) (02 2006) Kaolin Clay - Respirable TWA 50 millions of particles per cubic foot of diar US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Kaolin Clay - Respirable TWA 50 millions of particles per cubic foot of diar US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Kaolin Clay - Respirable TWA 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Kaolin Clay - Total dust. TWA <td>Silica Sand - Respirable dust.</td> <td></td> <td></td> <td></td>	Silica Sand - Respirable dust.			
Shifea Sand - Respirable dust. Contaminants (29 CFR 1910.1000) (03 2016) Crystalline Silica (Quartz)/ Silica Sand - Respirable. TWA 2.4 millions of particles per cubic foot US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) n-(3.4-dichlorophenyl)-n,n- dimethylurea TWA 0.1 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) Kaolin Clay - Respirable TWA 2 mg/m3 US. ACGIH Threshold Limit Values (2011) Kaolin Clay - Total dust. PEL 5 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Kaolin Clay - Total dust. PEL 15 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Kaolin Clay - Total dust. PEL 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Kaolin Clay - Respirable TWA 50 millions of particles per cubic foot of US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Kaolin Clay - Total dust. TWA 15 millions of particles per cubic foot of US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Kaolin Clay - Total dust. TWA 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Kaolin Clay - Total dust. TWA 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) <		Т	5	(29 CFR 1910.1001-1053) (03 2016)
Silica Sand - Respirable. of particles per cubic food (3 air 0.1 mg/m3) (2000) (2000) n-(3,4-dichlorophenyl)-n, dimethylurea TWA 0.1 mg/m3 US. ACGIH Threshold Limit Values (2011) Kaolin Clay - Respirable fraction. TWA 2 mg/m3 US. ACGIH Threshold Limit Values (2011) Kaolin Clay - Respirable fraction. PEL 5 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Kaolin Clay - Total dust. PEL 15 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Kaolin Clay - Total dust. PEL 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Kaolin Clay - Respirable fraction. TWA 50 millions of particles per cubic foot of air US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Kaolin Clay - Total dust. TWA 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Kaolin Clay - Total dust. TWA 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Aluminum oxide - Respirable fraction. TWA 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Aluminum oxide - Total dust. PEL 5 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)	Silica Sand - Respirable dust.	PEL	0.05 mg/m3	Contaminants (29 CFR 1910.1000) (03 2016)
per cubic foot of air per cubic foot of air TWA 0.1 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) n-(3,4-dichlorophenyl)-n,n- dimethylurea TWA 10 mg/m3 US. ACGIH Threshold Limit Values (2011) Kaolin Clay - Respirable fraction. TWA 2 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Kaolin Clay - Total dust. PEL 5 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Kaolin Clay - Total dust. PEL 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (02 2006) Kaolin Clay - Total dust. PEL 50 millions of particles per cubic foot of air US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Kaolin Clay - Respirable fraction. TWA 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Kaolin Clay - Total dust. TWA 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Kaolin Clay - Total dust. TWA 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Aluminum oxide - Respirable fraction. TWA 15 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Aluminum oxide - Total dust. PEL 5 mg/m3		TWA		
of air of air TWA 0.1 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) n-(3,4-dichlorophenyl)-n,n- dimethylurea TWA 10 mg/m3 US. ACGIH Threshold Limit Values (2011) Kaolin Clay - Respirable fraction. TWA 2 mg/m3 US. ACGIH Threshold Limit Values (2011) Kaolin Clay - Total dust. PEL 5 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Kaolin Clay - Total dust. PEL 15 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Kaolin Clay - Total dust. PEL 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2006) Kaolin Clay - Respirable fraction. TWA 15 millions of particles per cubic foot of air US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Kaolin Clay - Total dust. TWA 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Kaolin Clay - Total dust. TWA 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Kaolin Clay - Total dust. TWA 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Kaolin Clay - Total dust. TWA 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)	Silica Sand - Respirable.			(2000)
TWA 0.1 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) n-(3,4-dichlorophenyl)-n,n- dimethylurea TWA 10 mg/m3 US. ACGIH Threshold Limit Values (2011) Kaolin Clay - Respirable fraction. TWA 2 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Kaolin Clay - Total dust. PEL 5 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Kaolin Clay - Total dust. PEL 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (02 2006) Kaolin Clay - Respirable fraction. TWA 50 millions of patricles per cubic foot of air US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Kaolin Clay - Respirable fraction. TWA 15 millions of patricles per cubic foot of air US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Kaolin Clay - Total dust. TWA 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Kaolin Clay - Total dust. TWA 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Aluminum oxide - Respirable fraction. TWA 15 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Aluminum oxide - Total dust. PEL 5 mg/m3 US. OSHA Table Z-1 Limits for Ai				
Image: Construction of the construction of		TWA		US_OSHA Table 7-3 (29 CER 1910 1000)
dimethylurea TWA 2 mg/m3 US. ACGIH Threshold Limit Values (2011) fraction. PEL 5 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Kaolin Clay - Total dust. PEL 15 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Kaolin Clay - Total dust. PEL 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (02 2006) Kaolin Clay - Respirable fraction. TWA 50 millions of particles per cubic foot of air US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Kaolin Clay - Respirable fraction. TWA 15 millions of particles per cubic foot of air US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Kaolin Clay - Total dust. TWA 5 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Kaolin Clay - Total dust. TWA 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Kaolin Clay - Total dust. TWA 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Kaolin Clay - Total dust. TWA 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Aluminum oxide - Total dust. PEL 5 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (02 2006) <			0.1go	
fraction. PEL 5 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Kaolin Clay - Total dust. PEL 15 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) TWA 50 millions of particles per cubic foot of fraction. US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Kaolin Clay - Respirable fraction. TWA 15 millions of particles per cubic foot of air US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Kaolin Clay - Respirable fraction. TWA 15 millions of particles per cubic foot of air US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Kaolin Clay - Total dust. TWA 5 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Kaolin Clay - Total dust. TWA 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Aluminum oxide - Respirable fraction. TWA 15 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Aluminum oxide - Total dust. PEL 5 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Aluminum oxide - Total dust. PEL 5 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) Aluminum oxide - Respirable fraction. TWA 15 mg/m3 US. OSHA Table Z-3 (29 C		TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Kaolin Clay - Total dust.PEL15 mg/m3US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)TWA50 millions of particles per cubic foot ofUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Kaolin Clay - Respirable fraction.TWA15 millions of particles per cubic foot ofUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Kaolin Clay - Respirable fraction.TWA15 millions of particles per cubic foot ofUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Kaolin Clay - Respirable fraction.TWA15 mg/m3 us. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Kaolin Clay - Total dust.TWA15 mg/m3 us. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA15 mg/m3 aUS. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)Aluminum oxide - Total dust.PEL5 mg/m3 aUS. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)Aluminum oxide - Respirable fraction.TWA15 mg/m3 aUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA15 mg/m3 aUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA15 mg/m3 aUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Total dust.TWA15 mg/m3 aUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide		TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
Kaolin Clay - Total dust.PEL15 mg/m3US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)TWA50 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Kaolin Clay - Respirable fraction.TWA15 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Kaolin Clay - Respirable fraction.TWA15 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Kaolin Clay - Total dust.TWA5 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Kaolin Clay - Total dust.TWA15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA15 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)Aluminum oxide - Total dust.PEL15 mg/m3 particles per cubic foot of airUS. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)Aluminum oxide - Respirable fraction.TWA15 mg/m3 particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA15 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA15 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Total dust.TWA15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 20		PEL	5 mg/m3	
TWA50 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Kaolin Clay - Respirable fraction.TWA15 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Kaolin Clay - Total dust.TWA5 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Kaolin Clay - Total dust.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Total dust.PEL5 mg/m3US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)Aluminum oxide - Total dust.PEL15 mg/m3US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)Aluminum oxide - Respirable fraction.TWA50 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA15 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA15 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Total dust.TWA15 mg/m3 <td>Kaolin Clay - Total dust.</td> <td>PEL</td> <td>15 mg/m3</td> <td>US. OSHA Table Z-1 Limits for Air</td>	Kaolin Clay - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air
Kaolin Clay - Respirable fraction.TWA15 millions of ur particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Kaolin Clay - Total dust.TWA5 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Kaolin Clay - Total dust.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA1 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Total dust.PEL5 mg/m3US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)Aluminum oxide - Total dust.PEL15 mg/m3US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)Aluminum oxide - Total dust.PEL15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (02 2006)TWAS0 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA15 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Total dust.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)		TWA		US. OSHA Table Z-3 (29 CFR 1910.1000) (03
Kaolin Clay - Respirable fraction.TWA15 millions of particles per cubic foot ofUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Kaolin Clay - Total dust.TWA5 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Kaolin Clay - Total dust.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Total dust.TWA1 mg/m3US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)Aluminum oxide - Total dust.PEL5 mg/m3US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)Aluminum oxide - Total dust.PEL15 mg/m3US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)Aluminum oxide - Respirable fraction.TWA50 millions of particles per cubic foot ofUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Total dust.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Total dust.				2016)
Kaolin Clay - Respirable fraction.TWA15 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Kaolin Clay - Total dust.TWA5 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Kaolin Clay - Total dust.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA1 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Total dust.PEL5 mg/m3US. ACGIH Threshold Limit Values (2011)Aluminum oxide - Total dust.PEL15 mg/m3US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)Aluminum oxide - Total dust.PEL15 mg/m3US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)Aluminum oxide - Respirable fraction.TWA50 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA15 mg/m3 2016)US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Total dust.TWA15 mg/m3 2016)US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Total dust.TWA15 mg/m3 2016)US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)				
fraction.particles per cubic foot of air2016)TWA5 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Kaolin Clay - Total dust.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA1 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA1 mg/m3US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)Aluminum oxide - Total dust.PEL5 mg/m3US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)Aluminum oxide - Total dust.PEL15 mg/m3US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)Aluminum oxide - Respirable fraction.TWA50 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Total dust.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Total dust.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)	Kaolin Clay - Respirable	TWA		US. OSHA Table Z-3 (29 CFR 1910,1000) (03
interpretationinterpretationKaolin Clay - Total dust.TWA5 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Kaolin Clay - Total dust.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA1 mg/m3US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)Aluminum oxide - Total dust.PEL5 mg/m3US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)Aluminum oxide - Total dust.PEL15 mg/m3US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)Aluminum oxide - Respirable fraction.TWA50 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA15 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Total dust.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Total dust.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)	, ,			
TWA5 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Kaolin Clay - Total dust.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA1 mg/m3US. OSHA Table Z-1 (29 CFR 1910.1000) (02 2016)Aluminum oxide - Total dust.PEL5 mg/m3US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)Aluminum oxide - Total dust.PEL15 mg/m3US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)TWA50 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (02 2006)Aluminum oxide - Respirable fraction.TWA15 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Total dust.TWA15 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Total dust.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Total dust.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)				
Kaolin Clay - Total dust.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA1 mg/m3US. ACGIH Threshold Limit Values (2011)PEL5 mg/m3US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)Aluminum oxide - Total dust.PEL15 mg/m3US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)Aluminum oxide - Total dust.PEL15 mg/m3US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)Aluminum oxide - Respirable fraction.TWA50 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA15 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Total dust.TWA15 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Total dust.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)		T)A/A		
Kaolin Clay - Total dust.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA1 mg/m3US. ACGIH Threshold Limit Values (2011)PEL5 mg/m3US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)Aluminum oxide - Total dust.PEL15 mg/m3US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)Aluminum oxide - Total dust.PEL15 mg/m3US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)Aluminum oxide - Respirable fraction.TWA50 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA15 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Total dust.TWA15 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Total dust.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)		IWA	5 mg/m3	
Aluminum oxide - Respirable fraction.TWA1 mg/m3US. ACGIH Threshold Limit Values (2011)PEL5 mg/m3US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)Aluminum oxide - Total dust.PEL15 mg/m3US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)Aluminum oxide - Total dust.PEL15 mg/m3US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)Aluminum oxide - Respirable fraction.TWA50 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA15 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Total dust.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Total dust.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)	Kaolin Clay - Total dust.	TWA	15 ma/m3	
fraction.PEL5 mg/m3US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)Aluminum oxide - Total dust.PEL15 mg/m3US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)TWA50 millions of particles per cubic foot of fraction.US. OSHA Table Z-3 (29 CFR 1910.1000) (02 2006)Aluminum oxide - Respirable fraction.TWA15 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA15 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Total dust.TWA5 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)				
Aluminum oxide - Total dust.PEL15 mg/m3US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)Aluminum oxide - Total dust.PEL15 mg/m3US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)TWA50 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA15 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)TWA15 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Total dust.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)		TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
TWA50 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (02 2006)Aluminum oxide - Respirable fraction.TWA15 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)TWA15 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Respirable fraction.TWA15 millions of particles per cubic foot of airTWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Total dust.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)			5 mg/m3	Contaminants (29 CFR 1910.1000) (02 2006)
particles per cubic foot of air2016)Aluminum oxide - Respirable fraction.TWA15 millions of particles per cubic foot of airUS. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)Aluminum oxide - Total dust.TWA15 mg/m3Aluminum oxide - Total dust.TWA15 mg/m3US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)	Aluminum oxide - Total dust.		5	Contaminants (29 CFR 1910.1000) (02 2006)
Aluminum oxide - Respirable fraction. TWA 15 millions of particles per cubic foot of air US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) TWA 15 millions of particles per cubic foot of air US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) TWA 5 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Aluminum oxide - Total dust. TWA 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03		TWA		
Aluminum oxide - Respirable fraction. TWA 15 millions of particles per cubic foot of air US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) TWA 5 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Aluminum oxide - Total dust. TWA 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03				2016)
Aluminum oxide - Respirable fraction. TWA 15 millions of particles per cubic foot of air US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) TWA 5 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Aluminum oxide - Total dust. TWA 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)				
fraction. particles per cubic foot of air 2016) TWA 5 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Aluminum oxide - Total dust. TWA 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)	Aluminum oxide - Respirable	TWA		US. OSHA Table Z-3 (29 CFR 1910.1000) (03
air TWA 5 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Aluminum oxide - Total dust. TWA 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03				
TWA 5 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) Aluminum oxide - Total dust. TWA 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03				
2016) Aluminum oxide - Total dust. TWA 15 mg/m3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03				
			5	2016)
	Aluminum oxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)





Chemical name	Туре	Exposure Limit	Values	Source
Calcium carbonate - Total dust.	STEL		20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA		10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Titanium dioxide - Total dust.	TWA		10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA		10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Propylene glycol - Aerosol.	TWA		10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Propylene glycol - Vapor and aerosol.	TWA	50 ppm	155 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.	.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA		0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA		0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Appropriate Engineering
ControlsObserve good industrial hygiene practices. Observe occupational exposure
limits and minimize the risk of inhalation of vapors and mist. Mechanical
ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information:	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	



Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing.
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use.

9. Physical and chemical properties

Appearance	
Physical state:	liquid
Form:	liquid
Color:	Pale yellow
Odor:	Mild
Odor threshold:	No data available.
pH:	8 - 10
Melting point/freezing point:	-0.00 °C 32 °F
Initial boiling point and boiling range:	No data available.
Flash Point:	> 93 °C > 199 °F
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.46
Solubility(ies)	
Solubility in water:	Soluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:

No data available.



Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Strong acids. Strong bases.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of ex Inhalation:	(posure In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.	
Skin Contact:	May be harmful in contact with skin.	
Eye contact:	Eye contact is possible and should be avoided.	
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.	
Symptoms related to the physical, chemical and toxicological characteristics		
Inhalation:	No data available.	
Skin Contact:	No data available.	
Eye contact:	No data available.	
Ingestion:	No data available.	

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral Product:

Not classified for acute toxicity based on available data.



Calcium carbonate	LD 50 (Rat): > 2,000 mg/kg
Titanium dioxide	LD 50 (Rat): > 5,000 mg/kg
Propylene glycol	LD 50 (Rat): 22,000 mg/kg
Magnesite	LD 50 (Rat): > 2,000 mg/kg
n-(3,4-dichlorophenyl)- n,n-dimethylurea	LD 50 (Rat): 4,150 mg/kg
Kaolin Clay	LD 50 (Rat): > 5,000 mg/kg
Methyl benzimidazole-2- yl carbamate	LD 50 (Rat): 6,400 mg/kg
Aluminum oxide	LD 50 (Rat): > 10,000 mg/kg
Dermal Product:	ATEmix: 3,361.22 mg/kg
Inhalation Product:	ATEmix: 3.02 mg/l
Repeated dose toxicity Product:	No data available.
Skin Corrosion/Irritation Product:	No data available.

Specified substance(s):



Calcium carbonate	in vivo (Rabbit): Not irritant Experimental result, Key study
Titanium dioxide	in vivo (Rabbit): Not irritant Experimental result, Supporting study
Propylene glycol	in vivo (Rabbit): Not irritant Experimental result, Key study
Magnesite	In vitro (Human, in vitro reconstituted epidermis model): Not irritant Experimental result, Key study
n-(3,4-dichlorophenyl)- n,n-dimethylurea	Possibly Irritating in vivo (Rabbit): Not irritant Experimental result, Key study
Aluminum oxide	in vivo (Rabbit): Not irritant Experimental result, Key study

Serious Eye Damage/Eye Irritation

Product: Specified substance(s):	No data available.
Calcium carbonate	Rabbit, 24 - 72 hrs: Not irritating
Titanium dioxide	Rabbit, 24 hrs: Not irritating
Magnesite	Reconstituted Corneal Epithelium model, 10 min: Not irritating
Aluminum oxide	Rabbit, 24 hrs: Not irritating

Respiratory or Skin Sensitization Product: No data available.

Carcinogenicity	
	N N N N N N N N N N

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Crystalline Silica (Quartz)/ Silica Sand	Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens: Crystalline Silica Known To Be Human Carcinogen.

Crystalline Silica Known To Be Human Carcinogen. (Quartz)/ Silica Sand

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified



Germ Cell Mutagenicity

In vitro Product:	No data available.
In vivo Product:	No data available.
Reproductive toxicity Product:	May damage fertility or the unborn child.
Specific Target Organ Toxicity - Single ExposureProduct:No data available.	
Specific Target Organ Toxicity - Repeated Exposure Product: No data available.	
Aspiration Hazard Product:	No data available.
Other effects:	No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish Product:	No data available.
Specified substance(s): Propylene glycol	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 29,485 - 39,339 mg/l Mortality
n-(3,4-dichlorophenyl)- n,n-dimethylurea	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.4 - 15 mg/l Mortality
Methyl benzimidazole-2- yl carbamate	LC 50 (Bluegill (Lepomis macrochirus), 96 h): > 3.2 mg/l Mortality
Aquatic Invertebrates Product:	No data available.
Specified substance(s): Titanium dioxide	EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication



Propylene glycol	EC 50 (Water flea (Daphnia magna), 48 h): > 10,000 mg/l Intoxication	
n-(3,4-dichlorophenyl)- n,n-dimethylurea	EC 50 (Water flea (Daphnia pulex), 48 h): 1.4 mg/l Mortality	
Chronic hazards to the aquation	c environment:	
Fish Product:	No data available.	
Specified substance(s): Propylene glycol	NOAEL (Pimephales promelas, 7 d): 11,530 mg/l Experimental result, Not specified	
Aquatic Invertebrates Product:	No data available.	
Toxicity to Aquatic Plants Product:	No data available.	
Persistence and Degradability		
Biodegradation Product:	No data available.	
BOD/COD Ratio Product:	No data available.	
Bioaccumulative potential Bioconcentration Factor (BCF) Product: No data available.		
Partition Coefficient n-octanol / w Product:	vater (log Kow) No data available.	
Specified substance(s): Propylene glycol	Log Kow: -0.92	
n-(3,4-dichlorophenyl)- n,n-dimethylurea	Log Kow: 2.68	
Methyl benzimidazole-2- yl carbamate	Log Kow: 1.52	
Mobility in soil:	No data available.	
Other adverse effects:	Harmful to aquatic organisms.	



13. Disposal considerations	
Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.
14. Transport information	

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
n-(3,4-dichlorophenyl)-	100 lbs.
n,n-dimethylurea	
Methyl benzimidazole-2-	10 lbs.
yl carbamate	
Ammonium hydroxide	1000 lbs.
Sodium nitrite	100 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.



SARA 304 Emergency Release Notification Chemical Identity Reportable quantity

Chemical Identity	Reportable qua
n-(3,4-dichlorophenyl)-	100 lbs.
n,n-dimethylurea	
Methyl benzimidazole-2-	10 lbs.
yl carbamate	
Ammonium hydroxide	1000 lbs.
Sodium nitrite	100 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Calcium carbonate	10000 lbs
Titanium dioxide	10000 lbs
Propylene glycol	10000 lbs
Magnesite	10000 lbs
Crystalline Silica (Quartz)/	10000 lbs
Silica Sand	
n-(3,4-dichlorophenyl)-n,n-	10000 lbs
dimethylurea	
Kaolin Clay	10000 lbs
Methyl benzimidazole-2-yl	10000 lbs
carbamate	
Aluminum oxide	10000 lbs

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3) None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65



WARNING

Cancer - www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Calcium carbonate Titanium dioxide Propylene glycol Crystalline Silica (Quartz)/ Silica Sand

US. Massachusetts RTK - Substance List

Chemical Identity

Calcium carbonate Titanium dioxide Crystalline Silica (Quartz)/ Silica Sand



US. Pennsylvania RTK - Hazardous Substances

<u>Chemical Identity</u> Calcium carbonate Titanium dioxide Propylene glycol

US. Rhode Island RTK

Chemical Identity Calcium carbonate Titanium dioxide Propylene glycol

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

VOC:

Regulatory VOC (less water and exempt solvent)	:	36 g/l
VOC Method 310	:	1.29 %



Inventory Status: Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	One or more components in this product are not listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:	07/21/2018
Version #:	1.1
Further Information:	No data available.



Disclaimer:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.