

Revision Date: 06/08/2018

SAFETY DATA SHEET

1. Identification

Material name: SOLARGARD H.B. SCC COLONIAL TAN 5 GL

Material: 1512042505P

Recommended use and restriction on use

Recommended use: Coatings Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco Incorporated 3735 Green Road BEACHWOOD OH 44122 US

Contact person:EH&S DepartmentTelephone:216-292-5000

Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Carcinogenicity Category 1A

Unknown toxicity - Health

Acute toxicity, oral 34.27 %
Acute toxicity, dermal 39.22 %
Acute toxicity, inhalation, vapor 100 %
Acute toxicity, inhalation, dust 99.69 %
or mist

Environmental Hazards

Acute hazards to the aquatic Category 3

environment

Unknown toxicity - Environment

Acute hazards to the aquatic 90.86 %

environment

Chronic hazards to the aquatic 97.3 %

environment

Label Elements

Hazard Symbol:



Revision Date: 06/08/2018



Signal Word: Danger

Hazard Statement: May cause cancer.

Harmful to aquatic life.

Precautionary Statements

Prevention: Obtain special instructions before use. Do not handle until all safety

precautions have been read and understood. Use personal protective

equipment as required. Avoid release to the environment.

Response: IF exposed or concerned: Get medical advice/attention.

Storage: Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC):

None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	20 - <50%
Titanium dioxide	13463-67-7	1 - <5%
Propylene glycol	57-55-6	1 - <5%
Zinc oxide	1314-13-2	1 - <5%
Cellulose	9004-34-6	1 - <5%
Clay	1332-58-7	0.1 - <1%
Magnesite	546-93-0	0.1 - <1%
Talc	14807-96-6	0.1 - <1%
Aluminum oxide	1344-28-1	0.1 - <1%
Trade Secret	Trade Secret	0.1 - <1%
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	0.1 - <1%
Ammonium hydroxide	1336-21-6	0.1 - <1%

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures



Revision Date: 06/08/2018

Ingestion: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

Inhalation: Move to fresh air.

Skin Contact: Wash skin thoroughly with soap and water. Get medical attention if

symptoms occur.

Eye contact: Any material that contacts the eye should be washed out immediately with

water. If easy to do, remove contact lenses. If eye irritation persists: Get

medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be

worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: No data available.

Methods and material for containment and cleaning

up:

Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for

disposal according to local regulations.



Revision Date: 06/08/2018

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in

accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or

spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Precautions for safe handling: Do not handle until all safety precautions have been read and understood.

Obtain special instructions before use. Use personal protective equipment as required. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage,

including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Туре	Exposure Limit Values	Source
Calcium carbonate - Total	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air
dust.		_	Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate -	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air
Respirable fraction.			Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air
			Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide - Respirable	TWA	15 millions of	US. OSHA Table Z-3 (29 CFR 1910.1000) (03
fraction.		particles per	2016)
		cubic foot of	
		air	
Titanium dioxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA	50 millions of	US. OSHA Table Z-3 (29 CFR 1910.1000) (03
That have a control of the control		particles per	2016)
		cubic foot of	
		air	
Zinc oxide - Respirable	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
fraction.			, ,
	STEL	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Zinc oxide - Fume.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air
			Contaminants (29 CFR 1910.1000) (02 2006)
Zinc oxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air
			Contaminants (29 CFR 1910.1000) (02 2006)
Zinc oxide - Respirable	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air
fraction.			Contaminants (29 CFR 1910.1000) (02 2006)
Cellulose	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Cellulose - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air
			Contaminants (29 CFR 1910.1000) (02 2006)
Cellulose - Respirable	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air
fraction.			Contaminants (29 CFR 1910.1000) (02 2006)
Clay - Respirable fraction.	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air
			Contaminants (29 CFR 1910.1000) (02 2006)
Clay - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air
			Contaminants (29 CFR 1910.1000) (02 2006)



Revision Date: 06/08/2018

	TWA	50 millions of particles per cubic foot of	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
		air	
Clay - Respirable fraction.	TWA	15 millions of	US. OSHA Table Z-3 (29 CFR 1910.1000) (03
		particles per	2016)
		cubic foot of	
		air	
	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03
		· ·	2016)
Clay - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03
,		3	2016)
Magnesite - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air
g			Contaminants (29 CFR 1910.1000) (02 2006)
Magnesite - Respirable	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air
fraction.	1	o mg/mo	Contaminants (29 CFR 1910.1000) (02 2006)
Talc - Respirable fraction.	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
Talc	TWA	20 millions of	US. OSHA Table Z-3 (29 CFR 1910.1000)
Taic	IVVA		
		particles per	(2000)
		cubic foot of	
		air	
Talc - Respirable.	TWA	2.4 millions	US. OSHA Table Z-3 (29 CFR 1910.1000)
		of particles	(2000)
		per cubic foot	
		of air	
	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000)
		9	(2000)
Aluminum oxide - Respirable	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
fraction.		g/iiio	Co. 70 Ciri Tili Colloid Ellilli Valado (2011)
naction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air
	FEL	5 mg/m3	Contaminants (29 CFR 1910.1000) (02 2006)
Almaiana anida Tatal duat	DEL	45/2	
Aluminum oxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air
			Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of	US. OSHA Table Z-3 (29 CFR 1910.1000) (03
		particles per	2016)
		cubic foot of	
		air	
Aluminum oxide - Respirable	TWA	15 millions of	US. OSHA Table Z-3 (29 CFR 1910.1000) (03
fraction.		particles per	2016)
		cubic foot of	• • • •
		air	
	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03
	1 447.1	o mg/mo	2016)
Aluminum oxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03
Aluminum oxide - Total dust.	IVVA	15 mg/m3	, , ,
	TIA/A	40 1 2	2016)
Trade Secret - Inhalable	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (03 2015)
particles.			
	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (03 2015)
Trade Secret - Respirable		5g, 1110	221112 3111 1111 201101 (00 Z0 10)
particles.	<u> </u>		
Trade Secret - Respirable	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air
fraction.			Contaminants (29 CFR 1910.1000) (02 2006)
	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air
Trade Secret - Total dust.	' <u></u> -	15 mg/ms	Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000)
	IVVA	10 1119/1113	,
	T10/0	50	(2000)
	TWA	50 millions of	US. OSHA Table Z-3 (29 CFR 1910.1000)
		particles per	(2000)
		cubic foot of	
		air	
Trade Secret - Respirable	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000)
fraction.		-	(2000)
naodon.	TWA	15 millions of	US. OSHA Table Z-3 (29 CFR 1910.1000)
	1 1 1 1 1 1		(2000)
		particles per	(2000)
		cubic foot of	
	i l	air	
0 1 111 2111 12	T14/4		LIC ACCULTU I III III III III III III III III III
Crystalline Silica (Quartz)/	TWA	0.025 mg/m3	US. ACGIH Threshold Limit Values (2011)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA		US. ACGIH Threshold Limit Values (2011)



Revision Date: 06/08/2018

			•
Crystalline Silica (Quartz)/	TWA	0.05 mg/m3	US. OSHA Specifically Regulated Substances
Silica Sand - Respirable dust.			(29 CFR 1910.1001-1053) (03 2016)
	OSHA AC	0.025 mg/m3	US. OSHA Specifically Regulated Substances
	T	5.625 mg/mc	(29 CFR 1910.1001-1053) (03 2016)
Crystalline Silica (Quartz)/	PEL	0.05 mg/m3	US. OSHA Table Z-1 Limits for Air
Silica Sand - Respirable dust.		3 1	Contaminants (29 CFR 1910.1000) (03 2016)
Crystalline Silica (Quartz)/	TWA	2.4 millions	US. OSHA Table Z-3 (29 CFR 1910.1000)
Silica Sand - Respirable.		of particles	(2000)
		per cubic foot	(====)
		·	
		of air	
	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000)
			(2000)
Ammonium hydroxide	STEL	35 ppm	US. ACGIH Threshold Limit Values (2011)
	TWA	25 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	50 ppm 35 mg/m3	US. OSHA Table Z-1 Limits for Air
			Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	Туре	Exposure Limit	Values	Source
Calcium carbonate - Total dust.	STEL		20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA		10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA		10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA		10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Propylene glycol - Aerosol.	TWA		10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Propylene glycol - Vapor and aerosol.	TWA	50 ppm	155 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Zinc oxide - Respirable.	TWA		2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL		10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Zinc oxide - Respirable fraction.	TWA		2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL		10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)



Revision Date: 06/08/2018

Zinc oxide - Fume.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Zinc oxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Zinc oxide - Fume.	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Cellulose - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Cellulose - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Cellulose	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Cellulose - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Talc - Respirable.	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Talc	TWA	2 fibers/mL	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Talc - Respirable fraction.	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Talc - Respirable dust.	TWA	3 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information: Good general ventilation (typically 10 air changes per hour) should be used.

Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists,

mechanical generation of dusts, drying of solids, etc.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other: Wear suitable protective clothing.



Revision Date: 06/08/2018

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product.

9. Physical and chemical properties

Appearance

Physical state: liquid
Form: liquid
Color: Beige
Odor: Mild

Odor threshold:

pH:

No data available.

100 °C 212 °F

No data available.

Evaporation rate:

Slower than Ether

Flammability (solid, gas):

No
Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper (%):

No data available.

No data available.

No data available.

Vapor pressure:

No data available.

Vapor density: Vapors are heavier than air and may travel along the floor and

in the bottom of containers.

Relative density: 1.25

Solubility(ies)

Solubility in water: Soluble

Solubility (other): No data available.

Partition coefficient (n-octanol/water): No data available.

Auto-ignition temperature:No data available.Decomposition temperature:No data available.Viscosity:No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.



Revision Date: 06/08/2018

Conditions to avoid: Avoid heat or contamination.

Incompatible Materials: Strong acids. Strong bases.

Hazardous Decomposition

Products:

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation: In high concentrations, vapors, fumes or mists may irritate nose, throat and

mucus membranes.

Skin Contact: May be harmful in contact with skin.

Eye contact: Eye contact is possible and should be avoided.

Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: 119,151.27 mg/kg

Dermal

Product: ATEmix: 3,862.14 mg/kg

Inhalation

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Titanium dioxide LC 50 (Rat): 3.43 mg/l

Zinc oxide LC 50 (Rat): > 5,700 mg/m3

Cellulose LC 50 (Rabbit): 20.1 mg/l

Aluminum oxide LC 50 (Rat): 7.6 mg/l

Trade Secret LC 50 (Rabbit): 20.1 mg/l



Revision Date: 06/08/2018

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Calcium carbonate in vivo (Rabbit): Not irritant Experimental result, Key study

Titanium dioxide in vivo (Rabbit): Not irritant Experimental result, Supporting study

Propylene glycol in vivo (Rabbit): Not irritant Experimental result, Key study

Zinc oxide in vivo (Rabbit): Not irritant Experimental result, Key study

Magnesite In vitro (Human, in vitro reconstituted epidermis model): Not irritant

Experimental result, Key study

Aluminum oxide in vivo (Rabbit): Not irritant Experimental result, Key study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Calcium carbonate Rabbit, 24 - 72 hrs: Not irritating

Titanium dioxide Rabbit, 24 hrs: Not irritating

Zinc oxide Rabbit, 24 - 72 hrs: Not irritating

Magnesite Reconstituted Corneal Epithelium model, 10 min: Not irritating

Aluminum oxide Rabbit, 24 hrs: Not irritating

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: No data available.



Revision Date: 06/08/2018

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Titanium dioxide Overall evaluation: Possibly carcinogenic to humans.

Talc Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall

evaluation: Possibly carcinogenic to humans.

Crystalline Silica

(Quartz)/ Silica

Sand

Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Crystalline Silica Known To Be Human Carcinogen.

(Quartz)/ Silica

Sand

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Crystalline Silica

(Quartz)/ Silica Cancer

Sand

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.



Revision Date: 06/08/2018

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Propylene glycol LC 50 (Fathead minnow (Pimephales promelas), 96 h): 29,485 - 39,339 mg/l

Mortality

Zinc oxide LC 50 (Fathead minnow (Pimephales promelas), 96 h): 2,246 mg/l Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Titanium dioxide EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication

Propylene glycol EC 50 (Water flea (Daphnia magna), 48 h): > 10,000 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Propylene glycol NOAEL (Pimephales promelas, 7 d): 11,530 mg/l Experimental result, Not

specified

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)



Revision Date: 06/08/2018

Product: No data available.

Specified substance(s):

Propylene glycol Log Kow: -0.92

Mobility in soil: No data available.

Other adverse effects: Harmful to aquatic organisms.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.



Revision Date: 06/08/2018

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Chemical IdentityOSHA hazard(s)Crystalline Silicakidney effects(Quartz)/ Silica Sandlung effects

immune system effects

Cancer

Acrylonitrile Liver

Central nervous system

Flammability
Eye irritation
Skin irritation
Skin sensitization
Respiratory irritation

Cancer Acute toxicity

Ethylene oxide Skin sensitization

Reproductive toxicity

Mutagenicity
Eye irritation
Acute toxicity

respiratory tract irritation

Cancer Skin irritation Flammability

Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity Reportable quantity

Ammonium hydroxide 1000 lbs. n-(3,4-dichlorophenyl)- 100 lbs.

n,n-dimethylurea

Methyl benzimidazole-2- 10 lbs.

yl carbamate

Ammonia 100 lbs.
Acrylamide 5000 lbs.
Acrylonitrile 100 lbs.
Acetaldehyde 1000 lbs.
p-Dioxane 100 lbs.
Ethylene oxide 10 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard



Revision Date: 06/08/2018

SARA 302 Extremely Hazardous Substance

Reportable	
------------	--

Chemical IdentityquantityThreshold Planning QuantityAmmonia100 lbs.500 lbs.Acrylamide5000 lbs.----Acrylonitrile100 lbs.10000 lbs.Ethylene oxide10 lbs.1000 lbs.

SARA 304 Emergency Release Notification

Chemical Identity Reportable quantity

Zinc oxide

Ammonium hydroxide 1000 lbs. n-(3,4-dichlorophenyl)- 100 lbs.

n,n-dimethylurea

Methyl benzimidazole-2- 10 lbs.

yl carbamate

Ammonia 100 lbs.
Acrylamide 5000 lbs.
Acrylonitrile 100 lbs.
Acetaldehyde 1000 lbs.
p-Dioxane 100 lbs.
Ethylene oxide 10 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity Threshold Planning Quantity

Ammonia 500lbs Acrylamide 500lbs Acrylonitrile 500lbs Ethylene oxide 500lbs Calcium carbonate 10000 lbs Titanium dioxide 10000 lbs Propylene glycol 10000 lbs Zinc oxide 10000 lbs Cellulose 10000 lbs Clay 10000 lbs Magnesite 10000 lbs Talc 10000 lbs 10000 lbs Aluminum oxide 10000 lbs Trade Secret Crystalline Silica (Quartz)/ 10000 lbs Silica Sand

Ammonium hydroxide 10000 lbs

SARA 313 (TRI Reporting)

Chemical Identity

Zinc oxide

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Chemical Identity	Reportable quantity
Ammonia	lbs
Ammonia	lbs

Acrylonitrile lbs
Acetaldehyde lbs
Ethylene oxide lbs



Revision Date: 06/08/2018

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Titanium dioxide Carcinogenic. 09 2011 Crystalline Silica (Quartz)/ Carcinogenic. 09 2011

Silica Sand

n-(3,4-dichlorophenyl)-n,n- Carcinogenic. 09 2011

dimethylurea

Carbon Black Carcinogenic. 09 2011 Acrylamide Carcinogenic. 09 2011

Acrylamide Male reproductive toxin. 09 2011
Acrylamide Developmental toxin. 09 2011
n-Methylacrylamide Carcinogenic. 09 2011
Acrylonitrile Carcinogenic. 09 2011

Acetaldehyde Carcinogenic. 09 2011 p-Dioxane Carcinogenic. 09 2011 Ethylene oxide Carcinogenic. 09 2011

Ethylene oxide Female reproductive toxin. 09 2011
Ethylene oxide Male reproductive toxin. 09 2011
Ethylene oxide Developmental toxin. 09 2011

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Calcium carbonate Titanium dioxide Propylene glycol Zinc oxide

Cellulose Talc

Crystalline Silica (Quartz)/ Silica Sand

US. Massachusetts RTK - Substance List

Chemical Identity

Calcium carbonate

Titanium dioxide

Zinc oxide

Cellulose

Crystalline Silica (Quartz)/ Silica Sand

Ammonia Acrylamide Acrylonitrile

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Calcium carbonate Titanium dioxide Propylene glycol

Zinc oxide

Cellulose



Revision Date: 06/08/2018

US. Rhode Island RTK

Chemical Identity

Calcium carbonate
Titanium dioxide
Propylene glycol
Zinc oxide
Cellulose

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

VOC:

Regulatory VOC (less water and

exempt solvent)

VOC Method 310

: 20 g/l

: 0.92 %

17/19



Revision Date: 06/08/2018

Inventory Status:

Australia AICS:

One or more components in this product are not listed on or exempt from the Inventory.

Canada DSL Inventory List:

One or more components in this product are

not listed on or exempt from the Inventory.

EINECS, ELINCS or NLP:

One or more components in this product are not listed on or exempt from the Inventory.

Japan (ENCS) List:

One or more components in this product are not listed on or exempt from the Inventory.

China Inv. Existing Chemical Substances:

One or more components in this product are

not listed on or exempt from the Inventory.

Korea Existing Chemicals Inv. (KECI): One or more components in this product are

not listed on or exempt from the Inventory.

Canada NDSL Inventory: One or more components in this product are

not listed on or exempt from the Inventory.

Philippines PICCS: One or more components in this product are

not listed on or exempt from the Inventory.

New Zealand Inventory of Chemicals:

One or more components in this product are

not listed on or exempt from the Inventory.

Japan ISHL Listing:

One or more components in this product are

not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are

not listed on or exempt from the Inventory.

US TSCA Inventory:

All components in this product are listed on or

exempt from the Inventory.

Mexico INSQ:

One or more components in this product are

not listed on or exempt from the Inventory.

Ontario Inventory: One or more components in this product are

not listed on or exempt from the Inventory.

Taiwan Chemical Substance Inventory: One or more components in this product are

not listed on or exempt from the Inventory.



Revision Date: 06/08/2018

16.Other information, including date of preparation or last revision

Revision Date: 06/08/2018

Version #: 1.2

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard

information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including

the safe use of the product under every foreseeable condition.