

Revision Date: 07/21/2018

# SAFETY DATA SHEET

## 1. Identification

Material name: AlphaGuard® MT Base Coat

Material: 351602 805

Recommended use and restriction on use

Recommended use: Coatings Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S. Roofing 3735 Green Road Beachwood OH 44122

US

Contact person:EH&S DepartmentTelephone:216-292-5000

**Emergency telephone number:** 1-800-424-9300 (US); 1-613-996-6666 (Canada)

# 2. Hazard(s) identification

#### **Hazard Classification**

#### **Health Hazards**

Acute toxicity (Inhalation - dust and Category 4

mist)

Respiratory sensitizer Category 1
Skin sensitizer Category 1
Carcinogenicity Category 1A

#### **Unknown toxicity - Health**

Acute toxicity, oral 12.43 %
Acute toxicity, dermal 36.67 %
Acute toxicity, inhalation, vapor
Acute toxicity, inhalation, dust 91.28 %

or mist

## **Label Elements**

## **Hazard Symbol:**





Revision Date: 07/21/2018

Signal Word: Danger

**Hazard Statement:** Harmful if inhaled.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

May cause cancer.

Precautionary Statements

**Prevention:** Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a

well-ventilated area. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective

equipment as required.

**Response:** IF INHALED: Remove person to fresh air and keep comfortable for

breathing. If experiencing respiratory symptoms: Call a POISON

CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Call a POISON CENTER/doctor if you feel unwell. Specific treatment (see on this label). Wash contaminated

clothing before reuse.

Storage: Store locked up.

**Disposal:** Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC):

None.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical Identity	CAS number	Content in percent (%)*
-------------------	------------	-------------------------



Revision Date: 07/21/2018

Aluminum hydroxide	21645-51-2	7 - 13%
Calcium carbonate	471-34-1	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	5 - 10%
Titanium dioxide	13463-67-7	3 - 7%
Polyvinyl chloride	9002-86-2	3 - 7%
Isophorone Diisocyanate	4098-71-9	1 - 5%
Zinc oxide	1314-13-2	1 - 5%
Calcium oxide	1305-78-8	0.5 - 1.5%
Carbon Black	1333-86-4	0.5 - 1.5%
Stearic acid	57-11-4	0.1 - 1%
Aluminum oxide	1344-28-1	0.1 - 1%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%

<sup>\*</sup> All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

## 4. First-aid measures

Ingestion: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

**Inhalation:** Call a physician or poison control center immediately. If breathing stops,

provide artificial respiration. Move to fresh air. If breathing is difficult, give

oxygen.

**Skin Contact:** If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly

clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an

allergic skin reaction develops, get medical attention.

Eye contact: Any material that contacts the eye should be washed out immediately with

water. If easy to do, remove contact lenses. If eye irritation persists: Get

medical advice/attention.

Most important symptoms/effects, acute and delayed

**Symptoms:** May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

**Treatment:** Symptoms may be delayed.

#### 5. Fire-fighting measures

**General Fire Hazards:** No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.



Revision Date: 07/21/2018

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

During fire, gases hazardous to health may be formed.

#### Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be

worn in case of fire.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled

material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning

up:

Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for

disposal according to local regulations.

**Notification Procedures:** In the event of a spill or accidental release, notify relevant authorities in

accordance with all applicable regulations.

**Environmental Precautions:** Avoid release to the environment. Prevent further leakage or spillage if safe

to do so. Do not contaminate water sources or sewer. Environmental

manager must be informed of all major spillages.

#### 7. Handling and storage

Precautions for safe handling:

Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage,

including any incompatibilities:

Store locked up.

#### 8. Exposure controls/personal protection

#### **Control Parameters**

Occupational Exposure Limits

Chemical Identity	Туре	Exposure Limit Values	Source
Aluminum hydroxide - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03



			2016)
Aluminum hydroxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
	TWA	50 millions of particles per cubic foot of air	US. ÓSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Aluminum hydroxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide Titanium dioxide - Total dust.	TWA PEL	10 mg/m3 15 mg/m3	US. ACGIH Threshold Limit Values (2011) US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	OSHA_AC T	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Isophorone Diisocyanate	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
Zinc oxide - Respirable fraction.	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	STEL	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Zinc oxide - Fume.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Zinc oxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Zinc oxide - Respirable	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air



fraction.			Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air
			Contaminants (29 CFR 1910.1000) (02 2006)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (2011)
Carbon Black	PEL	3.5 mg/m3	US. OSHA Table Z-1 Limits for Air
			Contaminants (29 CFR 1910.1000) (02 2006)
Stearic acid - Respirable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (03 2017)
Stearic acid - Inhalable fraction.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (03 2017)
Aluminum oxide - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air
			Contaminants (29 CFR 1910.1000) (02 2006)
Aluminum oxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air
			Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of	
		particles per	
		cubic foot of	
<del></del>		air	
Aluminum oxide - Respirable	TWA	15 millions of	
fraction.		particles per	
		cubic foot of	
	TWA	air 5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03
	IVVA	3 mg/ms	2016)
Aluminum oxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Hydrotreated heavy	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
naphthenic distillate -			,
Inhalable fraction.			
Hydrotreated heavy	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air
naphthenic distillate			Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air
naphthenic distillate - Mist.			Contaminants (29 CFR 1910.1000) (02 2006)



Chemical name	Туре	Exposure Limit Values	Source
Aluminum hydroxide - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Aluminum hydroxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Aluminum hydroxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Aluminum hydroxide - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Aluminum hydroxide - Inhalable fraction.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Aluminum hydroxide - Respirable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Aluminum hydroxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)



Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m	3 Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Titanium dioxide - Total dust.	TWA	10 mg/m	3 Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m	3 Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA	10 mg/m	3 Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m	3 Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Polyvinyl chloride - Respirable.	TWA	1 mg/m	3 Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m	Regulation Respecting the Quality of the Work Environment) (09 2017)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m	3 Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Zinc oxide - Respirable.	TWA	2 mg/m	Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	10 mg/m	3 Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Zinc oxide - Respirable fraction.	TWA	2 mg/m	3 Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m	3 Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Zinc oxide - Fume.	TWA	5 mg/m	3 Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	STEL	10 mg/m	3 Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)



Revision Date: 07/21/2018

Zinc oxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Carbon Black - Inhalable	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Carbon Black	TWA	3.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Hydrotreated heavy naphthenic distillate - Mist.	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical

ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

**General information:** Use personal protective equipment as required.

**Eye/face protection:** Wear goggles/face shield.

**Skin Protection** 

**Hand Protection:** Use suitable protective gloves if risk of skin contact.

Other: Wear chemical-resistant gloves, footwear, and protective clothing

appropriate for the risk of exposure. Contact health and safety professional

or manufacturer for specific information.

**Respiratory Protection:** If engineering controls do not maintain airborne concentrations below

recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an

approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter,

cartridge or canister. Contact health and safety professional or

manufacturer for specific information.

**Hygiene measures:** Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product. Contaminated work clothing should

not be allowed out of the workplace. Avoid contact with skin.



Revision Date: 07/21/2018

# 9. Physical and chemical properties

**Appearance** 

Physical state:liquidForm:liquidColor:Gray

Odor: Mild petroleum/solvent
Odor threshold: No data available.

pH: No data available.

Melting point/freezing point: No data available.

Initial boiling point and boiling range: No data available.

Flash Point: > 100 °C > 212 °F(Setaflash Closed Cup)

**Evaporation rate:** Slower than Ether

Flammability (solid, gas): No Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper (%):

No data available.

No data available.

No data available.

Vapor pressure:

No data available.

Vapor density: Vapors are heavier than air and may travel along the floor and

in the bottom of containers.

Relative density: 1.33

Solubility(ies)

Solubility in water: Practically Insoluble
Solubility (other): No data available.

Partition coefficient (n-octanol/water): No data available.

Auto-ignition temperature:No data available.Decomposition temperature:No data available.Viscosity:No data available.

## 10. Stability and reactivity

**Reactivity:** No data available.

**Chemical Stability:** Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.

**Conditions to avoid:** Avoid heat or contamination.

Incompatible Materials: Alcohols. Amines. Strong acids. Strong bases. Water, moisture.



Revision Date: 07/21/2018

**Hazardous Decomposition** 

**Products:** 

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.

# 11. Toxicological information

Information on likely routes of exposure

**Inhalation:** In high concentrations, vapors, fumes or mists may irritate nose, throat and

mucus membranes.

**Skin Contact:** Causes mild skin irritation. May cause an allergic skin reaction.

**Eye contact:** Eye contact is possible and should be avoided.

**Ingestion:** May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

**Inhalation:** No data available.

**Skin Contact:** No data available.

Eye contact: No data available.

**Ingestion:** No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

**Product:** ATEmix: 22,737.33 mg/kg

**Dermal** 

**Product:** ATEmix: 14,560.83 mg/kg

Inhalation

**Product:** ATEmix: 2.38 mg/l

Repeated dose toxicity

**Product:** No data available.

Skin Corrosion/Irritation

**Product:** No data available.

Specified substance(s):



Revision Date: 07/21/2018

Aluminum hydroxide in vivo (Rabbit): Not classified as an Irritant Experimental result, Key study

Calcium carbonate in vivo (Rabbit): Not irritant Experimental result, Key study

Titanium dioxide in vivo (Rabbit): Not irritant Experimental result, Supporting study

Zinc oxide in vivo (Rabbit): Not irritant Experimental result, Key study

Calcium oxide in vivo (Rabbit): Irritating Read-across from supporting substance (structural

analogue or surrogate), Key study

Carbon Black in vivo (Rabbit): Not irritant Experimental result, Key study

Stearic acid in vivo (Rabbit): Not irritant Experimental result, Key study

Aluminum oxide in vivo (Rabbit): Not irritant Experimental result, Key study

Hydrotreated heavy naphthenic distillate

in vivo (Rabbit): Not irritant Experimental result, Key study

#### Serious Eye Damage/Eye Irritation

**Product:** No data available.

Specified substance(s):

Aluminum hydroxide Rabbit, 24 hrs: Not irritating

Calcium carbonate Rabbit, 24 - 72 hrs: Not irritating

Titanium dioxide Rabbit, 24 hrs: Not irritating

Zinc oxide Rabbit, 24 - 72 hrs: Not irritating

Carbon Black Rabbit, 24 - 72 hrs: Not irritating

Stearic acid Rabbit, 27 - 72 hrs: Not irritating

Aluminum oxide Rabbit, 24 hrs: Not irritating

Hydrotreated heavy naphthenic distillate

Rabbit, 24 hrs: Not irritating

#### Respiratory or Skin Sensitization

**Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause sensitization by inhalation.

Carcinogenicity

**Product:** No data available.



Revision Date: 07/21/2018

#### IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Titanium dioxide Overall evaluation: Possibly carcinogenic to humans.

Carbon Black Overall evaluation: Possibly carcinogenic to humans.

Hydrotreated heavy Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall

naphthenic distillate evaluation: Carcinogenic to humans.

**US. National Toxicology Program (NTP) Report on Carcinogens:** 

Hydrotreated heavy Known To Be Human Carcinogen.

naphthenic distillate

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

**Germ Cell Mutagenicity** 

In vitro

**Product:** No data available.

In vivo

**Product:** No data available.

Reproductive toxicity

**Product:** No data available.

**Specific Target Organ Toxicity - Single Exposure** 

**Product:** No data available.

**Specific Target Organ Toxicity - Repeated Exposure** 

**Product:** No data available.

**Aspiration Hazard** 

**Product:** No data available.

Other effects: No data available.



Revision Date: 07/21/2018

# 12. Ecological information

## **Ecotoxicity:**

#### Acute hazards to the aquatic environment:

Fish

**Product:** No data available.

Specified substance(s):

Zinc oxide LC 50 (Fathead minnow (Pimephales promelas), 96 h): 2,246 mg/l Mortality

**Aquatic Invertebrates** 

**Product:** No data available.

Specified substance(s):

Titanium dioxide EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication

## Chronic hazards to the aquatic environment:

**Fish** 

**Product:** No data available.

Specified substance(s):

Hydrotreated heavy NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR QSAR,

naphthenic distillate Supporting study

**Aquatic Invertebrates** 

**Product:** No data available.

**Toxicity to Aquatic Plants** 

**Product:** No data available.

## **Persistence and Degradability**

Biodegradation

**Product:** No data available.

**BOD/COD Ratio** 

**Product:** No data available.

# **Bioaccumulative potential**

**Bioconcentration Factor (BCF)** 

**Product:** No data available.

# Partition Coefficient n-octanol / water (log Kow)

**Product:** No data available.

Specified substance(s):



Revision Date: 07/21/2018

Stearic acid Log Kow: 8.23

Mobility in soil: No data available.

Other adverse effects: No data available.

#### 13. Disposal considerations

**Disposal instructions:** Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Contaminated Packaging: No data available.

## 14. Transport information

#### TDG:

Not Regulated

#### CFR / DOT:

Not Regulated

#### IMDG:

Not Regulated

# 15. Regulatory information

## **US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

# US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Chemical Identity OSHA hazard(s)

Polyvinyl chloride Blood

Liver Cancer Flammability

Central nervous system

Vinyl chloride Blood

Liver

Flammability

Central nervous system

Cancer



Revision Date: 07/21/2018

## CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Propionic acid	5000 lbs.
Propylene oxide	100 lbs.
Dioctyl phthalate	100 lbs.

Ethylbenzene 1000 lbs. Naphthalene 100 lbs. Vinyl chloride 1 lbs.

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### **Hazard categories**

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard

## **SARA 302 Extremely Hazardous Substance**

#### Reportable

Chemical Identity	quantity	Threshold Planning Quantity
Iconhorone Diicocyanate	500 lbc	500 lbc

Isophorone Diisocyanate 500 lbs. 500 lbs. Propylene oxide 100 lbs. 10000 lbs.

## **SARA 304 Emergency Release Notification**

Chemical Identity Reportable quantity

Isophorone Diisocyanate

Zinc oxide

Propionic acid 5000 lbs. Propylene oxide 100 lbs.

Diisodecyl phthalate

(mixed Is)

Dioctyl phthalate 100 lbs.
Ethylbenzene 1000 lbs.
Naphthalene 100 lbs.
Vinyl chloride 1 lbs.



Revision Date: 07/21/2018

#### SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Isophorone Diisocyanate	500lbs
Propylene oxide	500lbs
Aluminum hydroxide	10000 lbs
Calcium carbonate	10000 lbs
Calcium Carbonate	10000 lbs
(Limestone)	
Titanium dioxide	10000 lbs
Polyvinyl chloride	10000 lbs
Zinc oxide	10000 lbs
Calcium oxide	10000 lbs
Carbon Black	10000 lbs
Stearic acid	10000 lbs
Aluminum oxide	10000 lbs
Hydrotreated heavy	10000 lbs

# SARA 313 (TRI Reporting)

# **Chemical Identity**

naphthenic distillate

Isophorone Diisocyanate

Zinc oxide

# Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

**Chemical Identity** Reportable quantity

Propylene oxide Ibs Vinyl chloride Ibs

## Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

## **US State Regulations**

# **US. California Proposition 65**



## **WARNING**

Cancer and Reproductive Harm - www.P65Warnings.ca.gov

## US. New Jersey Worker and Community Right-to-Know Act

## **Chemical Identity**

Calcium carbonate

Calcium Carbonate (Limestone)

Titanium dioxide

Polyvinyl chloride

Isophorone Diisocyanate

Zinc oxide

Carbon Black

Hydrotreated heavy naphthenic distillate



Revision Date: 07/21/2018

#### US. Massachusetts RTK - Substance List

# **Chemical Identity**

Calcium carbonate
Calcium Carbonate (Limestone)
Titanium dioxide
Isophorone Diisocyanate
Zinc oxide
Crystalline Silica (Quartz)/ Silica Sand
Propylene oxide

## US. Pennsylvania RTK - Hazardous Substances

#### **Chemical Identity**

Dioctyl phthalate

Calcium carbonate
Calcium Carbonate (Limestone)
Titanium dioxide
Isophorone Diisocyanate
Diisodecyl phthalate
Zinc oxide

## **US. Rhode Island RTK**

#### **Chemical Identity**

Aluminum hydroxide
Calcium carbonate
Calcium Carbonate (Limestone)
Titanium dioxide
Polyvinyl chloride
Isophorone Diisocyanate
Zinc oxide

# International regulations

# **Montreal protocol**

Not applicable

#### Stockholm convention

Not applicable

#### **Rotterdam convention**

Not applicable

#### **Kyoto protocol**

Not applicable

## VOC:

Regulatory VOC (less water and

exempt solvent)

VOC Method 310 : 0.64 %

: 10 g/l



Revision Date: 07/21/2018

**Inventory Status:** 

Australia AICS: One or more components in this product are

not listed on or exempt from the Inventory.

Canada DSL Inventory List: All components in this product are listed on or

exempt from the Inventory.

EINECS, ELINCS or NLP: One or more components in this product are

not listed on or exempt from the Inventory.

Japan (ENCS) List:

One or more components in this product are

not listed on or exempt from the Inventory.

China Inv. Existing Chemical Substances:

One or more components in this product are

not listed on or exempt from the Inventory.

Korea Existing Chemicals Inv. (KECI): One or more components in this product are

not listed on or exempt from the Inventory.

Canada NDSL Inventory: One or more components in this product are

not listed on or exempt from the Inventory.

Philippines PICCS: One or more components in this product are

not listed on or exempt from the Inventory.

US TSCA Inventory:

All components in this product are listed on or

exempt from the Inventory.

New Zealand Inventory of Chemicals:

One or more components in this product are

not listed on or exempt from the Inventory.

Japan ISHL Listing: One or more components in this product are

not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are

not listed on or exempt from the Inventory.

# 16.Other information, including date of preparation or last revision

**Revision Date:** 07/21/2018

Version #: 1.1

Further Information: No data available.



Revision Date: 07/21/2018

Disclaimer:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.