

LEED DATA SHEET

DATE:			
PROJECT NAME:			
PROJECT LOCATION:			
NAME OF PRODUCT:		POWERply Endure 320 Smooth	
DESCRIPTION:		Smooth surfaced SBS/RET/TPU modified bitumen membrane wind iberlass reinforcing fabric, and Roof-ID RFID chips.	th a nonwicking polyester &
PRODUCT/MATERIAL COST: \$		OST: \$	
·	·		·

SOLAR REFLECTIVITY INDEX (SRI)

PAVING & SLOPED ROOF >2:12 MUST BE AT LEAST 29:	N/A
LOW SLOPED ROOF MATERIALS MUST BE AT LEAST 78:	N/A

RECYCLED CONTENT

PRE-CONSUMER:	0	%
POST CONSUMER:	0	%

${\bf REGIONAL\ QUALIFICATIONS\ FOR\ PRODUCT/MATERIALS:}$

		DISTANCE FROM PROJECT:	MILES
LOCATION OF PROCESS:		DISTANCE FROM PROJECT:	MILES
LOCATION OF MANUFACTURE:	Cleveland, OH	DISTANCE FROM PROJECT:	MILES

LOW EMITTING MATERIALS:

COATING VOC (GRAMS/L)	SEALANT VOC (GRAMS/L)	ADHESIVE VOC (GRAMS/L)	USE OF MATERIAL	

RAPIDLY RENEWABLE MATERIAL:

PERCENT RENEWABLE:	0	%
COST: \$		

PREPARED BY:	

^{*}Extraction/Process/Manufacture is defined as the assembly of a final product not including on-site assembly or installation.

^{**}Due to several sources of raw materials for this product, specifying the origin of the component materials may not be possible.