Skylight Guards

A non-penetrating skylight fall protection system.

FEATURES

Meets or exceeds National and California OSHA regulations.

No drilling required; unique compression system fastens to skylight frame.

Does not compromise roof membrane or skylight weatherproofing.

Will not void your roof warranty.

Installs with basic tools in 30 minutes.

Constructed of 1/4" diameter 4" x 4" galvanized mesh.

Customizable sizes available.

Optional Skylight Demarcation Kit.

- BENEFITS
- Structural load: 400lbs. minimum, in any direction to all components in accordance with California OSHA Regulations.
- Non-penetrating design eliminates possibility of damage to the rooftop, that could result from drilling.
- Uncompromised rooftop while maintaining a safe work environment for your employees.
- Protection from injuries and falls while keeping roof warranty intact.
- Fast installation
- Designed to protect against injuries and deaths around skylight openings.
- Designed to fit a wide variety of skylight shapes and dimensions (square, rectangular, and flat)
- Provides visual location of skylights on rooftops (available for square, rectangular, and flat guards).





DESCRIPTION

TECHNICAL SUPPORT

TREMCO

Roofing & Building Maintenance

www.tremcoroofing.com 3735 Green Road Beachwood, Ohio 44122 1.800.852.6013

50 Beth Nealson Drive Toronto, Ontario M4H 1M6 1.800.668.9879 The Tremco Skylight Guard is specifically designed to protect against injuries and deaths around skylight openings. The non-penetrating design is available in customizable sizes and features a unique compression attachment system. It installs in minutes and since there is no drilling required, you'll keep your surfaces uncompromised while maintaining a safe work environment for your employees.

Your local Tremco Representative, working with the Technical Service Staff, can help analyze conditions and needs to develop recommendations for special applications.

Tremco is a US Registered trademark of Tremco Incorporated.

The information provided on this data page supersedes all previous data concerning this product and its application. The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCE SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.