TremLock® R Plus Panel

Exposed Fastener Panel

FEATURES

Optional purlin bearing leg

Multi-use

BENEFITS

- Adds support to fastening to panel lap
- Used in roof or wall applications



DESCRIPTION

TremLock "R" Plus Panels are a propietary version of the industry standard R-Panel and is a multi-use roof and wall rib panel. An optional purlin bearing leg (PBR) rests on purlins and provides support for fastening to the panel lap.

BASIC USES

TremLock 'R" Plus panel is an exposed roof and wall panel. TremLock "R" Plus panel can be used as an exterior wall cover or roof panel, excellent for use on screen walls, equipment screens and parapet wall applications. A variety of fastener options are available to meet the needs of appearance and different substrate attachment.

SYSTEM DESIGN

The TremLock "R" Plus Panel features 1 1/4" major ribs 12" on center and minor ribs 6" on center. Standard panel lengths up to 40'. Please inquire for longer lengths.

FINISH/COLOR

Acrylic Coated Galvalume®

Fluoropolymer (Kynar 500° PVDF resin-based)

Siliconized Polyester and Polyester


Oil canning is inherent in all metal panels and is not cause for panel rejection

APPLICATION


TremLock "R" Plus panel is an exposed fastener wall / roof panel used on slopes down to 1:12. Tape sealant is required on seam (side-laps).

PANEL PROFILES

Walls (Non-Purlin Bearing Leg):



Roofs (Purlin Bearing Leg):



Fastener Pattern (@ Eaves Ridges and Endlaps):



1/4-14 X 7/8" LAP TEK ZAC Fastener (1'-8" O.C. Max.)

3/32" X 1" Roll Tape Sealant (Required on 3:12 or less Slopes)

(@ Intermediate Purlins):



1/4-14 X 7/8" LAP TEK ZAC Fastener (1'-8" O.C. Max.)

3/32" X 1" Roll Tape Sealant (Required on 3:12 or less Slopes)

Faom Inside Closure: =

Faom Outside Clusure:

TremLock® R Plus Panel

UL 2218 Class 4

TESTING

TITLE OF TEST TEST METHOD

Uplift Testing UL 580 Class 90, ASTM E1592

Air & Water Infiltration E1646 and E1680

Impact Testing Fire Resistance UL 263 & UL 790 Class A

Florida Product Approval FL 1832.10 (non-structural roofing), FL 1747.8 (structural roofing)

Texas Windstorm RC-63 & RC-283

Your local Tremco Roofing representative can provide you with effective maintenance procedures, which may vary depending upon specific conditions. Periodic inspections, early repairs and preventive maintenance are all part of a sound roof program.

Users must read container labels and Safety Data Sheets for health and safety precautions prior to use.

Your local Tremco Representative, working with the Technical Service Staff, can help analyze conditions and needs to develop recommendations for special applications. The services of the Tremco Research Center, which has earned a unique reputation in weatherproofing technology, complement and extend the service of the Tremco Service Staff.

MAINTENANCE

PRECAUTIONS

TECHNICAL SUPPORT



Roofing & Building Maintenance

www.tremcoroofing.com 3735 Green Road Beachwood, Ohio 44122 1.800.852.6013

220 Wicksteed Avenue Toronto, Ontario, M4H 1G7 1.800.668.9879

Tremco Roofing and Building Maintenance is part of Tremco Construction Products Group.

Tremco is a US Registered trademark of Tremco CPG Inc. Tremco is a US Registered trademark of Tremco CPG Inc.
The information provided on this data page supersedes all previous data concerning this product and its application.
The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCE SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.