TremLock® Ultra-Rib Panel

Exposed fastener wall/roof panel

FEATURES

BENEFITS

Utility panel

• Wall, roof and liner



DESCRIPTION

TremLock Ultra-Rib roof & wall panel systems are factory roll formed 24 or 26 gauge Galvalume* steel, zinc coated by hot-dip process per ASTM A792/A792M. The Galvalume panel is coated with Kynar* 500 /Hylar* 5000. Refer to color chart for available colors.

BASIC USES

TremLock Ultra-Rib panel is an exposed fastener roof and wall panel. TremLock Ultra-Rib panel can be used as an exterior wall cover or roof panel, basic shade and shelter panel used on screen walls and parapet wall applications. A variety of fastener options are available to meet the needs of appearance and different substrate attachment.

SYSTEM DESIGN

TremLock Ultra-Rib panels are designed with a coverage of 36" and up to 40' in length with three major corrugations; ¾" high 9" on center with two minor corrugations between each of the major corrugations the entire length of panel. The TremLock Ultra-Rib can be installed on slopes down to 1:12. Tape sealant is required in seams (side-laps) on slopes 3:12 to 1:12.

FINISH/COLOR

Acrylic Coated Galvalume

Fluoropolymer (Kynar 500 PVDF resin-based)


Siliconized Polyester and Polyester

Oil canning is inherent in all metal panels and is not cause for rejection.

APPLICATION

TremLock Ultra-Rib panels are installed over plywood or purlins. All exposed fasteners shall be prepainted to match roof or wall panel colors. All side laps shall be at least one full corrugation. Panels are sealed at the base of wall with metal closures.

PANEL OPTIONS



PHYSICAL PROPERTIES

TITLE OF TEST	TEST METHOD
Uplift	UL 580 Class 90
Fire Resistance	UL 263 & UL 790 Class A
Impact Testing	UL 2218 Class 4
Florida Product Approval FL 1747.2 & FL 1832.3	
Texas Windstorm	RC-157

MAINTENANCE

Your local Tremco Roofing Sales Representative can provide you with effective maintenance procedures which may vary, depending upon specific conditions. Periodic inspections, early repairs and preventative maintenance are all part of a sound roof program.

PRECAUTIONS

Users must read container labels and Safety Data Sheets for health and safety precautions prior to use.

TECHNICAL SUPPORT

TremLock™ Ultra-Rib Panel

Your local Tremco Representative, working with the Technical Service Staff, can help analyze conditions and needs to develop recommendations for special applications. The services of the Tremco Research Center, which has earned a unique reputation in weatherproofing technology, complement and extend the service of the Tremco Service Staff.



Roofing & Building Maintenance

www.tremcoroofing.com 3735 Green Road Beachwood, Ohio 44122 1.800.852.6013

220 Wicksteed Avenue Toronto, Ontario, M4H 1G7 1.800.668.9879

Tremco Roofing and Building Maintenance is part of Tremco Construction Products Group. Tremco is a US Registered trademark of Tremco CPG Inc.

The information provided on this data page supersedes all previous data concerning this product and its application.

The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCE SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.