TremPly® TPO Bonding Adhesive

An Accessory Designed for TremPly TPO Single Ply Roof System

<text><text><text><text><text><text><text><text><text><text><text><text><text><text><text><text><text><text><text><text><text><text><text><text><text>

FEATURES

Fast-drying solvent system

Excellent coverage

Multiple application options

Quicker application

• Quick and easy application

BENEFITS

• Easy with roller or brush, spray application also possible

• Up to 70 sq ft/gallon of bonded membrane

High initial tack

Yellow

?

DESCRIPTION

TremPly® TPO Bonding Adhesive is a contact-type bonding adhesive specially designed for bonding TPO single ply roofing membranes and flashings to various roofing substrates.

BASIC USE

TremPly® TPO Bonding Adhesive is a general purpose, rubber-based bonding adhesive for attaching TPObased single-ply membranes to various substrates, including polyisocyanurate insulation and gypsum-based cover boards.

COLOR PACKAGING APPLICATION PHYSICAL PROPERTIES

5 gallon pails. Weight, 37 lbs per pail; 45 pails per pallet

TYPICAL VALUE
Synthetic polymer
Hydrocarbon blend
0°F (-18°C)
7.4 lbs Viscosity: 2,300 - 2,700 cps
50-70 sq. ft./gallon
25% +/- 2.5%
<704 g/l
1 year, unopened
Up to 60 minutes
5 - 15 minutes
Roller, brush, or spray

TremPly® TPO Bonding Adhesive

MAINTENANCE

PRECAUTIONS

TECHNICAL SUPPORT



Roofing & Building Maintenance www.tremcoroofing.com 3735 Green Road Beachwood, Ohio 44122 1.800.852.6013

220 Wicksteed Avenue Toronto, Ontario, M4H 1G7 1.800.668.9879 Tremco Roofing and Building Maintenance is part of Tremco Construction Products Group.

Your local Tremco Roofing representative can provide you with effective maintenance procedures, which may vary depending upon specific conditions. Periodic inspections, early repairs and preventive maintenance are all part of a sound roof program.

Users must read container labels and Safety Data Sheets for health and safety precautions prior to use.

Your local Tremco Representative, working with the Technical Service Staff, can help analyze conditions and needs to develop recommendations for special applications. The services of the Tremco Research Center, which has earned a unique reputation in weatherproofing technology, complement and extend the service of the Tremco Service Staff.

Tremco is a US Registered trademark of Tremco CPG Inc. The information provided on this data page supersedes all previous data concerning this product and its application. The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those and distance designed accurate the sight for each of the second data accurate on the headling accurate the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCE SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.