

# TREMCO SINGLE PLY ADHESIVE COVERAGE RATES

	Single Ply WB Adhesive	TPA LV Bonding Adhesive	TPO LV Bonding Adhesive (Vertical - Flashing)	TPO LV Bonding Adhesive (Horizontal)	TPA Bonding Adhesive (FB)	TPA Bonding Adhesive	TremFast SF Adhesive (FB only)
Coverage Rate (SQFT/Gallon) (Per Surface)	100-120	120	150-180	200-240	80-100	50-60	150
Applied to Back of Sheet & Substrate		✓	✓	✓		✓	
Applied to Substrate Only(FB)	✓			✓ **	✓		✓

\* Coverage rates depend on the porosity of the substrate being covered. For rougher surfaces, increase the coverage rate accordingly.

\*\*Coverage Rates for Fleece Backed system will be 100-120 SQ FT/ Gallon.

Coverage rates will increase during colder temperatures. Installer must be careful to not apply the adhesive in an excessive manner.

# TREMCO SINGLE PLY ADHESIVE REFERENCE GUIDE

ADHESIVE	TPA PERIMETER SHEETS	TPA FIELD SHEETS	TPA FLEECE BACK	TPA FLASHING	TPO PERIMETER SHEETS	TPO FIELD SHEETS	TPO FLEECE BACK	TPO FLASHING
SINGLE PLY WB ADHESIVE			✓				✓	
TPA LV ADHESIVE				✓				
TPO LV ADHESIVE					✓	✓	✓	✓
TPA BONDING ADHESIVE	✓	✓	✓	✓		✓	✓	✓
TREMFAS SF			✓				✓	