AlphaGuard[™] PUMA Cleaner

Clear methyl methacrylate cleaning liquid

DESCRIPTION **BASIC USES** PACKAGING COLOR **STORAGE LIFE**

AlphaGuard PUMA Cleaner is a clear, liquid methyl methacrylate cleaning agent.

AlphaGuard PUMA Cleaner is ideal for cleaning application tools used during AlphaGuard PUMA installations.

6 gallon (22.71 L)

Clear.

12 months shelf life in unopened containers when properly stored.

DO NOT FREEZE

Recommended storage is indoors in a ventilated, dry area removed from heat, open flame, ignition sources and direct sunlight. Storage temperatures should range from 60-70°F (15-21°C) and must not drop below 32°F (0°C) or exceed 110°F (43°C).

On the job site, materials should remain on the pallet until use and be stored in a shaded, ventilated area. Materials should be covered with a light-colored, reflective tarp for protection against the elements. Allow for adequate air flow inside the pallets.

Shelf life could be affected if the product is not stored properly.

APPLICATION

Usage: AlphaGuard PUMA Cleaner can be poured into a separate container and used to clean application tools used during AlphaGuard PUMA installations including paddle mixers detailing tools, etc. The cleaner can be reused several times until heavily soiled.

MAINTENANCE

PRECAUTIONS **TECHNICAL SUPPORT**



Roofing & Building Maintenance www.tremcoroofing.com 3735 Green Road Beachwood, Ohio 44122 1.800.852.6013

220 Wicksteed Avenue Toronto, Ontario, M4H 1G7 1.800.668.9879 Tremco Roofing and Building Maintenance is part of Tremco Construction Products Group.

Your local Tremco Roofing sales representative can provide you with effective maintenance procedures which may vary, depending upon specific conditions. Periodic inspections, early repairs and preventive maintenance are all part of a sound roof program.

Users must read container labels and Safety Data Sheets for health and safety precautions prior to use.

Your local Tremco Roofing sales representative, working with the Technical Service Staff, can help analyze conditions and needs to develop recommendations for special applications.

Tremco is a US Registered trademark of Tremco CPG Inc.

Tremco is a US Registered trademark of Tremco CPG Inc. The information provided on this data page supersedes all previous data concerning this product and its application. The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FINESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCE SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION. TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING