



- ① STANDARD FASCIA WILL NOT FUNCTION WITH TPO OR PVC STRIP-IN MEMBRANE THICKER THAN .060".
- ② OIL CANNING CAN OCCUR ON LARGER FACE HEIGHTS. RECOMMEND .050" OR .063" FOR FACE HEIGHTS ABOVE 8 1/4".
- ③ WELDED ACCESSORIES REQUIRE A MINIMUM OF MATERIAL THICKNESS OF .050"

NOTE: -- UNLESS OTHERWISE NOTED, FABRICATION OF MITERS AND ACCESSORIES ARE FURNISHED STANDARD.

TREMLOCK 200S FASCIA DIMENSIONS

PRODUCT ID. NO.	H DIM	X DIM	NAILER COVERAGE
<input type="checkbox"/> FA-50	5 1/4"	2 7/8"	1 NAILER
<input type="checkbox"/> FA-65	6 3/4"	4 3/8"	2 NAILERS
<input type="checkbox"/> FA-80	8 1/4"	5 7/8"	3 NAILERS
<input type="checkbox"/> FA-95	9 3/4"	7 3/8"	4 NAILERS
<input type="checkbox"/> FA-110	11 1/4"	8 7/8"	5 NAILERS
<input type="checkbox"/> FA-125	12 3/4"	10 3/8"	6 NAILERS

ANSI/SPRI/FM 4435/ ES-1
DESIGN PRESSURE

FA-50 TO FA-80 IN 24 GA. OR .040" - 196 psf
FA-50 TO FA-80 IN .050 OR .063" - 216 psf
FA-95 TO FA-125 IN .050 OR .063" - 116 psf

AUTHORIZED SIGNATURE:

APPROVED BY: _____

DATE: _____

MATERIAL:

___ 24 GA. GALV. STEEL ② ___ .050" ALUMINUM
___ .040" ALUMINUM ② ___ .063" ALUMINUM
___ OTHER _____

COLOR: _____ FINISH: _____

QUANTITIES:

___ LINEAL FEET 12'-0" LENGTHS
___ OUTSIDE MITER(S) @ 90°
___ INSIDE MITER(S) @ 90°
___ RIGHT ENDCAP(S)
___ LEFT ENDCAP(S)
___ RIGHT ENDWALL FLASHING(S)
___ LEFT ENDWALL FLASHING(S)
___ OVERFLOW SCUPPER(S) STYLE ___A___B
___ SPILLOUT SCUPPER(S) STYLE ___A___B
___ DOWNSPOUT SCUPPER(S) STYLE ___A___B
(___X___) SIZE A: TAPERED 1 1/2" DROP
 B: FLAT
FOR NON-90 MITERS SEE PRINT APPROVAL #60010-29179

SPECIFY ACCESSORY TYPE:
☐ WELDED ③
☐ STANDARD

PROJECT:

ARCHITECT:

ROOFING CONTRACTOR:

REPRESENTATIVE/DISTRIBUTOR:

TREMCO ROOFING AND BUILDING MAINTENANCE
3735 GREEN RD; BEACHWOOD, OH 44122

PHONE: 800-558-2162
EDGESYSTEMS@TREMCOINC.COM
WWW.TREMCOROOFING.COM

DATE: 07/18/18

DRN BY: JJC

CKD BY: SAK

SHT.# ___ OF ___

DWG# 60010-29242

A